

## Erratum to: Ductile failure modeling

Ahmed Amine Benzerga · Jean-Baptiste Leblond ·  
Alan Needleman · Viggo Tvergaard

Published online: 17 October 2016  
© Springer Science+Business Media Dordrecht 2016

**Erratum to: Int J Fract (2016) 201:29–80**  
**DOI 10.1007/s10704-016-0142-6**

Equations (8) and (9) are wrong. The correct expressions are

$$\dot{W}^P = (1 - f)\bar{\sigma}\dot{\epsilon} = \boldsymbol{\sigma} : \mathbf{D}^P \quad (8)$$

where  $\bar{\sigma}\dot{\epsilon}$  is the plastic dissipation rate per unit matrix material volume and

$$\dot{\Lambda} = \frac{(1 - f)\bar{\sigma}\dot{\epsilon}}{\boldsymbol{\sigma} : (\partial\Phi/\partial\boldsymbol{\sigma})} \quad (9)$$

---

The online version of the original article can be found under doi:[10.1007/s10704-016-0142-6](https://doi.org/10.1007/s10704-016-0142-6).

---

A. A. Benzerga  
Department of Aerospace Engineering, Texas A&M  
University, College Station, TX, USA

J.-B. Leblond  
Institut Jean le Rond d'Alembert, Sorbonne Universités,  
Université Pierre et Marie Curie, Paris, France

A. Needleman (✉)  
Department of Materials Science and Engineering,  
Texas A&M University, College Station, TX, USA  
e-mail: needle@tamu.edu

V. Tvergaard  
Department of Mechanical Engineering, The Technical  
University of Denmark, Lyngby, Denmark