



## Correction to: Machine Learning to Analyze Single-Case Data: A Proof of Concept

Marc J. Lanovaz<sup>1</sup> · Antonia R. Giannakakos<sup>2</sup> · Océane Destras<sup>3</sup>

Published online: 10 February 2021

© Association for Behavior Analysis International 2021

### Correction to: Perspectives on Behavior Science

<https://doi.org/10.1007/s40614-020-00244-0>

The equation on page 33 should be replaced by the following:

“We used R code to generate 20,000 AB graphs with three points in Phase A and five points in Phase B. The R code generated an eight-point data series for each graph using the equations:

$$y_t = x_t + c$$

$$\text{where } x_t = ax_{t-1} + \varepsilon_t$$

In the previous equations,  $y$  represented a univariate time series,  $t$  an index of time (i.e., one to eight),  $a$  the autocorrelation value,  $\varepsilon$  a normally distributed error term with a mean of 0 and a standard deviation of 1, and  $c$  a constant of 10 to avoid graphs with negative values.”

---

The online version of the original article can be found at <https://doi.org/10.1007/s40614-020-00244-0>

✉ Marc J. Lanovaz  
marc.lanovaz@umontreal.ca

<sup>1</sup> École de Psychoéducation, Université de Montréal, C.P. 6128, succursale Centre-Ville, Montreal, QC H3C 3J7, Canada

<sup>2</sup> Manhattanville College, Purchase, NY, USA

<sup>3</sup> Polytechnique Montréal, Montréal, QC, Canada