THE APPLICATION OF LEAST SQUARE IN PRECISION CYLINDRICAL GRINDING

Dawei Fu, Li Su, Yang Wang

School of Mechanical Engineering, Hebei University of Technology, China; Email: ffdww@163.com.

Abstract: In this paper, PMAC(Programmable Multi-Axis Controller) is used as machine tool CNC system to control linear motor's micro-movement and to achieve on-line measurement of part circularity error. The part circularity is calculated through least square method by measured circularity error. The part circularity error can be decreased by PID control of PMAC, so precision cylindrical grinding can be achieved.

Key words: PMAC(Programmable Multi-Axis Controller); PID control ; precision grinding, LSM(Least Square Method).

1. INTRODUCTION

As high-speed and super high-speed grinding can greatly improve grinding efficiency and machine-part manufacturing quality, it is a kind of technology of powerful vitality and vast range of prospects. It is devoted much attention by the advanced industry countries of the world. In this paper, a LSM is proposed to fulfill high-speed precision grinding of cylindrical parts based on PMAC system. The linear motor's micro-movement and electric spindle of machine tool are controlled by open controller PMAC. Also, a set of numerical control system of grinder is integrated. A good experimental result is gotten in this grinder to grind cylindrical parts.

This project is supported by Doctor foundation of Hebei education bureau under grant B2003205.

Please use the following format when citing this chapter:

Fu, Dawei, Su, Li, Wang, Yang, 2006, in International Federation for Information Processing (IFIP), Volume 207, Knowledge Enterprise: Intelligent Strategies In Product Design, Manufacturing, and Management, eds. K. Wang, Kovacs G., Wozny M., Fang M., (Boston: Springer), pp. 749-754.

2. SYSTEM INTEGRATION OF CNC GRINDER

As shown in Fig.1, this machine tool adopts two-axis PMAC to control linear motor and servo motor. At the same time electric spindle is cooled by circulatory water.

Fig.1 The principle of high-speed precision cylindrical grinding

3. THE MATHEMATICAL METHOD OF LEAST SQUARES CIRCLE OF CIRCULARITY ERROR

Figure2. The mathematical method of least squares circle of circle of circularity error.

As shown in fig.2, took the rotary center O_1 of the measured section as the center of a circle and divided the measured circle into m equal angles, radii $r_i (i=1,2,\dots,m)$ from the point O_1 can be obtained. The points of

intersection between these m radii r_i and the measured circle are P_i . At the pole coordinate of O_1 as the origin, let the center of least squares circle as O , the radius as R , the offset of least squares circle and rotary center as e . The radial offset from each discrete sampling point P_i to least squares circle as ϵ_i ($i=1,2 \dots m$), the angle of line O_1P_i from each equal sampling point P_i to rotary center O_1 and the axis of pole coordinate as θ_i ($i=1,2 \dots m$). The point of the intersection between line OP_i and the least squares circle is D . The radial error Δr_i from the center O_1 is collected by the sensor. From the Fig.2, it is obtained $OD=R$, $OO_1=e$, $P_iD=\epsilon_i$, $O_1P_i=r_i$, $\angle P_iO_1\rho=\theta_i$, $\angle OO_1\rho=\alpha$, $a=e\cos\alpha$, $b=e\sin\alpha$

Also:

$$\begin{aligned} r_i &= e \cos(\theta_i - \alpha) + [(R + \epsilon_i)^2 - e^2 \sin^2(\theta_i - \alpha)]^{1/2} \\ &= e \cos\theta_i \cos\alpha + e \sin\theta_i \sin\alpha + [(R + \epsilon_i)^2 - e^2 \sin^2(\theta_i - \alpha)]^{1/2} \end{aligned} \quad (1)$$

Make the non-linear function $[(R + \epsilon_i)^2 - e^2 \sin^2(\theta_i - \alpha)]^{1/2}$ linear.

$$\text{Let } f(e) = [(R + \epsilon_i)^2 - e^2 \sin^2(\theta_i - \alpha)]^{1/2}$$

$$\text{By means of Maclaurin formula: } f(x) = \sum_{n=0}^{\infty} \frac{1}{n!} f^{(n)}(0) X^n$$

$$f(e) = R + \epsilon_i - \frac{e^2}{2(R + \epsilon_i)} \sin^2(\theta_i - \alpha) - \frac{e^4}{8(R + \epsilon_i)^3} \sin^4(\theta_i - \alpha) \quad (2)$$

If $e \ll R$, and $\sin^2(\theta_i - \alpha) \ll 1$

Therefore $f(e) \approx R + \epsilon_i$ where the maximum error caused is $\frac{e^2}{2(R + \epsilon_i)}$.

$$\text{Accordingly: } r_i = R + a \cos\theta_i + b \sin\theta_i + \epsilon_i \quad i=1,2 \dots m \quad (3)$$

The structural matrix of data is:

$$\theta = \begin{bmatrix} 1 & 1 & \dots & 1 \\ \cos \theta_1 & \cos \theta_2 & \dots & \cos \theta_m \\ \sin \theta_1 & \sin \theta_2 & \dots & \sin \theta_m \end{bmatrix}^T$$

Coefficient matrix of normal equations is:

$$A = \theta^T \theta = \begin{bmatrix} M & \sum_i \cos \theta_i & \sum_i \sin \theta_i \\ \sum_i \cos^2 \theta_i & \sum_i \cos \theta_i \sin \theta_i & \sum_i \sin^2 \theta_i \end{bmatrix}$$

As m is even number

$$\text{Therefore } A = \text{diag}[m, m/2, m/2]$$

$$A^{-1} = \text{diag}[1/m, 2/m, 2/m]$$

$$\text{Let } D = [r_1, r_2, \dots, r_m]^T$$

So constant matrix of normal equations is:

$$B = \theta^T D = [\sum r_i, \sum r_i \cos \theta_i, \sum r_i \sin \theta_i]^T$$

$$\text{Let } P = [R, a, b]^T$$

$$\text{So } P = A^{-1}B = \left[\frac{1}{m} \sum r_i, \frac{2}{m} \sum r_i \cos \theta_i, \frac{2}{m} \sum r_i \sin \theta_i \right]^T$$

That is: $R = \frac{\sum_i r_i}{m} = r_0 + \Delta R$, where $\Delta R = \frac{1}{m} \sum \Delta r_i$

$$a = \frac{2}{m} \sum_i r_i \cos \theta_i = \frac{2}{m} \sum \Delta r_i \cos \theta_i$$

similarly: $b = \frac{2}{m} \sum \Delta r_i \sin \theta_i$

So $\varepsilon_i = r_i - R - a \cos \theta_i - b \sin \theta_i \quad i=1,2, \dots, m$

Or $\varepsilon_i = \Delta r_i - \Delta R - a \cos \theta_i - b \sin \theta_i$

So the circularity error of workpiece is:

$$f_o = \max\{\varepsilon_i\} - \min\{\varepsilon_i\}$$

$$= \max\{\Delta r_i - a \cos \theta_i - b \sin \theta_i\} - \min\{\Delta r_i - a \cos \theta_i - b \sin \theta_i\}$$

$i=1,2, \dots, m$

4. THE PID CONTROL PRINCIPLE OF PMAC

This numerical control grinder adopts two-axis PMAC with which we can control Z-phase servomotor and X-phase linear motor's feed movement. The sensor collects workpiece circularity error signals by A/D channel on the PMAC. We can attain the error on a certain intersection of workpiece. Comparing this error with tolerance of workpiece, we can figure out deviation and decide the linear motor's feed in accordance with this deviation. Finally we can attain precise machining accuracy of workpiece by many times circle count (as shown in Fig.3). Different speeds of rotation of electric-spindle are achieved by D/A channel on PMAC. The travel limits

switch and the cooling water for electric-spindle are controlled by I/O channel on the PMAC.

Fig.3 P.I.D Servo Loop

5. CONCLUSIONS

This paper adopts PMAC to accomplish the precision machining for grinding. The feature of PMAC is that it can control two different types of motors to accomplish coordinate motion of two axis, and it can realize some special functions such as precise linear and circle interpolator, "S-Curve" acceleration and deceleration. Thus it can fulfill high precision grinding for cylindrical, elliptical, taper contours and other kinds of irregular machine ones.

6. REFERENCES

1. Zhang Yu: Computer Aided Precise Measurement.(Northeastern University Press, China,1993).
2. Francis.T.Farago: *Abrasive Methods Engineering*. (Industrial Press, Americal,1995).
3. Wang,YongZhang etc: Numerical Control for Machine Tool.(Harbin Institute of Technology Press,China,1995).
4. Pmac User'S Manual.(DELTA TAU Data System, Inc.1998).