Predicate Abstraction via Symbolic Decision Procedures

Shuvendu K. Lahiri, Thomas Ball, and Byron Cook

Microsoft Research

{shuvendu, tball, bycook}@microsoft.com

Abstract. We present a new approach for performing predicate abstraction based on *symbolic decision procedures*. A symbolic decision procedure for a theory T (SDP_T) takes sets of predicates G and E and symbolically executes a decision procedure for T on $G' \cup \{\neg e \mid e \in E\}$, for all the subsets G' of G . The result of SDP_T is a shared expression (represented by a directed acyclic graph) that implicitly represents the answer to a predicate abstraction query.

We present symbolic decision procedures for the logic of Equality and Uninterpreted Functions (EUF) and Difference logic (DIF) and show that these procedures run in pseudo-polynomial (rather than exponential) time. We then provide a method to construct SDP 's for simple mixed theories (including EUF + DIF) using an extension of the Nelson-Open combination method. We present preliminary evaluation of our procedure on predicate abstraction benchmarks from device driver verification in SLAM.

1 Introduction

Predicate abstraction is a technique for automatically creating finite abstract models of finite and infinite state systems [10]. The method has been widely used in abstracting finite-state models of programs in SLAM [2] and numerous other software verification projects [11, 4]. It has also been used for synthesizing loop invariants [9] and verifying distributed protocols [8, 13].

The fundamental operation in predicate abstraction can be summarized as follows: Given a set of predicates P describing some set of properties of the system state, and a formula e , compute the weakest Boolean formula $\mathcal{F}_P(e)$ over the predicates P that implies e ¹. Most implementations of predicate abstraction [10, 2] construct $\mathcal{F}_P(e)$ by collecting the set of cubes (a conjunction of the predicates or their negations) over P that imply e . The implication is checked using a first-order theorem prover. This method may require making a very large ($2^{|P|}$ in the worst case) number of calls to a theorem prover and can be expensive.

¹ The dual of this problem, which is to compute the strongest Boolean formula $\mathcal{G}_P(e)$ that is implied by e , can be expressed as $\neg \mathcal{F}_P(\neg e)$.

Several techniques have been suggested to improve the performance of predicate abstraction. Some techniques enumerate the cubes over P in an increasing order of size [8, 9, 18]. However, these techniques still require an exponential number of theorem prover calls in the worst case, and demonstrate worst case behavior in practice. Other techniques sacrifice precision to gain efficiency, by only considering cubes of some fixed length [2].

Alternately, predicate abstraction can be formulated as a quantifier elimination problem. Lahiri et al. [13] and Clarke et al. [5] perform predicate abstraction by reducing the problem to Boolean quantifier elimination. The former method first transforms a first-order quantifier elimination problem into Boolean quantifier elimination by encoding first-order formulas into Boolean formulas; the latter assumes a finite representation of integers. The method in [13] first converts the quantifier-free first-order formula to a Boolean formula such that the translation preserves the set of satisfying assignments of the Boolean variables in the original variable. Both these techniques use incremental Boolean Satisfiability (SAT) techniques [5, 14] to perform the Boolean quantifier elimination. Namjoshi and Kurshan [15] also proposed using quantifier elimination for first-order logic directly to perform predicate abstraction — however many theories (such as the theory of Equality with Uninterpreted Functions) do not admit quantifier elimination.

Most of the above approaches use decision procedures or SAT solvers as “black boxes”, at best in an incremental fashion, to perform predicate abstraction. We believe that having a customized procedure for predicate abstraction can help improve the efficiency of predicate abstraction on large problems.

We propose a new way to perform predicate abstraction based on *symbolic decision procedures*. A symbolic decision procedure for a theory T (SDP_T) takes sets of predicates G and E and symbolically executes a decision procedure for T on $G' \cup \{\neg e \mid e \in E\}$, for all the subsets G' of G . The output of $SDP_T(G, E)$ is a shared expression (an expression where common subexpressions can be shared) representing those subsets $G' \subseteq G$, for which $G' \cup \{\neg e \mid e \in E\}$ is unsatisfiable. We show that such a procedure can be used to compute $\mathcal{F}_P(e)$ for performing predicate abstraction.

We present symbolic decision procedures for the logic of Equality and Uninterpreted Functions (EUF) and Difference logic (DIF) and show that these procedures run in polynomial and pseudo-polynomial time respectively, and therefore produce compact shared expressions. We provide a method to construct SDP for a combination of two simple theories $T_1 \cup T_2$ (including $EUF + DIF$), by using an extension of the Nelson-Oppen combination method. We use Binary Decision Diagrams (BDDs) [3] to construct $\mathcal{F}_P(e)$ from the shared representations efficiently in practice. The proofs for the theorems and lemmas can be found in a detailed technical report [12].

We present a preliminary evaluation of our procedure on predicate abstraction benchmarks from device driver verification in SLAM, and show that our method outperforms existing methods for doing predicate abstraction.

2 Setup

Figure 1 defines the syntax of a quantifier-free fragment of first-order logic. An expression in the logic can either be a *term* or a *formula*. A *term* can either be a variable or an application of a function symbol to a list of terms. A *formula* can be the constants **true** or **false** or an atomic formula or Boolean combination of other formulas. Atomic formulas can be formed by an equality between terms or by an application of a predicate symbol to a list of terms.

$$\begin{aligned}
 \text{term} &::= \text{variable} \mid \text{function-symbol}(\text{term}, \dots, \text{term}) \\
 \text{formula} &::= \mathbf{true} \mid \mathbf{false} \mid \text{atomic-formula} \\
 &\quad \mid \text{formula} \wedge \text{formula} \mid \text{formula} \vee \text{formula} \mid \neg \text{formula} \\
 \text{atomic-formula} &::= \text{term} = \text{term} \mid \text{predicate-symbol}(\text{term}, \dots, \text{term})
 \end{aligned}$$

Fig. 1. Syntax of a quantifier-free fragment of first-order logic

The function and predicate symbols can either be *uninterpreted* or can be defined by a particular theory. For instance, the theory of integer linear arithmetic defines the function-symbol “+” to be the addition function over integers and “<” to be the comparison predicate over integers. If an expression involves function or predicate symbols from multiple theories, then it is said to be an expression over *mixed* theories.

A formula F is said to be *satisfiable* if it is possible to assign values to the various symbols in the formula from the domains associated with the theories to make the formula **true**. A formula is *valid* if $\neg F$ is not satisfiable (or unsatisfiable). We say a formula A *implies* a formula B ($A \Rightarrow B$) if and only if $(\neg A) \vee B$ is valid.

We define a *shared expression* to be a Directed Acyclic Graph (DAG) representation of an expression where common subexpressions can be shared, by using names to refer to common subexpressions. For example, the intermediate variable t refers to the expression e_1 in the shared expression “**let** $t = e_1$ **in** $(e_2 \wedge t) \vee (e_3 \wedge \neg t)$ ”.

2.1 Predicate Abstraction

A *predicate* is an atomic formula or its negation². If G is a set of predicates, then we define $\widehat{G} \doteq \{\neg g \mid g \in G\}$, to be the set containing the negations of the predicates in G . We use the term “predicate” in a general sense to refer to any atomic formula or its negation and should not be confused to only mean the set of predicates that are used in predicate abstraction.

Definition 1. For a set of predicates P , a *literal* l_i over P is either a predicate p_i or $\neg p_i$, where $p_i \in P$. A *cube* c over P is a conjunction of literals. A *clause*

² We always use the term “predicate symbol” (and not “predicate”) to refer to symbols like “<”.

cl over P is a disjunction of literals. Finally, a minterm over P is a cube with $|P|$ literals, and exactly one of p_i or $\neg p_i$ is present in the cube.

Given a set of predicates $P \doteq \{p_1, \dots, p_n\}$ and a formula e , the main operation in predicate abstraction involves constructing the *weakest* Boolean formula $\mathcal{F}_P(e)$ over P such that $\mathcal{F}_P(e) \Rightarrow e$. The expression $\mathcal{F}_P(e)$ can be expressed as the set of all the minterms over P that imply e :

$$\mathcal{F}_P(e) = \bigvee \{c \mid c \text{ is a minterm over } P \text{ and } c \text{ implies } e\} \quad (1)$$

Proposition 1. *For a set of predicates P and a formula e , (i) $\mathcal{F}_P(\neg e) \Rightarrow \neg \mathcal{F}_P(e)$, (ii) $\mathcal{F}_P(e_1 \wedge e_2) \Leftrightarrow \mathcal{F}_P(e_1) \wedge \mathcal{F}_P(e_2)$, and (iii) $\mathcal{F}_P(e_1) \vee \mathcal{F}_P(e_2) \Rightarrow \mathcal{F}_P(e_1 \vee e_2)$ (refer to [12] for proofs).*

The operation $\mathcal{F}_P(e)$ does not distribute over disjunctions. Consider the example where $P \doteq \{x \neq 5\}$ and $e \doteq x < 5 \vee x > 5$. In this case, $\mathcal{F}_P(e) = x \neq 5$. However $\mathcal{F}_P(x < 5) = \mathbf{false}$ and $\mathcal{F}_P(x > 5) = \mathbf{false}$ and thus $(\mathcal{F}_P(x < 5) \vee \mathcal{F}_P(x > 5))$ is not the same as $\mathcal{F}_P(e)$.

The above properties suggest that one can adopt a two-tier approach to compute $\mathcal{F}_P(e)$ for any formula e :

1. Convert e into an equivalent Conjunctive Normal Form (CNF), which comprises of a conjunction of clauses, i.e., $e \equiv (\bigwedge_i cl_i)$.
2. For each clause $cl_i \doteq (e_1^i \vee e_2^i \dots \vee e_m^i)$, compute $r_i \doteq \mathcal{F}_P(cl_i)$ and return $\mathcal{F}_P(e) \doteq \bigwedge_i r_i$.

We focus here on computing $\mathcal{F}_P(\bigvee_{e_i \in E} e_i)$ when e_i is a predicate. Unless specified otherwise, we always use e to denote $(\bigvee_{e_i \in E} e_i)$, a disjunction of predicates in the set E in the sequel. For converting a formula to an equivalent CNF efficiently, we can use the method proposed by McMillan [14].

3 Symbolic Decision Procedures (SDP)

We now show how to perform predicate abstraction using symbolic decision procedures. We start by describing a saturation-based decision procedure for a theory T and then use it to describe the meaning of a symbolic decision procedure for the theory T . Finally, we show how a symbolic decision procedure can yield a shared expression of $\mathcal{F}_P(e)$ for predicate abstraction.

$$\begin{array}{c}
 \frac{X = Y}{Y = X} \\
 \\
 \frac{X = Y \quad Y = Z}{X = Z}
 \end{array}
 \qquad
 \begin{array}{c}
 \frac{X = Y \quad X \neq Y}{\perp} \\
 \\
 \frac{X_1 = Y_1 \quad \dots \quad X_n = Y_n}{f(X_1, \dots, X_n) = f(Y_1, \dots, Y_n)}
 \end{array}$$

Fig. 2. Inference rules for theory of equality and uninterpreted functions

A set of predicates G (over theory T) is unsatisfiable if the formula $(\bigwedge_{g \in G} g)$ is unsatisfiable. For a given theory T , the decision procedure for T takes a set of predicates G in the theory and checks if G is unsatisfiable. A theory is defined by a set of *inference rules*. An inference rule R is of the form:

$$\frac{A_1 \quad A_2 \quad \dots \quad A_n}{A} \quad (\text{R})$$

which denotes that the predicate A can be derived from predicates $A_1, \dots, A_n$ in one step. Each theory has least one inference rule for deriving *contradiction* ($\perp$). We also use $g : - g_1, \dots, g_k$ to denote that the predicate g (or $\perp$, where $g = \perp$) can be derived from the predicates $g_1, \dots, g_k$ using one of the inference rules in a single step. Figure 2 describes the inference rules for the theory of Equality and Uninterpreted Functions.

3.1 Saturation Based Decision Procedures

Consider a simple saturation-based procedure DP_T shown in Figure 3, that takes a set of predicates G as input and returns SATISFIABLE or UNSATISFIABLE.

The algorithm maintains two sets: (i) W is the set of predicates derived from G up to (and including) the current iteration of the loop in step (2); (ii) W' is the set of all predicates derived before the current iteration. These sets are initialized in step (1). During each iteration of step (2), if a new predicate g can be derived from a set of predicates $\{g_1, \dots, g_k\} \subseteq W'$, then g is added to W . The loop terminates after a bound $derivDepth_T(G)$. In step (3), we check if *any* subset of facts in W can derive contradiction. If such a subset exists, the algorithm returns UNSATISFIABLE, otherwise it returns SATISFIABLE.

The parameter $d \doteq derivDepth_T(G)$ is a bound (that is determined solely by the set G for the theory T) such that if the loop in step (2) is repeated for at least d steps, then $DP_T(G)$ returns UNSATISFIABLE if and only if G is unsatisfiable. If such a bound exists for any set of predicates G in the theory, then DP_T procedure implements a decision procedure for T .

Definition 2. A theory T is called a *saturation theory*, if the procedure DP_T described in Figure 3 implements a decision procedure for T .

In the rest of the paper, we only consider saturation theories. To show that a theory T is a saturation theory, it suffices to consider a decision procedure algorithm for T (say A_T) and show that DP_T implements A_T . This can be shown by deriving a bound on $derivDepth_T(G)$ for any set G in the theory.

3.2 Symbolic Decision Procedure

For a (saturation) theory T , a symbolic decision procedure for T (SDP_T) takes sets of predicates G and E as inputs, and symbolically simulates DP_T on $G' \cup \tilde{E}$, for every subset $G' \subseteq G$. The output of $SDP_T(G, E)$ is a symbolic expression representing those subsets $G' \subseteq G$, such that $G' \cup \tilde{E}$ is unsatisfiable. Thus with $|G| = n$, a single run of SDP_T symbolically executes 2^n runs of DP_T .

1. Initialize $W \leftarrow G$. $W' \leftarrow \{\}$.
2. For $i = 1$ to $\text{derivDepth}_T(G)$:
 - (a) Let $W' \leftarrow W$.
 - (b) For every fact $g \notin W'$, if $(g : -g_1, \dots, g_k)$ and $g_m \in W'$ for all $m \in [1, k]$:
 - $W \leftarrow W \cup \{g\}$.
3. If $(\perp : -g_1, \dots, g_k)$ and $g_m \in W$ for all $m \in [1, k]$:
 - return UNSATISFIABLE
4. else return SATISFIABLE

Fig. 3. $DP_T(G)$: A simple saturation-based procedure for theory T

We introduce a set of Boolean variables $B_G \doteq \{b_g \mid g \in G\}$, one for each predicate in G . An assignment $\sigma : B_G \rightarrow \{\text{true}, \text{false}\}$ over B_G uniquely represents a subset $G' \doteq \{g \mid \sigma(b_g) = \text{true}\}$ of G .

Figure 4 presents the symbolic decision procedure for a theory T , which symbolically executes the saturation based decision procedure DP_T on all possible subsets of the input component G . Just like the DP_T algorithm, this procedure also has three main components: *initialization*, *saturation* and *contradiction* detection. The algorithm also maintains sets W and W' , as the DP_T algorithm does.

Since $SDP(G, E)$ has to execute $DP_T(G' \cup \tilde{E})$ on all $G' \subseteq G$, the number of steps to iterate the saturation loop equals the maximum $\text{derivDepth}_T(G' \cup \tilde{E})$ for any $G' \subseteq G$. For a set of predicates S , we define the bound $\text{maxDerivDepth}_T(S)$ as follows:

$$\text{maxDerivDepth}_T(S) \doteq \max\{\text{derivDepth}_T(S') \mid S' \subseteq S\}$$

During the execution, the algorithm constructs a set of shared expressions with the variables over B_G as the leaves and temporary variables $t[\cdot]$ to name intermediate expressions. We use $t[(g, i)]$ to denote the expression for the predicate g after the iteration i of the loop in step (2) of the algorithm. We use $t[(g, \top)]$ to denote the top-most expression for g in the shared expression. Below, we briefly describe each of the phases of SDP_T :

Initialization [Step (1)]. The set W is initialized to $G \cup \tilde{E}$ and W' to $\{\}$. The leaves of the shared expression symbolically encode each subset $G' \cup \tilde{E}$, for every $G' \subseteq G$. For each $g \in G$, the leaf $t[(g, 0)]$ is set to b_g . For any $e_i \in E$, since $\neg e_i$ is present in all possible subset $G' \cup \tilde{E}$, we replace the leaf for $\neg e_i$ with **true**.

Saturation [Step (2)]. For each predicate g , $S(g)$ is the set of derivations of g from predicates in W' during any iteration. For any predicate g , we first add all the ways to derive g until the previous steps by adding $t[(g, i - 1)]$ to $S(g)$. Every time g can be derived from some set of facts $g_1, \dots, g_k$ such that each g_j is in W' , we add this derivation to $S(g)$ in Equation 2. At the end of the iteration i , $t[(g, i)]$ and $t[(g, \top)]$ are updated with the set of derivations in $S(g)$. The loop is executed $\text{maxDerivDepth}_T(G \cup \tilde{E})$ times.

Contradiction [Steps (3,4)]. We know that if $G' \cup \tilde{E}$ is unsatisfiable, then G' implies e (recall, e stands for $\bigvee_{e_i \in E} e_i$). Therefore, each derivation of $\perp$

1. Initialization
 - (a) $W \leftarrow G \cup \tilde{E}$ and $W' \leftarrow \{\}$.
 - (b) For each $g \in G$, $t[(g, 0)] \leftarrow b_g$.
 - (c) For each $e_i \in E$, $t[(\neg e_i, 0)] \leftarrow \mathbf{true}$.
2. For $i = 1$ to $\maxDerivDepth_T(G \cup \tilde{E})$ do:
 - (a) $W' \leftarrow W$.
 - (b) Initialize $S(g) = \{\}$, for any predicate g .
 - (c) For every $g \in W'$, $S(g) \leftarrow S(g) \cup \{t[(g, i - 1)]\}$.
 - (d) For every g , if $(g : -g_1, \dots, g_k)$ and $g_m \in W'$ for all $m \in [1, k]$:
 - i. Update the set of derivations of g at this level:

$$S(g) \leftarrow S(g) \cup \left\{ \left(\bigwedge_{m \in [1, k]} t[(g_m, i - 1)] \right) \right\} \quad (2)$$

- ii. $W \leftarrow W \cup \{g\}$.
 - (e) For each $g \in W$: $t[(g, i)] \leftarrow \bigvee_{d \in S(g)} d$
 - (f) For each $g \in W$, $t[(g, \top)] \leftarrow t[(g, i)]$
3. Check for contradiction:
 - (a) Initialize $S(e) = \{\}$.
 - (b) For every $\{g_1, \dots, g_k\} \subseteq W$, if $(\perp : -g_1, \dots, g_k)$ then

$$S(e) \leftarrow S(e) \cup \left\{ \left(\bigwedge_{m \in [1, k]} t[(g_m, \top)] \right) \right\} \quad (3)$$

- (c) Create the derivations for the goal e as $t[e] \leftarrow \left(\bigvee_{d \in S(e)} d \right)$

4. Return the shared expression for $t[e]$.

Fig. 4. Symbolic decision procedure $SDP_T(G, E)$ for theory T . The expression e stands for $\bigvee_{e_i \in E} e_i$.

from predicates in W gives a new derivation of e . The set $S(e)$ collects these derivations and constructs the final expression $t[e]$, which is returned in step (4).

The output of the procedure is the shared expression $t[e]$. The leaves of the expression are the variables in B_G . The only operations in $t[e]$ are conjunction and disjunction; $t[e]$ is thus a Boolean expression over B_G . We now define the evaluation of a (shared) expression with respect to a subset $G' \subseteq G$.

Definition 3. For any expression $t[x]$ whose leaves are in set B_G , and a set $G' \subseteq G$, we define $eval(t[x], G')$ as the evaluation of $t[x]$, after replacing each leaf b_g of $t[x]$ with **true** if $g \in G'$ and with **false** otherwise.

The following theorem explains the correctness of the symbolic decision procedure.

Theorem 1. If $t[e] \doteq SDP_T(G, E)$, then for any set of predicates $G' \subseteq G$, $eval(t[e], G') = \mathbf{true}$ if and only if $DP_T(G' \cup \tilde{E})$ returns UNSATISFIABLE.

Corollary 1. *For a set of predicates P , if $t[e] \doteq SDP_T(P \cup \tilde{P}, E)$, then for any $P' \subseteq (P \cup \tilde{P})$ representing a minterm over P (i.e. $p_i \in P' \text{ iff } \neg p_i \notin P'$), $eval(t[e], P') = eval(\mathcal{F}_P(e), P')$.*

Hence $t[e]$ is a shared expression for $\mathcal{F}_P(e)$, where e denotes $\bigvee_{e_i \in E} e_i$. An explicit representation of $\mathcal{F}_P(e)$ can be obtained by first computing $t[e] \doteq SDP_T(P \cup \tilde{P}, E)$ and then enumerating the cubes over P that make $t[e]$ **true**.

In the following sections, we will instantiate T to be the EUF and DIF theories and show that SDP_T exists for such theories. For each theory, we only need to determine the value of $maxDerivDepth_T(G)$ for any set of predicates G .

Remark 1. It may be tempting to terminate the loop in step (2) of $SDP_T(G, E)$ once the set of predicates in W does not change across two iterations. However, this would lead to an incomplete procedure and the following example demonstrates this.

Example 1. Consider an example where G contains a set of predicates that denotes an “almost” fully connected graph over vertices $x_1, \dots, x_n$. G contains an equality predicate between every pair of variables except the edge between x_1 and x_n . Let $E \doteq \{x_1 = x_n\}$.

After one iteration of the SDP_T algorithm on this example, W will contain an equality between every pair of variables including x_1 and x_n since $x_1 = x_n$ can be derived from $x_1 = x_i, x_i = x_n$, for every $1 < i < n$. Therefore, if the SDP_T algorithm terminates once the set of predicates in W terminates, the procedure will terminate after two steps.

Now, consider the subset $G' = \{x_1 = x_2, x_2 = x_3, \dots, x_i = x_{i+1}, \dots, x_{n-1} = x_n\}$ of G . For this subset of G , $DP_T(G' \cup \tilde{E})$ requires $lg(n) > 1$ (for $n > 2$) steps to derive the fact $x_1 = x_n$. Therefore $SDP_T(G, E)$ does not simulate the action of $DP_T(G' \cup \tilde{E})$. More formally, we can show that $eval(t[e], G') = \text{false}$, but $G' \cup \tilde{E}$ is unsatisfiable.

3.3 SDP for Equality and Uninterpreted Functions

The terms in this logic can either be variables or application of an uninterpreted function symbol to a list of terms. A predicate in this theory is $t_1 \sim t_2$, where t_i is a term and $\sim \in \{=, \neq\}$. For a set G of EUF predicates, $G_=_$ and $G_{\neq}$ denote the set of equality and disequality predicates in G , respectively. Figure 2 describes the inference rules for this theory.

Let $terms(\phi)$ denote the set of syntactically distinct terms in an expression (a term or a formula) ϕ . For example, $terms(f(h(x)))$ is $\{x, h(x), f(h(x))\}$. For a set of predicates G , $terms(G)$ denotes the union of the set of terms in any $g \in G$.

A decision procedure for EUF can be obtained by the *congruence closure* algorithm [17], described in Figure 5.

For a set of predicates G , let $m = |terms(G)|$. We can show that if we iterate the loop in step (2) of $DP_T(G)$ (shown in Figure 3) for at least $3m$ steps, then DP_T can implement the congruence closure algorithm. More precisely, for two

1. Partition the set of terms in $terms(G)$ into equivalence classes using the $G_=_$ predicates. At any point in the algorithm, let $EC(t)$ denote the equivalence class for any term $t \in terms(G)$.
 - (a) Initially, each term belongs to its own distinct equivalence class.
 - (b) We define a procedure $merge(t_1, t_2)$ that takes two terms as inputs. The procedure first merges the equivalence classes of t_1 and t_2 . If there are two terms $s_1 \doteq f(u_1, \dots, u_n)$ and $s_2 \doteq f(v_1, \dots, v_n)$ such that $EC(u_i) = EC(v_i)$, for every $1 \leq i \leq n$, then it recursively calls $merge(s_1, s_2)$.
 - (c) For each $t_1 = t_2 \in G_=_$, call $merge(t_1, t_2)$.
2. If there exists a predicate $t_1 \neq t_2$ in $G_{\neq}$, such that $EC(t_1) = EC(t_2)$, then return UNSATISFIABLE; else SATISFIABLE.

Fig. 5. Simple description of the congruence closure algorithm

terms t_1 and t_2 in $terms(G)$, the predicate $t_1 = t_2$ will be derived within $3m$ iterations of the loop in step 2 of $DP_T(G)$ if and only if $EC(t_1) = EC(t_2)$ after step (1) of the congruence closure algorithm (the proof can be found in [12]).

Proposition 2. *For a set of EUF predicates G , if $m \doteq |terms(G)|$, then the value of $maxDerivDepth_T(G)$ for the theory is bound by $3m$.*

Complexity of SDP_T . The run time and size of expression generated by SDP_T depend both on $maxDerivDepth_T(G)$ for the theory and also on the maximum number of predicates in W at any point during the algorithm. The maximum number of predicates in W can be at most $m(m-1)/2$, considering equality between every pair of term. The disequalities are never used except for generating contradictions. It is also easy to verify that the size of $S(g)$ (used in step (2) of SDP_T) is polynomial in the size of input. Hence the run time of SDP_T for EUF and the size of the shared expression returned by the procedure is polynomial in the size of the input.

3.4 SDP for Difference Logic

Difference logic is a simple yet useful fragment of linear arithmetic, where predicates are of the form $x \bowtie y + c$, where x, y are variables, $\bowtie \in \{<, \leq\}$ and c is a real constant. Any equality $x = y + c$ is represented as a conjunction of $x \leq y + c$ and $y \leq x - c$. The variables x and y are interpreted over real numbers. The function symbol “+” and the predicate symbols $\{<, \leq\}$ are the interpreted symbols of this theory. Figure 6 presents the inference rules for this theory³.

Given a set G of difference logic predicates, we can construct a graph where the vertices of the graph are the variables in G and there is a directed edge in the graph from x to y , labeled with $(\bowtie, c)$ if $x \bowtie y + c \in G$. We will use a predicate and an edge interchangeably in this section.

Definition 4. *A simple cycle $x_1 \bowtie x_2 + c_1, x_2 \bowtie x_3 + c_2, \dots, x_n \bowtie x_1 + c_n$ (where each x_i is distinct) is “illegal” if the sum of the edges is $d = \sum_{i \in [1, n]} c_i$*

³ Constraints like $x \bowtie c$ are handled by adding a special variable x_0 to denote the constant 0, and rewriting the constraint as $x \bowtie x_0 + c$ [19].

and either (i) all the edges in the cycle are $\leq$ edges and $d < 0$, or (ii) at least one edge is an $<$ edge and $d \leq 0$.

It is well known [6] that a set of difference predicates G is unsatisfiable if and only the graph constructed from the predicates has a simple illegal cycle. Alternately, if we add an edge $(\bowtie, c)$ between x and y for every simple path from x to y of weight c ($\bowtie$ determined by the labels of the edges in the path), then we only need to check for simple cycles of length two in the resultant graph. This corresponds to the rules (C) and (D) in Figure 6.

$$\begin{array}{c}
 \frac{X \leq Z + C \quad Z \bowtie Y + D}{X \bowtie Y + (C + D)} \quad (A) \\
 \frac{X < Z + C \quad Z \bowtie Y + D}{X < Y + (C + D)} \quad (B) \\
 \frac{X < Y + C \quad Y \bowtie X + D \quad C + D \leq 0}{\perp} \quad (C) \\
 \frac{X \leq Y + C \quad Y \leq X + D \quad C + D < 0}{\perp} \quad (D) \\
 \frac{X \leq Y \quad Y \leq X}{X = Y} \quad (E)
 \end{array}$$

Fig. 6. Inference rules for Difference logic

For a set of predicates G , a predicate corresponding to a simple path in the graph of G can be derived within $lg(m)$ iterations of step (2) of DP_T procedure, where m is the number of variables in G (the proof is in [12]).

Proposition 3. *For a set of DIF predicates G , if m is the number of variables in G , then $\maxDerivDepth_T(G)$ for the DIF theory is bound by $lg(m)$.*

Complexity of SDP_T . Let c_{max} be the absolute value of the largest constant in the set G . We can ignore any derived predicate in of the form $x \bowtie y + C$ from the set W where the absolute value of C is greater than $(m - 1) * c_{max}$. This is because the maximum weight of any simple path between x and y can be at most $(m - 1) * c_{max}$. Again, let $const(g)$ be the absolute value of the constant in a predicate g . The maximum weight on any simple path has to be a combination of these weights. Thus, the absolute value of the constant is bound by:

$$C \leq \min\{(m - 1) * c_{max}, \sum_{g \in G} const(g)\}$$

The maximum number of derived predicates in W can be $2 * m^2 * (2 * C + 1)$, where a predicate can be either $\leq$ or $<$, with m^2 possible variable pairs and the absolute value of the constant is bound by C . This is a *pseudo polynomial* bound as it depends on the value of the constants in the input.

However, many program verification queries use a subset of difference logic where each predicate is of the form $x \bowtie y$ or $x \bowtie c$. For this case, the maximum number of predicates generated can be $2 * m * (m - 1 + k)$, where k is the number of different constants in the input.

4 Combining *SDP* for Saturation Theories

In this section, we provide a method to construct a symbolic decision procedure for the combination of saturation theories T_1 and T_2 , given *SDP* for T_1 and T_2 . The combination is based on an extension of the Nelson-Oppen (N-O) framework [16] that constructs a decision procedure for the theory $T_1 \cup T_2$ using the decision procedures of T_1 and T_2 .

We assume that the theories T_1 and T_2 have disjoint signatures (i.e., they do not share any function symbol), and each theory T_i is *convex* and *stably infinite*⁴. Let us briefly explain the N-O method for combining decision procedures before explaining the method for combining *SDP*.

4.1 Nelson-Oppen Method for Combining Decision Procedures

Given two theories T_1 and T_2 , and the decision procedures DP_{T_1} and DP_{T_2} , the N-O framework constructs the decision procedure for $T_1 \cup T_2$, denoted as $DP_{T_1 \cup T_2}$.

To decide an input set G , the first step in the procedure is to *purify* G into sets G_1 and G_2 such that G_i only contains symbols from theory T_i and G is satisfiable if and only if $G_1 \cup G_2$ is satisfiable. Consider a predicate $g \doteq p(t_1, \dots, t_n)$ in G , where p is a theory T_1 symbol. The predicate g is purified to g' by replacing each subterm t_j whose top-level symbol does not belong to T_1 with a fresh variable w_j . The expression t_j is then purified to t'_j recursively. We add g' to G_1 and the *binding predicate* $w_j = t'_j$ to the set G_2 . We denote the latter as binding predicate because it binds the fresh variable w_j to a term t'_j .

Let V_{sh} be the set of *shared* variables that appear in $G_1 \cap G_2$. A set of equalities Δ over variables in V_{sh} is maintained; Δ records the set of equalities implied by the facts from either theory. Initially, $\Delta = \{\}$.

Each theory T_i then alternately decides if $DP_{T_i}(G_i \cup \Delta)$ is unsatisfiable. If any theory reports UNSATISFIABLE, the algorithm returns UNSATISFIABLE; otherwise, the theory T_i generates the new set of equalities over V_{sh} that are implied by $G_i \cup \Delta$ ⁵. These equalities are added to Δ and are communicated to the other theory. This process is continued until the set Δ does not change. In this case, the method returns SATISFIABLE. Let us denote this algorithm as $DP_{T_1 \cup T_2}$.

Theorem 2 ([16]). *For convex, stably infinite and signature-disjoint theories T_1 and T_2 , $DP_{T_1 \cup T_2}$ is a decision procedure for $T_1 \cup T_2$.*

There can be at most $|V_{sh}|$ irredundant equalities over V_{sh} , therefore the N-O loop terminates after $|V_{sh}|$ iterations for any input.

4.2 Combining *SDP* Using Nelson-Oppen Method

We will briefly describe a method to construct the $SDP_{T_1 \cup T_2}$ by combining SDP_{T_1} and SDP_{T_2} . As before, the input to the method is the pair (G, E) and

⁴ We need these restrictions only to exploit the N-O combination result. The definition of convexity and stably infiniteness can be found in [16].

⁵ We assume that each theory has an inference rule for deriving equality between variables in the theory, and DP_T also returns a set of equality over variables.

the output is an expression $t[e]$. The facts in E are also purified into sets E_1 and E_2 and the new binding predicates are added to either G_1 or G_2 .

Our goal is to symbolically encode the runs of the N-O procedure for $G' \cup \widetilde{E}$, for every $G' \subseteq G$. For any equality predicate δ over V_{sh} , we maintain an expression ψ_δ that records all the different ways to derive δ (initialized to **false**). We also maintain an expression ψ_e to record all the derivations of e (initialized to **false**).

The N-O loop operates just like the case for constructing $DP_{T_1 \cup T_2}$. The SDP_{T_i} for each theory T_i now takes $(G_i \cup \Delta, E_i)$ as input, where Δ is the set of equalities over V_{sh} derived so far. In addition to computing the (shared) expression $t[e]$ as before, SDP_{T_i} also returns the expression $t[(\delta, \top)]$, for each equality δ over V_{sh} that can be derived in step (2) of the SDP_T algorithm.

The leaves of the expressions $t[e]$ and $t[(\delta, \top)]$ are $G_i \cup \Delta$ (since leaves for $\widetilde{E}_i$ are replaced with **true**). We substitute the leaves for any $\delta \in \Delta$ with the expression ψ_δ , to incorporate the derivations of δ until this point. We also update $\psi_\delta \leftarrow (\psi_\delta \vee t[(\delta, \top)])$ to add the new derivations of δ . Similarly, we update $\psi_e \leftarrow (\psi_e \vee t[e])$ with the new derivations.

The N-O loop iterates $|V_{sh}|$ number of times to ensure that it has seen every derivation of a shared equality over V_{sh} from any set $G'_1 \cup G'_2 \cup \widetilde{E}_1 \cup \widetilde{E}_2$, where $G'_i \subseteq G_i$.

After the N-O iteration terminates, ψ_e contains all the derivations of e from G . However, at this point, there are two kind of predicates in the leaves of ψ_e ; the purified predicates and the binding predicates. If g' was the purified form of a predicate $g \in G$, we replace the leaf for g' with b_g . The leaves of the binding predicates are replaced with **true**, as the fresh variables in these predicates are really names for subterms in any predicate, and thus their presence does not affect the satisfiability of a formula. Let $t[e]$ denote the final expression for ψ_e that is returned by $SDP_{T_1 \cup T_2}$. Observe that the leaves of $t[e]$ are variables in B_G .

Theorem 3. *For two convex, stably-infinite and signature-disjoint theories T_1 and T_2 , if $t[e] \doteq SDP_{T_1 \cup T_2}(G, E)$, then for any set of predicates $G' \subseteq G$, $eval(t[e], G') = \mathbf{true}$ if and only if $DP_{T_1 \cup T_2}(G' \cup \widetilde{E})$ returns UNSATISFIABLE.*

Since the theory of EUF and DIF satisfy all the restrictions of the theories of this section, we can construct an SDP for the combined theory that still runs in pseudo-polynomial time.

5 Implementation and Results

We have implemented a prototype of the symbolic decision procedure for the combination of EUF and DIF theories. To construct $\mathcal{F}_P(e)$, we first build a BDD (using the CUDD [7] BDD package) for the expression $t[e]$ (returned by $SDP_T(P \cup \widetilde{P}, E)$) and then enumerate the cubes from the BDD.

Creating the BDD for the shared expression $t[e]$ and enumerating the cubes from the BDD can have exponential complexity in the worst case. This is because

n	$ P $	SDP_T time (s)	UCLID time (s)
3	14	0.20	19.37
4	19	0.43	656
5	24	0.65	-
10	49	5.81	-
12	59	12.28	-

Fig. 7. Result on diamond examples with increasing number of diamonds. The expression e is $(a1 = dn)$. A “-” denotes a timeout of 1000 seconds

the expression for $\mathcal{F}_P(e)$ can involve an exponential number of cubes (e.g. the example in Fig 7). However, most problems in practice have a few cubes in $\mathcal{F}_P(e)$. Secondly, as the number of leaves of $t[e]$ (alternately, number of BDD variables) is bound by $|P|$, the size of the overall BDD is usually small, and is computed efficiently in practice. Finally, by generating only the *prime implicants*⁶ of $\mathcal{F}_P(e)$ from the BDD, we obtain a compact representation of $\mathcal{F}_P(e)$.

We report preliminary results evaluating our symbolic decision procedure based predicate abstraction method on a set of software verification benchmarks. The benchmarks are generated from the predicate abstraction step for constructing Boolean Programs from C programs of Microsoft Windows device drivers in SLAM [2].

We compare our method with two other methods for performing predicate abstraction: (i) DP-based: This method uses the decision procedure ZAPATO [1] to enumerate the set of cubes that imply e . Various optimizations (e.g. considering cubes in increasing order of size) are used to prevent enumerating exponential number of cubes in practice. (ii) UCLID-based: This method performs quantifier-elimination using incremental SAT-based methods [13].

To compare with the DP-based method, we generated 665 predicate abstraction queries from the verification of device-driver programs. Most of these queries had between 5 and 14 predicates in them and are fairly representative of queries in SLAM. The run time of DP-based method was 27904 seconds on a 3 GHz. machine with 1GB memory. The run time of SDP -based method was 273 seconds. This gives a little more than 100X speedup on these examples, demonstrating that our approach can scale much better than decision procedure based methods. We have not been able to run UCLID-based method on SLAM benchmarks at the point of submitting this paper.

To compare with UCLID-based approach, we generated different instances of a problem (see Figure 7 for the example) where P is a set of equality predicates representing n diamonds connected in a chain and e is an equality $a1 = dn$. We generated different problem instances by varying the size of n . For an instance

⁶ For any Boolean formula ϕ over variables in V , prime implicants of ϕ is a set of cubes $C \doteq \{c_1, \dots, c_m\}$ over V such that $\phi \Leftrightarrow \bigvee_{c \in C} c$ and two or more cubes from C can't be combined to form a larger cube.

with n diamonds, there are $5n - 1$ predicates in P and 2^n cubes in $\mathcal{F}_P(e)$ to denote all the paths from $a1$ to dn . Figure 7 shows the result comparing both the methods. We should note that UCLID method was run on a slightly slower 2GHz machine. The results illustrate that our method scales much better than the SAT-based enumeration used in UCLID for this example. Intuitively, UCLID-based approach grows exponentially with the number of predicates ($2^{|P|}$), whereas our approach only grows exponentially with the number of diamonds (2^n) in the result.

References

1. T. Ball, B. Cook, S. K. Lahiri, and L. Zhang. Zapato: Automatic Theorem Proving for Software Predicate Abstraction Refinement. In *Computer Aided Verification (CAV '04)*, LNCS 3114. Springer-Verlag, 2004.
2. T. Ball, R. Majumdar, T. Millstein, and S. K. Rajamani. Automatic predicate abstraction of C programs. In *Programming Language Design and Implementation (PLDI '01)*, Snowbird, Utah, June, 2001. *SIGPLAN Notices*, 36(5), May 2001.
3. R. E. Bryant. Graph-based algorithms for Boolean function manipulation. *IEEE Transactions on Computers*, C-35(8), August 1986.
4. S. Chaki, E. M. Clarke, A. Groce, S. Jha, and H. Veith. Modular Verification of Software Components in C. *IEEE Transactions on Software Engineering*, 30(6), June 2004.
5. E. Clarke, D. Kroening, N. Sharygina, and K. Yorav. Predicate abstraction of ANSI-C programs using SAT. *Formal Methods in System Design (FMSD)*, 25, 2004.
6. T. H. Cormen, C. E. Leiserson, and R. L. Rivest. *Introduction to Algorithms*. MIT Press, 1990.
7. CUDD:CU Decision Diagram Package. Available at <http://vlsi.colorado.edu/~fabio/CUDD/cuddIntro.html>.
8. S. Das, D. Dill, and S. Park. Experience with predicate abstraction. In *Computer-Aided Verification (CAV '99)*, LNCS 1633. Springer-Verlag, July 1999.
9. C. Flanagan and S. Qadeer. Predicate abstraction for software verification. In *Symposium on Principles of programming languages (POPL '02)*. ACM Press, 2002.
10. S. Graf and H. Saïdi. Construction of abstract state graphs with PVS. In *Computer-Aided Verification (CAV '97)*, LNCS 1254. Springer-Verlag, June 1997.
11. T. A. Henzinger, R. Jhala, R. Majumdar, and G. Sutre. Lazy Abstraction. In *Symposium on Principles of programming languages (POPL '02)*. ACM Press, 2002.
12. S. K. Lahiri, T. Ball, and B. Cook. Predicate abstraction via symbolic decision procedures. Technical Report MSR-TR-2005-53, Microsoft Research, April 2005.
13. S. K. Lahiri, R. E. Bryant, and B. Cook. A symbolic approach to predicate abstraction. In *Computer-Aided Verification (CAV 2003)*, LNCS 2725. Springer-Verlag, 2003.
14. K. McMillan. Applying SAT Methods in Unbounded Symbolic Model Checking. In *Proc. Computer-Aided Verification (CAV'02)*, LNCS 2404, July 2002.
15. K. S. Namjoshi and R. P. Kurshan. Syntactic program transformations for automatic abstraction. In *Computer Aided Verification*, LNCS 1855, 2000.
16. G. Nelson and D. C. Oppen. Simplification by cooperating decision procedures. *ACM Transactions on Programming Languages and Systems (TOPLAS)*, 2(1), 1979.

17. G. Nelson and D. C. Oppen. Fast decision procedures based on the congruence closure. *Journal of the ACM*, 27(2), 1980.
18. H. Saïdi and N. Shankar. Abstract and model check while you prove. In *Computer-Aided Verification*, volume 1633 of *LNCS*. Springer-Verlag, July 1999.
19. O. Strichman, S. A. Seshia, and R. E. Bryant. Deciding Separation Formulas with SAT. In *Proc. Computer-Aided Verification (CAV'02)*, LNCS 2404, July 2002.