Monitoring the Health Condition of a Ubiquitous System: Rejuvenation vs. Recovery

Kazuki Iwamoto¹, Tadashi Dohi¹, and Naoto Kaio²

¹ Department of Information Engineering, Hiroshima University,
Higashi-Hiroshima 739-8527, Japan
`dohi@rel.hiroshima-u.ac.jp`

² Department of Economic Informatics, Hiroshima Shudo University,
Hiroshima 731-3195, Japan
`kaio@shudo-u.ac.jp`

Abstract. Software rejuvenation is a preventive and proactive solution that is particularly useful for counteracting the phenomenon of software aging. In this article, we consider a periodic software rejuvenation model based on the steady-state system availability in discrete operational circumstance. More precisely, we treat a telecommunication billing application as a simple ubiquitous application, and describe its stochastic behavior by applying the discrete renewal reward process. The main objective is the determination of the optimal frequency to rejuvenate the ubiquitous application, maximizing the steady-state system availability. Also, we develop a statistically non-parametric algorithm to estimate the optimal rejuvenation schedule with the discrete total time on test concept.

1 Introduction

Since ubiquitous systems around us are controlled by software in almost all cases, it is quite important to check their health condition occasionally or periodically. Software rejuvenation is a preventive and proactive solution that is particularly useful for counteracting the phenomenon of software aging. The faults involved in embedded software systems should ideally have been removed during the debugging phase. Even if the embedded software may have been thoroughly tested, it still may have some design faults that are yet to be revealed. Such design faults are called *bohrbugs* and may exist even in mature software such as commercial operating systems. Also, even mature software can be expected to have what are known as *heisenbugs*. These are bugs in the software that are revealed only during specific collusions of events. For example, a sequence of operations may leave the software in a state that results in an error on an operation executed next. Simply retrying a failed operation, or if the application process has crashed, restarting the process might resolve such a problem. Another type of fault observed in ubiquitous applications is due to the phenomenon of resource exhaustion. These faults may exist in not only middleware under ubiquitous computing circumstance but also typical operating systems and telecommunication applications. For instance, operating system resources such as swap space and free memory available are progressively depleted due to defects in software such as memory leaks and incomplete cleanup of resources after use.

In fact, when a ubiquitous application executes continuously for long periods of time, some of the faults cause the software to age due to the error conditions that accrue with time and/or load. *Software aging* will affect the performance of the application and eventually cause it to fail [1], [3]. A complementary approach to handle software aging and its related transient software failures, called *software rejuvenation*, are becoming popular [7]. Software rejuvenation is a preventive and proactive solution that is particularly useful for counteracting the phenomenon of software aging. It involves stopping the running software occasionally, cleaning its internal state and restarting it. Cleaning the internal state of a software might involve garbage collection, flushing operating system kernel tables, reinitializing internal data structures, and hardware reboot. For many ubiquitous applications, the rejuvenation may correspond to a system reconfiguration in the sleep mode during the idle period.

Huang *et al.* [7] report the software aging phenomenon in a real telecommunication billing application where over time the application experiences a crash or a hang failure, and propose to perform the rejuvenation occasionally. More specifically, they consider the degradation as a two step process. From the clean state the software system jumps into a degraded state from which two actions are possible: rejuvenation with return to the clean state or transition to the complete failure state. They model the four-state process as a continuous-time Markov chain, and derive the steady-state system availability. Avritzer and Weyuker [2] discuss the aging in a telecommunication switching software where the effect manifests as gradual performance degradation. Garg *et al.* [6] introduce the idea of periodic rejuvenation (deterministic interval between successive rejuvenations) into the Huang *et al.* model [7] and represent the stochastic behavior by using a Markov regenerative stochastic Petri net. Recently, Dohi *et al.* [4], [8] extend both the original Huang *et al.* model [7] and Garg *et al.* model [6] to semi-Markov models, and develop statistically non-parametric algorithms to estimate the optimal software rejuvenation schedules from the complete sample data of failure time.

It should be noted in the past literature that the software system is assumed to operate in continuous time. However, in many practical situations, system lifetime (degradation time) can not be measured in calendar time. For instance, consider the system failure of an embedded system where the number of rounds for use before system failure is more significant than the system age measured by CPU time. Also, in some mission critical systems based on the transaction processing, the number of transactions strongly depends on the software aging and its related transient failure. In such systems, the system lifetime should be regarded as a discrete random variable. Unfortunately, enough research has not been carried out on discrete software rejuvenation models. Dohi *et al.* [5] reformulate the semi-Markov rejuvenation models in [4] as those in discrete time under the steady-state system availability criterion. More specifically, they model the stochastic behavior of a telecommunication billing application discussed in [4], [7] by using discrete semi-Markov processes, and determine the optimal periodic software rejuvenation schedules in discrete-time setting. Similar to the paper [4], the same authors develop non-parametric estimators of the optimal

non-periodic software rejuvenation schedules maximizing the steady-state system availability [5].

This paper is a continuation of the above work [5]. That is, we reformulate the periodic software rejuvenation model in continuous time [6], [8] as a discrete one. In a fashion similar to the previous work [5], we apply the discrete Markov regenerative process and derive analytically the optimal periodic software rejuvenation schedule in discrete-time setting, maximizing the steady-state system availability. Also, we wish to emphasize here that the discrete model considered here is not a simple analogy of the continuous-time software rejuvenation model. First, we utilize the discrete total time on test (DTTT) concept (scaled DTTT transform and scaled DTTT statistics), which is first introduced in [5] and is a quite new statistical device. It is needed to develop a statistically non-parametric algorithm of the optimal software rejuvenation schedule. In addition, the results in [5] are based on the discrete-time semi-Markov processes, but our model considered in this paper is classified into the discrete-time Markov regenerative process which belongs to the more wide class stochastic process. As pointed out in the literature [6], [8], the periodic rejuvenation scheme is feasible in practice since the time interval between successive rejuvenations is deterministic. Also, it is noted that the resulting optimal rejuvenation schedule based on the discrete modeling framework is not always equivalent to the discretized one for continuous-time model, because the discrete model involves a delicate problem on the uniqueness of the optimal schedule. In that sense, our modeling approach developed in this paper is not a trivial example.

2 Model Description

2.1 Notation and Assumption

Z : time interval from highly robust state to failure probable state (discrete random variable)

$F_0(n)$, $f_0(n)$, μ_0 (> 0): cumulative distribution function (cdf), probability mass function (pmf) and mean of Z , where $n = 0, 1, 2, \dots$

X : failure time from failure probable state (discrete random variable)

$F_f(n)$, $f_f(n)$, μ_f (> 0): cdf, pmf and mean of X

$' * '$: discrete convolution operator, *i.e.* $F_0 * F_f(n) = \sum_{j=0}^n F_0(n-j)f_f(j) = \sum_{j=0}^n F_f(n-j)f_0(j)$

$\bar{\psi}(\cdot)$: survivor function ($= 1 - \psi(\cdot)$)

$r_{0f}(n)$: failure rate ($= f_0 * f_f(n) / \overline{F_0 * F_f(n-1)}$)

Y : recovery time from failure state (discrete random variable)

$F_a(n)$, $f_a(n)$, μ_a (> 0): cdf, pmf and mean of Y

N : rejuvenation time from highly robust state (discrete random variable)

$F(n)$, n_0 (≥ 0): cdf and mean of N

R : system overhead incurred by software rejuvenation (discrete random variable)

$F_c(n)$, $f_c(n)$, μ_c (> 0): cdf, pmf and mean of R

Assumption: $\mu_a > \mu_c$, *i.e.* the mean recovery time from the system failure is strictly greater than the mean time to complete the rejuvenation.

Fig. 1. Transition diagram

Consider the similar stochastic model with periodic software rejuvenation to Garg *et al.* [6] and Suzuki *et al.* [8] in discrete time. Suppose that the software system starts for operation at time $n = 0$ and is in the highly robust state (normal operation state). Let Z be the random time to reach the failure probable state from the highly robust state. Let $\Pr\{Z \leq n\} = F_0(n)$, ($n = 0, 1, 2, \dots$). Just after the state becomes the failure probable state, a system failure may occur with positive probability. Let X be the time to failure from the failure probable state having the cdf $\Pr\{X \leq n\} = F_f(n)$. Then, two actions are possible to be taken; rejuvenation and recovery from the system failure. If the system failure occurs before triggering a software rejuvenation, then the recovery operation starts immediately. The time to complete the recovery operation Y is also the positive random variable having the cdf $\Pr\{Y \leq n\} = F_a(n)$. Without any loss of generality, it is assumed that after completing recovery operation the software system becomes as good as new.

On the other hand, rejuvenation is performed at a random time interval measured from the start (or restart) of the software in the robust state. The cdf of the time to invoke the software rejuvenation, say N , and the cdf of the time to complete software rejuvenation are represented by $F(n)$ and $F_c(n)$, respectively. Suppose that the time to rejuvenate the software is a constant n_0 , *i.e.* the software rejuvenation is performed periodically. Then, the cdf $F(n)$ has to be replaced by

$$F(n) = U(n - n_0) = \begin{cases} 1 : (n \geq n_0) \\ 0 : (n < n_0), \end{cases} \quad (1)$$

where $U(\cdot)$ is the unit step function. We call n_0 (≥ 0) *the software rejuvenative schedule* in this paper. After completing the software rejuvenation, the software system becomes as good as new, and the software age is initiated at the beginning of the next highly robust state.

Define the following five states:

State 0: highly robust state (normal operation state)

State 1: failure probable state

State 2: software rejuvenation state from failure probable state

State 3: failure state

State 4: software rejuvenation state from highly robust state.

Figure 1 depicts the transition diagram for the stochastic model under consideration, where the states denoted by circles (0, 2, 3, 4) and square (1) are regeneration points and non-regeneration points, respectively, in the Markov regenerative process. Strictly speaking, this stochastic process is not a simple semi-Markov process. However, since only one non-regeneration point is included in the transition diagram, it can be reduced to an equivalent semi-Markov process.

3 Availability Analysis

We formulate the steady-state system availability as a criterion of optimality. Define the time length from the beginning of the system operation to the completion of the preventive or corrective maintenance of software system as one cycle. Suppose that the same cycle is repeated again and again over an infinite time horizon. The mean operative time during one cycle is obtained as

$$S(n_0) = \sum_{n=0}^{n_0-1} \overline{F_f * F_0}(n). \quad (2)$$

The mean time length of one cycle is given by

$$T(n_0) = \mu_c + (\mu_a - \mu_c)F_f * F_0(n_0) + \sum_{n=0}^{n_0-1} \overline{F_f * F_0}(n). \quad (3)$$

Then the steady-state system availability is, from the discrete renewal reward theorem, derived by $AV(n_0) = S(n_0)/T(n_0)$, and the problem is to seek the optimal software rejuvenation schedule n_0^* maximizing $AV(n_0)$.

Taking the difference of $AV(n_0)$ with respect to n_0 , define the following function:

$$q(n_0) = \frac{T(n_0 + 1)T(n_0)\{AV(n_0 + 1) - AV(n_0)\}}{\overline{F_0 * F_f}(n_0)}$$

$$= (\mu_c - \mu_a)S(n_0)r_{0f}(n_0 + 1) + T(n_0) - S(n_0), \quad (4)$$

where $q(0) = T(0) - S(0) + (\mu_c - \mu_a)S(0)r_{0f}(1) = \mu_c > 0$. The following result gives the optimal software rejuvenation schedule.

Theorem 1: (1) Suppose that the convoluted cdf $F_0 * F_f(n)$ is strictly IFR (increasing failure rate) under the assumption $\mu_a > \mu_c$.

- (i) If $q(\infty) < 0$, then there exist (at least one, at most two) optimal software rejuvenation schedule n_0^* ($0 < n_0^* < \infty$) satisfying $q(n_0^* - 1) > 0$ and $q(n_0^*) \leq 0$. Then, the maximum system availability is given by

$$\underline{AV}(n_0^*) \leq AV(n_0^*) < \overline{AV}(n_0^*), \quad (5)$$

where

$$\underline{AV}(n_0^*) = \frac{1}{1 + (\mu_a - \mu_c)r_{0f}(n_0^* + 1)}, \quad (6)$$

$$\overline{AV}(n_0^*) = \frac{1}{1 + (\mu_a - \mu_c)r_{0f}(n_0^*)}. \quad (7)$$

- (ii) If $q(\infty) \geq 0$, then the optimal software rejuvenation schedule becomes $n_0^* \rightarrow \infty$, *i.e.* it is optimal not to carry out the software rejuvenation. Then, the maximum system availability is given by $AV(\infty) = \mu_f/(\mu_a + \mu_f)$.

(2) Suppose that the convoluted cdf $F_0 * F_f(n)$ is DFR (decreasing failure rate) under the assumption $\mu_a > \mu_c$. Then, the steady-state system availability $AV(n_0)$ is a convex function of n_0 , and the optimal software rejuvenation schedule is $n_0^* = 0$ or $n_0^* \rightarrow \infty$.

In the following section, we give an alternative graphical interpretation of Theorem 1 by applying the DTTT concept.

4 Statistical Estimation Algorithm

For the discrete cdf $F_f * F_0(n)$, define the scaled DTTT transform [5]:

$$\phi(p) = \sum_{n=0}^{(F_f * F_0)^{-1}(p)} \frac{\overline{F_f * F_0}(n)}{\mu_f + \mu_0}, \quad (8)$$

where

$$(F_f * F_0)^{-1}(p) = \min\{n : F_f * F_0(n) > p\} - 1, \quad (9)$$

if the inverse function exists. Then it is evident that

$$\mu_f + \mu_0 = \sum_{n=0}^{\infty} \overline{F_f * F_0}(n). \quad (10)$$

The scaled DTTT transform can be regarded as a discrete analogy of the familiar total time on test transform of continuous cdf, and can be used to examine the aging property of discrete probability distribution. To our best knowledge, this interesting statistical device has not sufficiently been studied in the context of reliability statistics.

Based on the definition in Eq.(8), let us represent the system availability by the parameter p instead of n_0 . Suppose that p is one-to-one corresponding to n_0 . After a few algebraic manipulations, we can obtain the following result:

Theorem 2: Obtaining the optimal software rejuvenation schedule n_0^* maximizing the steady-state system availability $AV(n_0)$ is equivalent to obtaining p^* ($0 \leq p^* \leq 1$) such as

$$\max_{0 \leq p \leq 1} \frac{\phi(p)}{p + \beta}, \quad (11)$$

where $\beta = \mu_c / (\mu_a - \mu_c)$.

Theorem 2 is the dual of Theorem 1. From this result, it is seen that the optimal software rejuvenation schedule $n_0^* = (F_f * F_0)^{-1}(p^*)$ is determined by calculating the optimal point p^* ($0 \leq p^* \leq 1$) maximizing the tangent slope from the point $(-\beta, 0)$ to the curve $(p, \phi(p)) \in [0, 1] \times [0, 1]$ in the two-dimensional plane. This graphical idea is very useful to calculate the optimal rejuvenation schedule in practice. For the continuous-time models [4], [8], the optimal solution can be characterized as a unique solution of non-linear equation in the non-trivial case. On the other hand, in discrete-time setting, we have to solve simultaneous inequalities $q(n_0^* - 1) > 0$ and $q(n_0^*) \leq 0$. If n_0 is large, this is equivalent to solve a non-trivial combinatorial problem. However, from Theorem 2, we can plot the graph $(p, \phi(p))$ easily and seek the optimal point p^* so as to maximize the tangent slope geometrically. The other benefit of this approach arises in an educational aspect to perform the sensitivity analysis. For varying model parameters, we can check the sensitivity of model parameters on the optimal rejuvenation schedule on the graph.

Next, suppose that the optimal software rejuvenation schedule has to be estimated from k ordered complete observations: $0 = x_0 \leq x_1 \leq x_2 \leq \dots \leq x_k$ of the times from a discrete cdf $F_0 * F_f(n)$, which is unknown. Then, the empirical distribution for this sample, is given by

$$F_{fk}(n) = \begin{cases} i/k & \text{for } x_i \leq n < x_{i+1}, \\ 1 & \text{for } x_k \leq n. \end{cases} \quad (12)$$

The numerical counterpart of the scaled DTTT transform, called *scaled DTTT statistics*, based on this sample, is defined by

$$\phi_{ik} = \psi_i / \psi_k, \quad i = 0, 1, 2, \dots, k, \quad (13)$$

where

$$\psi_i = \sum_{j=1}^i (k - j + 1)(x_j - x_{j-1}), \quad i = 1, 2, \dots, k \quad (14)$$

Fig. 2. Estimation of the optimal software rejuvenation schedule

Fig. 3. Asymptotic behavior of the estimates for the maximum system availability

with $\psi_0 = 0$. The resulting step function by plotting the points $(i/k, \phi_{ik})$ ($i = 0, 1, 2, \dots, k$) is called *scaled DTTT plot*.

The following theorem gives a statistically non-parametric estimation algorithm for the optimal software rejuvenation schedule.

Theorem 3: Suppose that the optimal software rejuvenation schedule has to be estimated from k ordered complete sample $0 = x_0 \leq x_1 \leq x_2 \leq \dots \leq x_k$ of the times from a discrete cdf $F_f * F_0(n)$, which is unknown. Then, a non-parametric estimator of the optimal software rejuvenation schedule $\hat{n}_0^*$ which maximizes $AV(n_0)$ is given by x_{j^*} , where

$$j^* = \left\{ j \mid \max_{0 \leq j \leq k} \frac{\phi_{jk}}{j/k + \beta} \right\}. \tag{15}$$

The above result is a direct application of Theorem 2. In fact, it can be expected that the resulting estimator x_{j^*} may function well to estimate the optimal soft-

ware rejuvenation schedule maximizing the steady-state system availability, if the number of sample is sufficiently large. Unfortunately, the strong consistency of ϕ_{ik} has not been analytically proved in the literature, *i.e.* $\phi_{ik} \rightarrow \phi(p)$ as $k \rightarrow \infty$. However, this hypothesis seems to be correct in our simulation experiments. In the following section, we give a numerical example to show usefulness of the estimation algorithm.

5 A Numerical Example

We present an example to determine the optimal software rejuvenation schedule which maximizes the steady-state system availability. Suppose that the time $Z + X$ obeys the negative binomial distribution with pmf:

$$f_f(n) = \binom{n-1}{r-1} q^r (1-q)^{n-r}, \quad n = 1, 2, 3, \dots, \quad (16)$$

where $q \in (0, 1)$ and $r = 1, 2, \dots$ is the natural number. Also, it is assumed that Z is a geometrically distributed random variable having pmf:

$$f_0(n) = p(1-p)^n, \quad n = 0, 1, 2, \dots \quad (17)$$

Suppose that $(r, q) = (10, 0.3)$, $p = 0.3$, $\mu_a = 5.0$ [day] and $\mu_c = 2.0$ [day]. In this case, the optimal software rejuvenation schedule is given by $n_0^* = (F_f * F_0)^{-1}(0.125291) = 26$ with $AV(26) = 0.912150$, if we can know the pmf $f_f(n)$ completely. In Fig. 2 we show the estimation result of the optimal software rejuvenation schedule, where the failure time data are generated from the negative binomial distribution. For 200 simulation data (negative binomial distributed random number), the estimates of the optimal periodic rejuvenation schedule and its associated system availability are given by $\hat{n}_0^* = x_{19} = 26$ and $AV(\hat{n}_0^*) = 0.918798$, respectively.

Of our next concern is the investigation of asymptotic property of the estimators given in Theorem 3. In the simulation experiment, we generate the negative binomial distributed random number as the system failure time data and sequentially estimate the optimal software rejuvenation schedule and the corresponding system availability. In Fig. 3, we plot estimates of the maximum system availability, where the horizontal line denotes the really maximum availability $AV(26)$ mentioned before. From this figure, it is observed that the estimate of the steady-state system availability fluctuates around the real maximum and that the non-parametric method proposed here can provide a good estimate. As the number of data increases, the estimated system availability converges to the corresponding asymptotic value. Hence, the estimator of the optimal software rejuvenation schedule can be expected to be consistent numerically. On the other hand, from this result, it can be seen that a number of system failure data are not always needed to get the good estimates with higher accuracy. For instance, in the above example, around 30 data will be enough even if we can not know the underlying system failure time distribution. This

result tells us that the proposed statistical estimation method provides a good predictive performance of the optimal rejuvenation schedule for an operational software system.

Acknowledgments

The present research was partially supported by a Grant-in-Aid for Scientific Research from the Ministry of Education, Sports, Science and Culture of Japan under Grant Nos. 15651076 and 16310116, the Research Program 2005 under the Institute for Advanced Studies of the Hiroshima Shudo University.

References

1. Adams, E. (1984), Optimizing preventive service of the software products, *IBM J. Research & Development*, **28**, 2–14.
2. Avritzer, A. and Weyuker, E. J. (1997), Monitoring smoothly degrading systems for increased dependability, *Empirical Software Eng.*, **2**, 59–77.
3. Castelli, V., Harper, R. E., Heidelberg, P., Hunter, S. W., Trivedi, K. S., Vaidyanathan, K. V. and Zeggert, W. P. (2001), Proactive management of software aging, *IBM J. Research & Development*, **45**, 311–332.
4. Dohi, T., Goševa-Popstojanova, K. and Trivedi, K. S. (2001), Estimating software rejuvenation schedule in high assurance systems, *The Computer Journal*, **44**, 473–485.
5. Dohi, T., Iwamoto, K., Okamura, H. and Kaio, N. (2003), Discrete availability models to rejuvenate a telecommunication billing application, *IEICE Trans. on Communications (B)*, **E86-B**, 2931–2939.
6. Garg, S., Telek, M., Puliafito, A. and Trivedi, K. S. (1995), Analysis of software rejuvenation using Markov regenerative stochastic Petri net, *Proc. 6th Int'l Symp. on Software Reliab. Eng.*, 24–27, IEEE CS Press.
7. Huang, Y., Kintala, C., Koletti, N. and Fulton, N. D. (1995), Software rejuvenation: analysis, module and applications, *Proc. 25th Int'l Symp. on Fault Tolerant Computing*, 381–390, IEEE CS Press.
8. Suzuki, H., Dohi, T., Goševa-Popstojanova, K. and Trivedi, K. S. (2002), Analysis of multistep failure models with periodic software rejuvenation, *Advances in Stochastic Modelling* (J. R. Artalejo and A. Krishnamoorthy, eds.), Notable Publications, Inc., 85–108.