Pore Pressure

Michael T. Hendry

Department Civil and Environmental Engineering, University of Alberta, Edmonton, AB, Canada

Definition

Pore pressure (u) within a soil is the net pressure of the fluids within the voids that exist between the soil particles. Pore pressure is most commonly associated with pore water, which has a pore-water pressure (u_w). Pressures of other fluids such as pore-air pressure (u_a) and other nonsoluble materials may be considered for specialized analyses.

The simplest spatial distribution of u_w is a result of hydrostatic pressure, where the pressure at a given point is the result depth below the phreatic surface, and thus u_w increases with increasing depth. Where the phreatic surface or water table is the height of water within observation wells that correspond to a u_w equal to zero. The hydrostatic pressure can be

calculated from the unit weight of water (γ_w), and the depth (d) below the phreatic surface (Terzaghi et al. 1996).

$$u_w = \gamma_w d$$

The surface tension of the water interacts with the fine interconnected voids within soil and results in a capillary rise of the water above the phreatic surface to a height that is a function of the effective diameter of the interconnected voids. This rise of water above the phreatic surface and tension within the water results in a negative u_w (Terzaghi et al. 1996).

From **Darcy's law**, where there is a flow of pore fluids, there must also exist a corresponding gradient of u_w in the direction of that flow.

References

- Terzaghi K, Peck RB, Mesri G (1996) Soil mechanics in engineering practice, 3rd edn. Wiley, New York