Strain

Jeffrey R. Keaton
Amec Foster Wheeler, Los Angeles, CA, USA

Definition

Strain is the response in a rock or soil mass produced by applied load or stress. Strain is a tensor quantity, as is stress (Eberhardt 2009). Stress acting on a rock or soil mass can cause the mass to experience a change in volume, a change in shape, or a change in both volume and shape. The change in length Δl of a solid, right, circular bar can be normalized to its initial length l_o to produce axial or linear strain ε (Holmes 2016).

$$\varepsilon = \frac{\Delta l}{l_o} \quad (1)$$

Similarly, a change in volume ΔV divided by the initial volume V_o is volumetric strain ε_V

$$\varepsilon_V = \frac{\Delta V}{V_o} \quad (2)$$

Shear strain γ can be explained as a change in the position

of one surface of a solid, right rectangular prism relative to a parallel surface Δl caused by shear stress τ applied to the first surface, without an accompanying volume change, divided by the thickness of the prism h_o (Pariseau 2012).

$$\gamma = \frac{\Delta l}{h_o} \quad (3)$$

Cross-References

- [Hooke's Law](#)
- [Stress](#)

References

- Eberhardt E (2009) Stress & strain: a review. StressStrain-Review.pdf, Course notes EOSC 433, University of British Columbia, Vancouver. <https://www.eoas.ubc.ca/courses/eosc433/lecture-material/>. Accessed April 2016
- Holmes DP (2016) Mechanics of materials: Strain. Mechanics of slender structures. Boston University. <http://www.bu.edu/moss/mechanics-of-materials-strain/>. Accessed April 2016
- Pariseau WG (2012) Design analysis in rock mechanics, 2nd edn. CRC Press, London