Research on the Collaboration Service Mechanism for Pig Diseases Diagnosis Based on Semantic Web

Xiang Sun, Huarui Wu*, Huaji Zhu, Cheng Peng, and Jingqiu Gu

Beijing Research Center for Information Technology in Agriculture, Beijing, 100097
{sunx,wuhr,zhuhj,pengc,gujq}@nercita.org.cn

Abstract. Distributed knowledge resources for the pig diseases diagnosis have the characteristics of heterogeneous, autonomy and difficult to be shared among different systems. Based on the web-based ontology modeling language, a descriptive model to describe the heterogeneous knowledge resources of the pig diseases diagnosis and a formal model to express the decision services of pig diseases are proposed in this work. Based on the two models, a complex decision task can be automatically divided into many dependent simple decision fragments. The relationships between different fragments, the mapping relationships between each fragment which can be dynamically adjusted according the divided fragments and its distributed knowledge resources can be formally described. The models form a mechanism for cooperative decision for pig diseases diagnosis. The method is proposed by achieving the balanced decomposition of decision task and intelligent schedule of knowledge resources. The method is verified in a pig diseases collaborative diagnosis system. The result shows that the method is superior to the traditional intelligent decision-making method.

Keywords: semantic web; context awareness; collaborative decision; pig diseases diagnosis; agricultural intelligent system.

1 Introduction

Nowadays, along with the application of intelligent information techniques in agricultural information systems, the amount of knowledge resources of raising pig in the process of monitoring, production, operation and management grows rapidly [1]. However, these knowledge resources belong to different owners and they are heterogenous in type and representation. The dispersed diagnostic knowledge which has some incomplete issues inevitably reduces the efficiency of knowledge service. Collaborative decision-making is the decision-making process or ability of coordinating different data resources, knowledge resources, terminal devices, applications [2],[3]. The purpose of collaborative decision-making service in the field of pig diseases diagnosis which has heterogeneous knowledge is rapidly positioning associated knowledge resources and making decision. As a result, it can achieve the semantic interaction between providers and users of knowledge resources based on function and application of quality.

* Corresponding author.

2 The Semantic Description of Decision-Making Services Knowledge Resources

Distributed environment is the basis environment of achieving resource sharing and collaborative decision-making. A wide range of agricultural knowledge resources, the representation model, location, underlying communication mechanism are different. To realize collaborative service in distributed agricultural resources, the paper puts forward a semantic description model that can support the multiple type, shield heterogeneity and adapt to dynamic environment. This model uses OWL as the agricultural knowledge ontology expression language [4], [5], [6] and explains the related agricultural sharing concept model. Additionally, it provides basic terms and relationship for agricultural knowledge resource model and makes up the extension rules and complex definitions using those relationship and terms. This mechanism realizes the concept system of classifying and describing the agricultural mass knowledge. It is the basic for collaborative knowledge resource organization and management and information exchange.

3 Ontology Description of Decision-Making Services of Agriculture Knowledge

Semantics heterogeneity brings on differences of understanding the agricultural knowledge resources, described by using same descript mode, between agriculture knowledge resources of providers and users. This will affect the effect of the collaborative decision-making. In order to solve semantic heterogeneity problem, this paper introduces the semantic ontology quaternion group to describe the decision-making service of agriculture knowledge:

$$KR = \{ \langle kobject \rangle, \langle relation \rangle, \langle owner \rangle, \langle constraint \rangle \} \quad (1)$$

‘kobject’ is the agricultural knowledge atom, which is the smallest knowledge resources unit in the entire descriptive model. Expressed as:

$$kobject = \{ ra_i | 1 \leq i \leq n, ra \notin \Phi, ra \in \Omega \} \quad (2)$$

‘Ra’ is the knowledge atom in the field of agricultural knowledge resources; ‘relation’ means the collection that has reciprocity and affects among the knowledge atom and knowledge entities. Namely:

$$relation = \{ r_{ij} (ra_i + ra_j) \vee r_{ij} (rm_k, rm_j) | 1 \leq i, j, k, l \leq n, r \notin \Phi \} \quad (3)$$

‘Rm’ means a knowledge entity which is constituted by agriculture knowledge resources.

$$rm = \{ \sum ra \cdot ra_j \vee \prod ra \cdot ra_j | 1 \leq i, j \leq n; ra \cdot ra_j \notin \Phi, ra \cdot ra_j \in \Omega \} \quad (4)$$

‘rij (rai+raj)’ means the connections among knowledge atoms of agricultural knowledge resource. rij (rmk, rmj) means the connections among knowledge entities. Owner is the identifying information that marked the agriculture knowledge resources

resources naming, attribute and extension. For example, OWL: `equivalentClass` and OWL: `equivalentProperty` are used to solve the problem of naming heterogeneity that different information sources denote the same concept according to multiple languages. Rdfs: `subPropertyOf` is used to solve the problem of attribute heterogeneity. Owl: `equivalentClass` and owl: `equivalentProperty` are used to solve the problem of equivalence element and owl: `intersectionOf` is used to solve the problem of crossed element. Rdfs: `subClassOf` and rdfs: `subPropertyOf` are used to solve the problem of contain elements in ontology syntax. and owl: `unionOf` in global ontology are used to solve the problem of disjoint elements. The solutions of these problems achieve the unified description of knowledge representations that have many types such as production rules, examples, and semantic web. These solutions also can convert variety of types of knowledge to the personalized knowledge representation required by collaborative decision-making [8].

Resource label and exterior extension are made use of combining the information resources and the knowledge resources. It includes plain text, multi-media, HTML, GIS, remote sensing images, database and other resources marks. Moreover, it realizes the knowledge integration of frame, production rule, example, description and other models of knowledge expression.

According to the composition of agricultural knowledge resources and the definition of semantic description system, knowledge resources of agricultural collaborative decision-making service is divided into three layers, decision-making problem layer, correlative information layer, knowledge model layer. Decision-making layer includes definition of atom of agricultural knowledge resources. Such as, decision-making facts, concepts, fact attribute those related to agricultural knowledge rules and the relations among the concepts. Correlative information layer mostly includes related information of different decision-making model, resources label information that related to decision-making project; the efficiency of resource reference, etc. Knowledge layer includes meta-knowledge of agricultural knowledge resource model and related index of model, index of decision-making problem, index of resource correlation. By means of related index, it can accurately locate the related model, decision-making problem, related information resource of each node in a distributed environment [9].

5 The Representation Formalism of Decision-Making Service Problem

5.1 Description of Decision-Making Problems List

In the semantic description model of decision-making service knowledge resources, decision-making layer provide users with a description of their required decision-making service and the abstract of actual decision-making data item, to realize the analysis of decision-making problem requirement. It means an expression of decision-making problem requirement.

$$\begin{aligned} R_{dec} &= R_s \wedge R_{d1} \wedge R_{d2} \wedge \cdots \wedge R_{dn}, \\ R_d &= (UID, RO, RA, RC, RF, RU) \end{aligned} \quad (5)$$

R5 means initial limit of decision-making goals. Rd means the restriction of decision-making premise data items. UID is the unique identifier of the decision-making service users. RO is the domain limit of knowledge or resources. RA is the restriction of functional properties of agricultural knowledge. RC means the explanation of the initial value of agricultural knowledge. RF is the restriction of information resources. RU is the memory of decision-making service.

There are a large number of agricultural knowledge resources. These knowledge resources provide decision-making knowledge service for problem of decision-making service. Based on the decision-making goal of decision-making user and the model of agricultural knowledge resources, the formalism representations of decision-making service problem identify the interaction in each step progressively.

$$RU_{UID} = \{Rxt, (< k_1 >, Rxt_1), (< k_2 >, Rxt_2), \cdots, (< k_n >, Rxt_n)\} \quad (6)$$

‘Ki’ means the node identification of decision-making problem flow. ‘Rxti’ is the node information set of decision-making service problem. When collaborative decision-making occurred, the description of problem and the context information are stored in RU as a unique identification. It provides the problem list that interacts with the user for collaborative decision-making services.

Firstly, according to the domain type, content, owner of knowledge resources, property, states of obtained decision-making services goal, the limited value is initialize and then the decision-making knowledge resources are obtained to calculate the decision-making problem list.

5.2 Matching of Decision-Making Problem and Knowledge Resources

It is the key that to determine the knowledge resources related to decision-making problem in the distributed environment and achieve the representation formalism of decision-making service problem. The semantic matching between knowledge resource and user decision-making problem is determined by the matching degree of the concepts similarities of description terms and functional property constraint.

The concepts similarity is gained by calculating the semantic distance between problem description and description terms of context knowledge resource. The similarity of functional property is get by calculating the problem description and context knowledge resource property [10-12]. The calculate method of concept similarity is as follows:

$$\begin{aligned} Sim_{question}(Qterm, Kterm) &= \sum_{i=1}^n \omega_i \times Cd_sim_i(Qterm, Kterm) \\ &+ \sum_{j=1}^n \omega_j \times Ca_sim_j(Qterm, Kterm) \end{aligned} \quad (7)$$

Additionally, ‘Cd_sim(Qterm, Kterm)’ is the distance similarity of semantic concept. ‘Ca_sim(Qterm, Kterm)’ is the concept property similarity. ‘Qterm’ represents the problem description. ‘Kterm’ is the description of knowledge resources.

$$\begin{aligned}
 Cd_sim_i(Qterm, Kterm) &= \begin{cases} 1, & Qterm, Kterm \text{ before the } i\text{-with the same parent class} \\ 0, & Qterm, Kterm \text{ before } i \text{ not accompanied by a parent class} \end{cases} \\
 Ca_sim_j(Qterm, Kterm) &= \begin{cases} 1, & Qterm, Kterm \text{ before the } j\text{-with the same parent class} \\ 0, & Qterm, Kterm \text{ before } j \text{ not accompanied by a parent class} \end{cases}
 \end{aligned} \tag{8}$$

‘N’ is the maximum depth of ‘Qterm’ and “Kterm” in description model of agricultural knowledge resource ontology. ω is corresponding weight coefficient.

$$\sum_{i=1}^n \omega_i + \sum_{j=1}^n \omega_j = 1.$$

The functional property constrain matching of agricultural knowledge atoms is decided by the domain of knowledge atom and the decision-making service premise data items constrain. The value of constrain is related to the initial value of agricultural knowledge atom. So the constrain value of decision-making problem need to be converted to the interval form. ‘C(Qterm)’ is the value range of problem description sub-constrain. ‘C(Kterm)’ is the value range of knowledge description sub-constrain. μ_k is the weight coefficient of matching degree of constraint. Then the calculating method of similarity degree of functional property is as follows:

$$Fmatch = \begin{cases} 1, & C(Qterm) = C(Kterm) \\ \sum_{k=1}^n \frac{P_k(C(Qterm) \cap C(Kterm))}{P(C(Kterm))} \mu_k, & C(Qterm) \cap C(Kterm) \neq \Phi \\ 0, & C(Qterm) \cap C(Kterm) = \Phi. \end{cases} \tag{9}$$

‘Fmatch’ is weighted sum of ‘Amatch’ and ‘Sim_question’.

$$Amatch = \mu_1 \times Sim_question(R_s, R_d) + \mu_2 \times Fmatch(R_s, RA) \tag{10}$$

In above formula, μ_1, μ_2 means the correspond weight of each type matching degree. And $\mu_1 + \mu_2 = 1$.

6 Agricultural Cooperative Decision-Making Service Mechanisms

The completion of specific agricultural cooperative decision-making service needs multiple process fragments. In the collaborative decision-making process, it's necessary to achieve task decomposition of distributed decision-making services, matching of knowledge resources and intelligent invocation of agricultural cooperative decision-making tasks based on the user demand for services, the context memory of agricultural decision-making service problem flow and the message of user interaction decision-making premise items.

Agricultural cooperative decision-making service module has two main functions: the matching of decision-making problems' knowledge resources and the task decomposition of decision-making services [13-16]. The steps are as follows:

Fig. 2. The collaborative service model of agricultural knowledge resources

Step 1. Matching of decision-making problem knowledge resources based on the demands of user’s decision-making. Model of knowledge resource ontology description can analyse the agricultural knowledge resource, calculate the matching degree of knowledge resource and create a “decision-making service problem chain”.

Step 2. According to the content of “decision-making service problem chain”, decision-making task decomposition modules analyses the type and class degree of service to determine the character of the agricultural knowledge decision-making service and achieve mapping scheduling of decision-making task. Agricultural knowledge service can be divided into compute-intensive knowledge service, communicate-intensive knowledge service and compute-communicate relative equilibrium knowledge service. By analyzing class degree of knowledge service, the number and character of parallel task is determined and each node’s application quality of service resources is obtained. Finally, the analysis results are published regularly.

Step 3. The decision-making task mapping module divides knowledge service into many sub-tasks, using “service character description table”. These sub-tasks include some dependent or preferred constrain relationship and are mapped as some task sets that adapt to different machine characters and service characters. The goal is to make sure the sub-task can be carried out at suitable node.

Step 4. Agricultural collaborative decision-making service task scheduling module based on the result of task mapping, send task to specific node service queue and schedule the decision-making of distributed nodes to execute decision-making task.

Step 5. In the end the result returns. The conflict resolution is finished and the results return to user.

7 Analysis and Application

Based on the agricultural coordination decision-making service mechanism, we use J2EE platform to develop pig diseases collaborative diagnosis system. As the result of the great variety diseases of live pig symptom, although knowledge databases of various nodes follow the unified regulations, the knowledge engineers of system establishment are different, Therefore, the attention points on diagnosis knowledge are different and there are differences on symptom antecedent, the consequent as well as authentication. For this reason, the pig sickness main body is constructed, and by modeling the policy-making service knowledge resources' semantic description, the existing knowledge, the data, the multimedia resources are labeled. So the integrated applications of pig sickness diagnosis knowledge rules and related disease symptom, prevention method and so on are realized in Beijing, Tianjin, Hebei, Sichuan and other providence.

The system not only can recommend users more semantically related concepts based on knowledge of swine, but also can complete collaborative coordination of different expertise for the same diagnosis, and provide various results with recommendations for the diagnosis and disposal program. It's difficult for the traditional agricultural expert system to finish.

Fig. 3. Collaborative decision-making of swine diseases

Fig. 4. Ontology-based Collaborative decision-making of swine diseases

Take 4 swine diseases expert systems as the example; take 20 initial symptoms as the example to deduction, the inference experimental result as shown in Table 1. Comparing collaborative decision-making system based on semantic WEB to traditional expert system, the former has remarkable enhancement on the inference conclusion gain rate, the inference conclusion authentication mean value and the inference efficiency. Such as Rg increases 12.5%, Cn increases 14% and Rc improved 13.3%.

Table 1. Results of reasoning test

System	Kb	R(Gbit)	Rn	Cn	Rg	Rc
Beijing	450	1.8	16	87	80	83.5
Tianjin	347	0.7	14	79	70	74.5
Hebei	512	0.9	17	81	85	83
Sichuan	401	1.1	15	82	75	78.5
Coordination	1710	4.5	19	89	95	92

All the knowledge regular strip counts Kb; Amount of connection resources R; Integer Rn in view of 20 initial symptom's inference conclusions (confidence level threshold 60%); Inference conclusion gain rate $Rg = Rn / 20 * 100$; In view of confidence level of 20 inference conclusion mean values Cn; Inference efficiency $Rc = (Rg + Cn) / 2$.

8 Conclusion

In the application service of distributional knowledge resources, how to realize the knowledge resources coordination decision-making service is important. Based on the semantic WEB technology, the paper, proposed a kind of agriculture decision-making service knowledge resources semantics description model which supports the multi-types, shield isomerism, adaptation dynamically. It defines agricultural knowledge resources semantics description as 7 minor BNF. Based on this foundation, the formalized expression method of policy-making question is studied and the demands of agricultural coordination decision-making service are decomposed into many policy-making parts, according to the agricultural decision-making service question class context memory and user's interactive decision-making premise information. As a result, the match between distributional decision-making service task decomposition and the knowledge resources and the intelligent dispatch service of agricultural coordination decision-making task are realized, enhancing the using efficiency and inference efficiency of agricultural knowledge.

The collaborative service of agricultural knowledge resources is a complex engineering system. The collaborative decision-making service based on semantic WEB proposed in this paper took the semantic main body as the foundation of coordination service. The relationship of the quality of coordination service and the competition of ontology library is high. The future research will focus on the update of the increment of agricultural knowledge resources ontology and the resolution mechanism of coordination service conflict.

Acknowledgments. This paper is supported by a grant from Beijing Nova program (Grant No. 2009B26), a grant from Beijing Academy of Agriculture and Forestry Sciences for Young Scholars and the National Natural Science Foundation of China (Grant No. 60871042).

References

1. Wu, H., Sun, X.: Architecture of agricultural data grid system. *Transactions of the Chinese Society of Agricultural Engineering* 22, 183–186 (2006)
2. Paolucci, M., Kawmura, T., Payne, T., Sycara, K.: Semantic matching of web services capabilities. In: Horrocks, I., Hendler, J. (eds.) *ISWC 2002. LNCS*, vol. 2342, pp. 333–347. Springer, Heidelberg (2002)
3. Sycara, K., Klusch, M., Widof, S.: Dynamic service matchmaking among agents in open information environments. *SIGMOD Record* 281, 47–53 (1999)
4. Sun, J., Miao, H., Liu, L.: Intelligent Service-the Research of Integrating Web Service and Semantic Web. *Computer Engineering And Applications* 40, 144–145 (2004)
5. Wang, X., He, J., Qin, Z., Jia, X.: Web-oriented knowledge description language. *Journal of Beijing University of Aeronautics and Astronautics* 30, 674–678 (2004)
6. Yang, B., Liu, X., Yao, L.: The OWL Description of Ontology-Based Agriculture Domain Knowledge. *Microelectronics & Computer* 24, 58–65 (2007)
7. Gruber, T.: Towards principles for the design of ontologies used for knowledge sharing. *International Journal of Human-Computer Studies* 43, 907–928 (1995)

8. Sun, X., Chen, F., Wu, H.: Technology of Agricultural Production Knowledge Integration Based on Semantic Web. *Transactions of the Chinese Society of Agricultural Engineering* 125, 186–190 (2008)
9. Zhao, C., Wu, H., Yang, B., Sun, X., Wang, J., Gu, J.: Development platform for agricultural intelligent system based on techno-componentware model. *Transactions of the Chinese Society of Agricultural Engineering* 20, 140–143 (2004)
10. Li, M., Wang, D., Du, X., Wang, S.: Ontology Construction for Semantic Web: A Role-Based Collaborative Development Method. *APWeb*, 609–619 (2005)
11. Lei, Y., Zhang, B.: Application-Oriented Web Service Discovery and Matchmaking. *Journal of Northeastern University (Natural Science)* 28, 1544–1547 (2007)
12. Wang, Y., Wang, W., Wang, Z.: Reconfigurable Platform for Knowledge Management Based on Ontology. *Computer Integrated Manufacturing Systems* 9, 1136–1144 (2003)
13. Uschold, M., Gruninger, M.: Ontologies: Principles, methods and applications. *Knowledge Sharing and Review* 11, 76–79 (1996)
14. Holsapple, C.W., Joshi, K.D.: A Collaborative Approach to Ontology Design. *Communications of the ACM* 45, 34–38 (2002)
15. Mei, J., Liu, S., Lin, Z.: Logical Foundation of Semantic Web. *Pattern Recognition and Artificial Intelligence* 18, 513–521 (2005)
16. Ma, S., Gong, F., Liu, F.: Production and distribution collaborative decision-making based on supply hub. *Computer Integrated Manufacturing Systems* 14(12), 2421–2430 (2008)