Erratum: Evaluation of Different Decrease Schemes for LEDBAT Congestion Control

Mirja Kühlewind¹ and Stefan Fisches²

Institute of Communication Networks and Computer Engineering (IKR)
University of Stuttgart, Germany
mirja.kuehlewind@ikr.uni-stuttgart.de
sfisches@ikr.uni-stuttgart.de

R. Lehnert (Ed.): EUNICE 2011, LNCS 6955, pp. 112–123, 2011.
© Springer-Verlag Berlin Heidelberg 2011

DOI 10.1007/978-3-642-23541-2_27

The original version of this article unfortunately contained a mistake in the presentation of the formula on page 116. The corrections are given below:

- 1) Instead of “ $CWND = \frac{TARGET}{current_RTT} \times CWND$ ”,

it should read “ $CWND = (1 - \frac{TARGET}{current_RTT}) \times CWND$ ”

- 2) The line above the formula “Thus β must be $\frac{TARGET}{current_RTT}$.” should read

“Thus the congestion window must be reduced by $\frac{TARGET}{current_RTT} \times CWND$ and

β must be $1 - \frac{TARGET}{current_RTT}$.”

The original online version for this chapter can be found at
http://dx.doi.org/10.1007/978-3-642-23541-2_13