J. DUNWOODY

Errata:
One Dimensional Shock Waves
in Heat Conducting Materials with Memory

Part 1, Vol. 47, pp. 117–148 (1972); Part 2, Vol. 48, pp. 192–204 (1972);
Part 3, Vol. 50, pp. 278–289 (1973)

My attention has been drawn by P.J. CHEN & J.W. NUNZIATO to an error, *viz.* a missing term, in equation (2.10) of Part 1 and in the equation that follows it. The error does not alter any of the results or conclusions drawn in Part 1 or Part 2; Part 3 is affected in Sections 4 and 5, these being the only places in which equation (2.10) is applied.

Having been afforded the opportunity to correct this error, I have also corrected those algebraic and typographical errors which appeared in print. The full corrections I now list under the headings Part 1, *etc.* Some fresh observations are made relative to Sections 4 and 5 of Part 3 and these I put in italics.

PART 1

Page 123. In the final sentence of the footnote replace $\mathcal{F}$ by $\mathcal{F} P$.

Page 124. Equation (2.10) and the first equation in the proof of the corollary are missing terms and should read:

$$\begin{aligned}\frac{d[f]}{dt} &= \left[G_{\mathcal{F}}(0) \frac{dA}{dt} \right] + \int_0^{\infty} [G'_{\mathcal{F}}(s)] \frac{dA'_r(X, s)^+}{dt} ds, \\ \frac{\partial[f]}{\partial X} &= \left[G_{\mathcal{F}}(0) \frac{\partial A}{\partial X} \right] - \frac{G'_{\mathcal{F}}(0)}{U} [A] + \int_0^{\infty} [G'_{\mathcal{F}}(s)] \frac{\partial A'_r(X, s)^+}{\partial X} ds.\end{aligned}$$

That the final term in each should be included is a clear implication of (1.18) and (1.20); thus, in (2.8) $G'_{\mathcal{F}}(s)$ is a non-linear function of $(A'_r(\cdot), A)$.

Equation (2.13) should have the closing bracket after $\frac{1}{2} [\dot{x}]^2$ not after $[T\dot{x}]$.

Page 139. The caption for Figure 3 should be: The diagram is for the case $\tilde{E}^+ < 0$.

Page 140. In the last sentence of the first paragraph the words “explicitly” and “implicitly” should be transposed. In the first sentence of the second paragraph replace $\in$ in $(X, t) \in \mathcal{D} \cap \Sigma$ by $\notin$.

Page 141. In the final sentence replace “(5.1) and (5.2)” by the “inverse of (5.1) and (5.2)” and “specific heat” by “latent heat” in the statement of Theorem 7.

Page 147. Equation (A.39) should read:

$$\Lambda(X, t) = \begin{cases} [\Lambda](X), & (X, t) \in \mathcal{D}^- \cup \Sigma \\ 0, & (X, t) \in \mathcal{D}_0^+. \end{cases}$$

PART 3

Page 284. The first three equations here, viz. (3.1), (3.2) and (3.3) must have the following terms added to their right hand sides:

$$\int_0^\infty [G'_{\mathcal{F}}(s)] \frac{\partial A_r^t(X, s)^+}{\partial X} ds, \quad \int_0^\infty [G'_{\mathcal{F}}(s)] \frac{\partial A_r^t(X, s)^+}{\partial t} ds$$

and

$$\int_0^\infty [G'_{\mathcal{F}}(s)] \frac{dA_r^t(X, s)^+}{dt} ds,$$

respectively.

Also, in the right hand side of equation (3.4) $\frac{E_I}{\rho_0}$ in the first term should be $\frac{E_I^-}{\rho_0}$ and the term $-\frac{1}{2\rho_0\sqrt{U}} \int_0^\infty [G'_{\mathcal{F}}(s)] \frac{\partial A_r^t(X, s)^+}{\partial X} ds$ must be added.

Similarly equations (3.5) and (3.6) must have added to their right hand sides the terms

$$\frac{1}{2\rho_0 U [F]} \int_0^\infty [G'_{\mathcal{F}}(s)] \frac{dA_r^t(X, s)^+}{dt} ds$$

and

$$-\frac{1}{2\rho_0 U} \int_0^\infty [G'_{\mathcal{F}}(s)] \left\{ \frac{1}{2U} \frac{dA_r^t(X, s)^+}{dt} + \frac{\partial A_r^t(X, s)^+}{\partial X} \right\} ds, \quad \text{respectively.}$$

Page 286. Section 4 remains unaffected except for the last paragraph. There the sentence beginning "The solution of Rankine [10] ..." must be changed to read: "The solution of Rankine for an ideal, heat conducting, inviscid gas (see HAYES [11]) describes a steady motion, which is uniform behind the shock wave and non-uniform but steady ahead of it, in a Galilean frame moving with the constant wave velocity U in the direction of propagation." The necessary and sufficient condition which follows should be

$$\frac{\bar{\kappa}[F]}{4\rho_0 U} \left\{ -\frac{\partial F^+}{\partial X} + \frac{2}{\bar{\kappa}[F]} \left(G_1'(0)^- [F]/U - \int_0^\infty [G'_{\mathcal{F}}(s)] \frac{\partial A_r^t(X, s)^+}{\partial X} ds + \frac{\rho_0 L_I^+ [g]}{\theta} \right) \right\} = 0$$

and the critical strain gradient obtained therefrom is

$$\bar{\lambda} = \frac{2}{|\bar{\kappa}[F]|} \left(\frac{G_1'(0)^- [F]}{U} - \int_0^\infty [G'_{\mathcal{F}}(s)] \frac{\partial A_r^t(X, s)^+}{\partial X} ds + \frac{\rho_0 L_I^+ [g]}{\theta} \right).$$

The relation which holds for a gas has $G'_{\mathcal{F}}(s) = \phi$ for all s .

In a Galilean frame related to the reference frame by

$$\bar{X} = Ut - X,$$

such that for a standing wave at $\bar{X} = 0$ the velocity and deformation satisfy

$$\dot{x} = -UF = f(\bar{X}),$$

the preceding two relations become

$$\frac{\bar{\kappa}[F]}{4\rho_0 U} \left\{ -\frac{\partial F^+}{\partial X} + \frac{2}{\bar{\kappa}[F]} \left(G'_1(0)^- \frac{[F]}{U} - U^{-1} \int_0^\infty \left[G'_{\mathcal{F}} \left(\frac{\bar{X}}{U} \right) \right] \frac{d\bar{\Lambda}(\bar{X})}{d\bar{X}} d\bar{X} - \frac{\rho_0 L_I^+ g^+}{\theta} \right) \right\} = 0$$

and

$$\bar{\lambda} = \frac{2}{|\bar{\kappa}[F]|} \left(\frac{G'_1(0)^- [F]}{U} - U^{-1} \int_0^\infty \left[G'_{\mathcal{F}} \left(\frac{\bar{X}}{U} \right) \right] \frac{d\bar{\Lambda}(\bar{X})}{d\bar{X}} d\bar{X} + \frac{\rho_0 L_I^+ |[g]|}{\theta} \right).$$

Both of these relations can be put in terms of the Eulerian, or space variable $x (= \bar{x}(\bar{X}) = \tilde{x}(X, t))$ by using

$$F = \frac{\partial x}{\partial X} = \frac{\partial x}{\partial \bar{X}}.$$

However, complication is then introduced via the argument of the memory function $G'_{\mathcal{F}} \left(\frac{\bar{X}}{U} \right)$.

Page 287. In the right hand side of (5.2) the last two terms are given correctly, along with an additional term, by

$$+ \frac{3}{4\rho_0 U} \left([E_I] \frac{\partial F^+}{\partial X} + \int_0^\infty [G'_{\mathcal{F}}(s)] \frac{\partial F_r^t(X, s)^+}{\partial X} ds \right) - \frac{3[L_I] g^+}{4\theta U}.$$

Thus, in the purely mechanical theory, the wave strength may increase if

$$\left([E_I] \frac{\partial F^+}{\partial X} + \int_0^\infty [G'_1(s)] \frac{\partial F_r^t(X, s)^+}{\partial X} ds \right) > 0$$

even though the jump in strain gradient is less than critical. If the material ahead of the wave is in a steady condition then the wave strength may increase if

$$\frac{\partial F^+}{\partial X} > 0,$$

since it is to be expected that $[E_\infty] > 0$, where $E_\infty (= G_1(\infty))$ is the equilibrium elastic response.

At the bottom of page 287, $G'_1(0)^-$ may be replaced by $G'_{\mathcal{F}}(s)$. Thus

$$G'_{\mathcal{F}}(s)^- = G'_{\mathcal{F}}(s)^+ + o(1)$$

for $o < |[F]| = \delta \ll 1$.

Page 288. The above equation shows that the list (5.3)–(5.6) should include also

$$[G'_{\mathcal{F}}(s)] = \tilde{G}'_{\mathcal{F}}(s)^+ [F] + o([F]),$$

where

$$\tilde{G}'_{\mathcal{F}}(s) = \frac{\partial G'^*(\Delta F, \Delta \theta; s)}{\partial \Delta F}$$

and

$$\int_0^\infty \tilde{G}'_{\mathcal{F}}(s)^+ \frac{\partial A'_r(X, s)^+}{\partial X} ds / \rho_0 U \frac{d|[F]|}{dt} = o(1)$$

should be added to the list of linearizing assumptions (5.10)–(5.12).

In equation (5.13) the terms not in brackets should read

$$\frac{3}{4\rho_0 C} \left(|\tilde{E}_I^+[F]| \frac{\partial F^+}{\partial X} + [F] \int_0^\infty \tilde{G}'_{\mathcal{F}}(s)^+ \frac{\partial A'_r(X, s)^+}{\partial X} ds \right) + \frac{3|\tilde{L}_I^+[F]|}{4\theta C} g^+.$$

In the last sentence of this page the phrase “(5.11) and (5.12)” should be read as referring to (5.11) and (5.12) as just supplemented.

Page 289. In the final sentence the phrase “(5.10), (5.11) and (5.12), (5.13)” should be read as referring to those equations as just supplemented.

Department of Engineering Mathematics
The Queen's University of Belfast

(Received December 3, 1974)