Introduction

It is my pleasure to introduce this third Special Issue on Genetic Algorithms (GAs). The articles presented here were selected from preliminary versions presented at the International Conference on Genetic Algorithms in June 1991, as well as at a special Workshop on Genetic Algorithms for Machine Learning at the same Conference.

Genetic algorithms are general-purpose search algorithms that use principles inspired by natural population genetics to evolve solutions to problems (Holland, 1975). The basic idea is to maintain a population of knowledge structures that represent candidate solutions to the problem of interest. The population evolves over time through a process of competition (i.e., survival of the fittest) and controlled variation (i.e., recombination and mutation). For further background material on GAs for machine learning, interested readers are referred to Davis (1991), De Jong (1990), Goldberg (1989), and Holland (1986).

Previous special issues on GAs (volume 3, numbers 2–3; volume 5, number 4) as well as articles appearing in regular issues of *Machine Learning*, have given a fair indication of the rich variety of work in the field. Although there certainly has not been exhaustive coverage of any topic, there have been several good illustrations of the use of genetic algorithms in classifier systems, in systems that learn sequential decision rules, and in systems that perform parameter learning. Taking the previous distribution of topics into account, the current issue is devoted to filling in some of the gaps. Consequently, this issue contains articles on three topics that have not been the focus of many previous articles on GAs in *Machine Learning*, namely, concept learning from examples, reinforcement learning for control, and theoretical analysis of GAs. It is hoped that this sample will serve to broaden the acquaintance of the general machine learning community with the major areas of work on GAs.

The articles in this issue address a number of central issues in applying GAs to machine learning problems. For example, the choice of an appropriate representation and the corresponding set of genetic learning operators is an important set of decisions facing a user of a genetic algorithm. The first two articles in this issue illustrate two contrasting approaches. One approach is to adopt the traditional string representation and its corresponding crossover and mutation operators. This approach offers the advantage of a good fit with the theoretical analysis that has been performed to date, as well as the convenience of using widely available software. The article by De Jong, Spears, and Gordon takes this minimalist approach to the problem of learning concepts from examples. A second approach is taken in the article by Janikow. The idea here is to adopt a representation (e.g., symbolic rules) that more closely reflects that semantics of the specific problem to be solved (e.g., concept learning), and to design specialized genetic operators (e.g., rule specialization, rule generalization) that take advantage of the particular representation being used. The second approach offers the possibility of exploiting knowledge about the problem being solved in the hope of achieving a more efficient search. The second approach also offers the advantage of possibly combining genetic algorithms with other problem-solving methods, as illustrated by the SAMUEL system in the domain of sequential decision making (Grefenstette, Ramsey, &

Schultz, 1990), but it relies on an assumption that the important search properties of GAs carry over to the new formulation. The results presented here show that both approaches can work reasonably well, compared to traditional symbolic concept learning systems. Whether one approach to GA-based learning should be preferred over the other remains an interesting open question.

Both of the first two articles also explore the issue of dynamically adjusting the bias of the genetic search during learning. De Jong et al. adjust the bias explicitly by including switches for alternative operators as part of the evolving knowledge structures. Janikow dynamically adjusts the probability of applying his extended set of operators based on the consistency and completeness of the current hypotheses. Both articles reflect a growing trend in GAs to reduce the number of free parameters in a GA by enabling the system to adapt its internal operations during the course of the search.

Another important dimension along with GAs differ is whether the knowledge structures in the population represent independent solutions or dependent components of a single solution. For example, each structure in SAMUEL represents an entire set of decision rules (Grefenstette et al., 1990), whereas the individuals in classifier systems represents single rules (Holland, 1986; Wilson 1987). The first two articles in this issue take the former approach, while the third article in this issue, by Greene and Smith, adopts the latter approach to concept learning. The innovation here is to measure the fitness of each rule in terms of both its classification accuracy and its ability to cover training examples not covered by other rules. Empirical results show that this "population-as-model" approach is competitive with existing symbolic induction methods.

The first three articles use what is commonly called the "generational model" of GAs. In this model, during each generation, a new population of knowledge structures is formed in two steps. First, structures in the current population are selected to be reproduced on the basis of their relative fitness. That is, high-performing structures may be chosen several times for replication, and poorly performing structures may not be chosen at all. Second, the selected structures are recombined using idealized genetic operators to form a new set of structures that are then evaluated as solutions to the given problem. The fourth article in this issue, by Whitley, Dominic, Das, and Anderson, presents a different model, called the "steady-state" GA. In the steady-state model, the GA selects two parent structures, recombines them, evaluates them, and adds them to the population, replacing some older structures. These two approaches represent different ways to simulate an essentially parallel algorithm on a sequential computer. The mathematical differences between the approaches depend on the details of the selection algorithms, and are still the object of discussion within the GA community. The steady-state approach appears to offer certain implementation advantages on massively parallel architectures. Whitley et al. apply the steady-state approach to a classic problem of learning to control an inverted pendulum system, using the GA to learn weights for a neural network. A set of empirical comparisons between the GA and the well-known Adaptive Heuristic Critic (AHC) show that rates of performance improvements are comparable, but the GA appears to be more robust in the sense that it can learn to successfully control the system from a wider range of initial conditions.

The reliance on empirical studies in the preceding articles is an indication of the current state of the art in GAs: we are clearly still in an experimental stage. Nonetheless, ever since Holland's original analysis, there has always been a high level of interest in developing a more theoretical characterization of the information processing mechanisms at work in

GAs. Viewed in the most general light, GAs gather information about regularities in the search space defined by the problem representation and the fitness function, and dynamically allocate future search effort to promising regions of that space. Some central questions are, then, what classes of landscapes are most easily searched by GAs, and what classes present the most challenging problems for GAs. While definitive answers are yet to be found, a number of interesting analytic tools have been developed that may help to characterize the difficulties associated with different fitness functions. The final article in this issue, by Forrest and Mitchell, provides a tutorial on some of these analytic methods for GAs. The article also provides an admirable example of replicating some previously reported empirical results that at first appeared puzzling, and then performing additional studies to distinguish among alternative theoretical explanations.

Beyond the results appearing in these articles, there have been a number of other interesting recent developments within the GA field. In the last few years, there has been an increasing level of communication and cooperation between formerly independent research communities. In North America, most of the GA community has been elaborating on the framework developed by John Holland during the 1960s and 1970s at the University of Michigan. In Europe, a similar framework, called the *EvolutionStrategie* (ES), was developed independently about the same time by Rechenberg and Schwefel (see back, Hoffmeister, & H.-P. Schwefel, 1991, for a survey of this area). While the GA community has focused on simple string representations that support general-purpose problem solving, and binary recombination operators like crossover, the ES community has generally focused on engineering applications involving function optimization, relying on sophisticated mutation operators to create variants in the population. This work has reawakened interest in the early work on mutation-based Evolutionary Programming (Fogel, Owens, & Walsh, 1966). The cross-fertilization of these research communities has begun to bear fruit (Schwefel & Maenner, 1991), and there is growing interest in moving toward a common framework, which has been called *Evolutionary Computation*.

The theoretical foundations of GAs continue to receive a high level of attention. Besides sessions devoted to theory within the main Conferences, there have been two specialized workshops on Foundation of Genetic Algorithms (FOGA), focusing on such issues as the mathematical models of genetic algorithms, characterization of problem difficulty, the role of representation, and the effects of various forms of genetic operators. The article by Forrest and Mitchell gives a sampling of the flavor of this work. For more of these topics, interested readers are referred to edited versions of the FOGA proceedings, which have been published in book form (Rawlins, 1991; Whitley, 1992).

Applications are also proceeding along a wide range of domains. A good survey of successful applications, along with a tutorial on implementation strategies, appears in the *Handbook of Genetic Algorithms*, edited by L. Davis (1991). In summary, the study of genetic algorithms is proceeding at a robust pace. If experimental progress and theoretical understanding continue to evolve as expected, genetic algorithms will continue to provide a distinctive approach to machine learning.

John J. Grefenstette
Navy Center for Applied Research in AI
Naval Research Laboratory
Washington, DC 20375-5000

References

- Back, T., Hoffmeister, F., & Schwefel, H.-P. (1991). A survey of evolution strategies. *Proceedings of the Fourth International Conference on Genetic Algorithms* (pp. 2–9). San Mateo, CA: Morgan Kaufmann.
- Davis, L. (Ed.). (1991). *Handbook of genetic algorithms*. New York: Van Nostrand Reinhold.
- De Jong, K.A. (1990). Genetic-algorithm-based learning. In Y. Kodratoff & R. Michalski (Eds.), *Machine learning: An artificial intelligence approach* (Vol. 3). San Mateo, CA: Morgan Kaufmann.
- Fogel, L.J., Owens, A.J., & Walsh, M.J. (1966). *Artificial intelligence through simulated evolution*. New York: Wiley.
- Goldberg, D.E. (1989). *Genetic algorithms in search, optimization, and machine learning*. Reading, MA: Addison-Wesley.
- Grefenstette, J.J., Ramsey, C.L., & Schultz, A.C. (1990). Learning sequential decision rules using simulation models and competition. *Machine Learning*, 5(4), 335–381.
- Holland, J.H. (1975). *Adaptation in natural and artificial systems*. Cambridge, MA: MIT Press.
- Holland, J.H. (1986). Escaping brittleness: The possibilities of general-purpose learning algorithms applied to parallel rule-based systems. In R.S. Michalski, J.G. Carbonnell, & T.M. Mitchell (Eds.), *Machine learning: An artificial intelligence approach* (Vol. 2). Los Altos, CA: Morgan Kaufmann.
- Rawlins, G.J.E. (Ed.). (1991). *Foundations of genetic algorithms*. San Mateo, CA: Morgan Kaufmann.
- Schwefel, H.-P., & R. Maenner (1991). *Parallel problem solving from nature*. Lecture Notes in Computer Science 496. Berlin: Springer-Verlag.
- Whitley, D. (Ed.). (1992). *Foundations of genetic algorithms 2*. San Mateo, CA: Morgan Kaufmann.
- Wilson, S.W. (1987). Classifier systems and the animat problem. *Machine Learning*, 2, 199–228.