Penny-Packing and Two-Dimensional Codes

R. L. Graham and N. J. A. Sloane

Mathematical Sciences Research Center, AT&T Bell Laboratories,
Murray Hill, NJ 07974, USA

Abstract. We consider the problem of packing n equal circles (i.e., pennies) in the plane so as to minimize the second moment U about their centroid. These packings are also minimal-energy two-dimensional codes. Adding one penny at a time according to the greedy algorithm produces a unique sequence of packings for the first 75 pennies, and appears to produce optimal packings for infinitely many values of n . Several other conjectures are proposed, and a table is given of the best packings known for $n \leq 500$. For large n , $U \sim \sqrt{3}n^2/(4\pi)$.

1. The Penny-Packing Problem

We wish to find the tightest packing in the plane of n equal circular disks, pennies for example, for $n = 1, 2, \dots$. Groemer, Wegner, and others have considered minimizing the area of the convex hull of the pennies [8], [15], but for our applications it is more appropriate to minimize their second moment.

Suppose the pennies have diameter d , let $P_1, \dots, P_n$ be their centers and $\bar{P} = n^{-1} \sum P_i$ their centroid. Then the problem is to choose points $P_1, \dots, P_n$ so as to satisfy

$$\|P_i - P_j\| \geq d, \quad i, j = 1, \dots, n, i \neq j, \quad (1)$$

and so that the *second moment*

$$U = \frac{1}{d^2} \sum_{i=1}^n \|P_i - \bar{P}\|^2 \quad (2)$$

is minimized, where $\|\cdot\|$ is the Euclidean distance. Let $U(n)$ be the minimal value of U (which can always be attained). A set of points $\mathcal{P} = \{P_1, \dots, P_n\}$ satisfying (1) is called an n -point *packing*, and is *optimal* if it attains $U(n)$.

The second moment U is a reasonable parameter to minimize, for several reasons. For applications to signal design, when the points $P_1, \dots, P_n$ form a two-dimensional *code* [3], [4], [7], U measures the energy in the code. Figure 1(b), for example, shows what is conjectured to be the 16-point code with the smallest possible energy [4]. Furthermore, the results look tightly packed (Fig. 1(a)–(c)), and when applied to packings in higher dimensions this criterion avoids the “sausage catastrophe” [5].

Penny packings also have applications in *cluster chemistry* [9], [14], quantiz-

Fig. 1. Packings of 7, 16, and 19 pennies that are believed to have the smallest second moments.

ation, and other areas [14]. Figure 1(c), for example, shows the 19 strands of wire in a cross-section of the cables used in the Brooklyn bridge [12]. The packing formed by pennies 1 to 37 in Fig. 4 occurs in the cross-section of an optical-fiber cable [11].

2. The Hexagonal Lattice

The familiar *hexagonal lattice* A_2 is spanned by $(1, 0)$ and $(\frac{1}{2}, \sqrt{3}/2)$. If we take $d = 1$ then any subset of A_2 is a packing.

Conjecture 1. *For $n \neq 4$ every optimal packing is (apart from a magnification, rotation and translation) a subset of A_2 .*

The case $n = 4$ is exceptional, since all packings of the type shown in Fig. 2 have $U = 2$ (as long as each penny touches its two neighbors), and in general these are not subsets of A_2 . Our investigations suggest that $n = 4$ is the only exception, although we cannot prove this.

Any point $P \in A_2$ can be written as

$$r(1, 0) + s\left(\frac{1}{2}, \frac{\sqrt{3}}{2}\right) = \left(r + \frac{s}{2}, \frac{s\sqrt{3}}{2}\right)$$

for $r, s \in \mathbb{Z}$; we call $\langle r, s \rangle$ oblique coordinates for P . There is a convenient formula for the second moment U of a subset $\{P_1, \dots, P_n\} \subseteq A_2$. Let P_i have oblique

Fig. 2. Optimal packings of four pennies. The second moment is constant, as long as each penny touches its two neighbors.

coordinates $\langle r_i, s_i \rangle$, and set $M_r = \sum r_i$, $M_s = \sum s_i$, $M_{rr} = \sum r_i^2$, $M_{rs} = \sum r_i s_i$, and $M_{ss} = \sum s_i^2$. Then

$$U = (M_{rr} + M_{rs} + M_{ss}) - \frac{1}{n} (M_r^2 + M_r M_s + M_s^2). \quad (3)$$

3. Constructions

We shall use three methods to construct packings.

(i) *The Greedy Algorithm.* A sequence of packings $\mathcal{P}_1, \mathcal{P}_2, \mathcal{P}_3, \dots$ is produced by the greedy algorithm if (a) $\mathcal{P}_1$ contains a single point, and (b) for $n = 2, 3, \dots$,

$$\mathcal{P}_n = \mathcal{P}_{n-1} \cup \{P_n\}$$

minimizes U over all choices of P_n satisfying (1). (There are many such sequences.)

(ii) *Circular Clusters in A_2 with a Specified Center.* Let C be a fixed point of the plane, let t be a real number, and let

$$\mathcal{Q} = \{P \in A_2 : \|P - C\| \leq t\}.$$

In general, the centroid of $\mathcal{Q}$ will not coincide with C . If it does, we call $\mathcal{Q}$ a *circular cluster* with center C .

The three most important cases occur when C is an element of A_2 , e.g.,

$$C_1 = \langle 0, 0 \rangle \quad (4)$$

in oblique coordinates, C is midway between two neighboring elements of A_2 , e.g.,

$$C_2 = \langle \frac{1}{2}, 0 \rangle, \quad (5)$$

or C is at the center of three neighboring elements of A_2 , e.g.,

$$C_3 = \langle \frac{1}{3}, \frac{1}{3} \rangle. \quad (6)$$

Figure 1(a) and (c) shows examples of clusters centered at C_1 . Figure 5 below shows a cluster centered at C_2 .

(iii) *The Iterative Construction.* The following iterative procedure produces an n -point packing with a small value of U . Choose a random initial point T_0 . For $k = 1, 2, \dots$ let $\mathcal{S}$ be the smallest circle around T_{k-1} that contains at least n points

of A_2 , let $\mathcal{R}_k$ be obtained by discarding just enough (randomly chosen) points from the perimeter of $\mathcal{S}$ to leave n points, and let T_k be the centroid of $\mathcal{R}_k$. The sequence $\mathcal{R}_1, \mathcal{R}_2, \dots$ converges rapidly to an n -point circular cluster $\mathcal{R}$ in A_2 .

The construction may now be repeated with a different choice for T_0 , and after a number of tries the cluster with the smallest second moment is selected.

For example, when $n = 16$, if the initial point T_0 is close to the origin, the algorithm usually converges in one step to the cluster shown in Fig. 1(b), which has centroid

$$C_{16} = \langle \frac{1}{4}, 0 \rangle. \quad (7)$$

4. Results

The most remarkable result, and our motivation for writing this note, is the following.

The greedy algorithm produces a unique packing for the first 75 pennies. (“Unique” means unique up to symmetry, of course. There are six ways to add a penny to Fig. 1(a), for example, but all are equivalent under symmetries of A_2 .)

There are two essentially distinct choices for the 76th penny, both leading to packings with the same second moment. Whichever is chosen, the other must be chosen next, and the 77-point packing is unique (see Fig. 3). The packings now remain unique up to 313 pennies, when again there are two inequivalent choices. The 313-point packing is shown in Fig. 4, together with two inequivalent choices for the 314th penny. The two paths merge again at the 318th penny, and the next choice occurs at the 354th penny (see Fig. 3).

The pennies in Fig. 4 are labeled sequentially, so in this figure one can see the n -point packings produced by the greedy algorithm for all $n \leq 313$.

Beyond 354 pennies we only followed one path of the greedy algorithm, which next splits at the 426th penny.

Table 1 combines the best results produced by the three algorithms (using 100 random initial points for the iterative construction). Table 1(a) gives the smallest second moment found for all packings of $n \leq 100$ pennies. Table 1(b) gives a selection of the best packings found for $101 \leq n \leq 500$, including all the cases where the best packing is a cluster centered at C_1, C_2 , or C_3 , and some of the

Fig. 3. Sequences of packings found by the greedy algorithm.

Fig. 4. Packing of the first 313 pennies found by the greedy algorithm. There are two inequivalent but equally good choices for the 314th penny (shaded).

cases where the greedy algorithm is the best (often just giving the beginning and end of a run of successes for the greedy algorithm).

A superscript g in the table indicates that the packing is produced by the greedy algorithm, and an asterisk that it is definitely *not* produced by the greedy algorithm. An integer superscript k denotes a circular cluster in the A_2 lattice with center C_k . We have defined C_1 , C_2 , C_3 , and C_{16} in equations (4)–(7); some other interesting centers are

$$\begin{aligned}
 C_5 &= \langle \frac{1}{5}, \frac{1}{5} \rangle, & C_6 &= \langle \frac{1}{6}, 0 \rangle, & C_8 &= \langle \frac{1}{8}, \frac{1}{8} \rangle, \\
 C_{15} &= \langle \frac{5}{15}, \frac{1}{15} \rangle, & C_{20} &= \langle \frac{2}{20}, \frac{1}{20} \rangle, & C_{32} &= \langle \frac{3}{32}, 0 \rangle, \\
 C_{44} &= \langle \frac{1}{4}, \frac{1}{4} \rangle, & C_{60} &= \langle \frac{1}{15}, 0 \rangle, & C_{256} &= \langle \frac{18}{256}, \frac{8}{256} \rangle.
 \end{aligned} \tag{8}$$

A superscript α indicates that the packing is known not to be unique. (For example 48-point clusters with the same second moment may be centered at either C_2 or C_3 .)

Our second discovery is that the greedy algorithm produces surprisingly good results. It finds all the best packings known for $n \leq 21$, including those of Fig. 1(a)–(c), and many clusters centered at C_1 , C_2 , or C_3 that are the best known.

Table 1. (a) Smallest second moment U for any known packing of $n \leq 100$ pennies. The left column gives n ; the other symbols are explained in the text.
(b) A selection of the best packings for $n \leq 500$.

(a)											
n	0^{1g}	0.5^{2g}	1^{3g}	$2^{2g\alpha}$	3.4^{5g}	4.833^{6g}	6^{1g}	8.625^{8g}	11^{1g}	13.5^{2g}	
1-10											
11-20	16.455 ^g	19 ^{3g}	23 ^g	26.5 ^{2g}	30.933 ^{15g}	35 ^{16g}	39.294 ^g	43.778 ^g	48 ^{1g}	54.65 ^{20g}	
21-30	60.714 ^g	66.5 ^{2*}	72.478 ^g	78.958 ^g	85.48 ^g	92.423 ^g	99 ^{3g}	107.04 ^g	115.38 ^g	123.5 ^{2*}	
31-40	132 ^{1*}	140.72 ^{32*}	149.18 [*]	157.94 ^g	167.23 ^g	176.75 ^g	186 ^{1g}	197.68 ^g	209.08 ^g	220.33 [*]	
41-50	231.41 [*]	242 ^{3*}	254.05 [*]	265.75 ^{44*}	277.91 ^g	290.46 ^g	303.40 ^g	316 ^{2g\alpha}	329.96 [*]	343.54 ^g	
51-60	358.04 ^g	372.25 ^{44g}	387.08 [*]	400.76 [*]	441 ^{1*}	429.71 [*]	445.16 ^g	460.90 ^g	477.19 ^g	493.73 ^{60g}	
61-70	510 ^{1g}	528.69 ^g	546.81 ^g	564 ^{2*}	581.97 [*]	599.77 [*]	617.36 [*]	635.41 [*]	653 ^{3*}	673.04 [*]	
71-80	692.75 ^g	712.88 ^g	732.95 ^g	753.34 ^g	773.48 ^g	794 ^{2g\alpha}	816.45 ^g	838.42 ^g	859.90 [*]	881.36 [*]	
81-90	903 [*]	925.10 [*]	947.02 [*]	968.75 [*]	990 ^{1*}	1014.7 ^g	1039.1 ^g	1063.9 ^g	1089.2 ^g	1114.7 ^g	
91-100	1140 ^{1g}	1165.9 [*]	1191.2 [*]	1216.4 [*]	1243.0 [*]	1269 ^{2*}	1295.8 [*]	1322.4 [*]	1349.0 [*]	1375.4 [*]	

(b)											
n	U	n	U	n	U	n	U	n	U	n	U
102	1,429 ^{3*}	163	3,654 ^{1*}	220	6,667.1 ^g	288	11,427 ^{2*}	341	16,021 ^g	418	24,082 ^g
107	1,576.5 ^g	164	3,701.7 ^g	225	6,969 ^{3g}	290	11,588 ^g	344	16,304 ^g	421	24,420 ¹
108	1,606 ^{2*}	174	4,168 ^{3*}	228	7,160.8 ^g	301	12,480 ^{1*}	345	16,399 ^{3*}	432	25,824 ¹
109	1,636.0 ^g	179	4,412.8 ^g	230	7,286.5 [*]	306	12,896 ^g	346	16,495 ^g	439	26,550 ¹
110	1,666.5 ^{2g}	180	4,462.3 ^{44g}	234	7,543.4 ^g	313	13,488 ^{1g}	350	16,882 ^g	450	27,907 ²
121	2,010 ^{1*}	181	4,512.7 ^g	238	7,804.5 ^{2g}	314	13,579 ^{g\alpha}	352	17,076 ²	454	28,406 ²
122	2,045.7 ^g	186	4,764.5 ^{**}	241	8,004 ^{1*}	315	13,669 ^g	361	17,952 ¹	465	29,789 ³
123	2,081.1 ^g	188	4,869.2 ^g	253	8,808 ^{1*}	316	13,759 ^g	367	18,552 ¹	471	30,565 ³
127	2,222.7 ^g	192	5,080 ^{1*}	255	8,952.9 ^{60g}	317	13,848 ^g	379	19,788 ¹	472	30,697 ^g
128	2,257.4 [*]	199	5,448 ^{1*}	256	9,024.9 ^{256g}	318	13,937 ^g	390	20,956 ³	473	30,829 ^g
130	2,327.5 ^{2*}	211	6,132 ^{1*}	265	9,676.4 ^g	319	14,026 ^{1*}	396	21,606 ³	480	31,749 ²
132	2,399.9 ^g	212	6,193 ^{2*}	268	9,896 ^{2*}	321	14,201 ^{3*}	400	22,046 ^g	482	32,014 ²
140	2,697.4 ^g	217	6,489.3 ^g	276	10,493 ^{3*}	324	14,466 ^{2*}	402	22,268 ³	499	34,302 ¹
141	2,735 ^{3g}	218	6,548.2 ^g	279	10,721 ^g	333	15,279 ^{3*}	406	22,712 ²		
151	3,138 ^{1*}	219	6,607 ^{3*}	285	11,191 ^g	339	15,833 ^{3*}	409	23,051 ^g		

Conjecture 2. *The greedy algorithm produces optimal packings for infinitely many values of n .*

Figure 5 shows a 22-point cluster centered at C_2 that is better than that found by the greedy algorithm. The results suggest:

Conjecture 3. *Circular clusters in the hexagonal lattice centered at the points C_1 , C_2 , or C_3 (or at equivalent points in the lattice) are optimal packings for infinitely many values of n . Clusters centered at any other point are optimal for only finitely many values of n .*

For example, out of all the centers $C_5, \dots, C_{256}$ defined in (7) and (8), only C_{44} and C_{60} occur more than once in the table.

There are also many examples where the greedy algorithm produces packings that are better than clusters centered at C_1 , C_2 , or C_3 (e.g., $n = 13, 6, 8$, respectively).

The experimental evidence suggests that all the packings in Table 1 are optimal. Unfortunately we can only determine the optimal packings for $n \leq 5$.

Physicists have considered similar problems in three dimensions [1], [10], although not exactly from this point of view. It would be nice to know what the greedy algorithm produces in three or more dimensions.

5. Lower Bounds on $U(n)$

The optimal packings of one, two, and three pennies are obvious, and it is easy to show that the packings of four pennies in Fig. 2 are optimal.

Theorem 1. *The five-penny packing in Fig. 6(a) is optimal, and $U(5) = 3.4$.*

Sketch of Proof. Let $P_1, \dots, P_5$ be the centers of an optimal packing $\mathcal{P}$ of five pennies of diameter 1. The corresponding adjacency graph G has a node for each penny, two nodes being joined by an edge if the pennies touch. It is easy to show that the only possibilities for G are the four connected graphs in Fig. 6(b)–(e), in which all nodes have valency ≥ 2 . Figure 6(b) corresponds to Fig. 6(a). The graphs in Fig. 6(c) and (d) have one degree of freedom. It is a straightforward exercise in calculus to show that the second moment U for Fig. 6(c) and (d) is minimized when an extra edge occurs and the graphs reduce to Fig. 6(b).

The pentagon in Fig. 6(e) has two degrees of freedom. Let the points P_i be $(-\cos \theta, 0)$, $(0, -\sin \theta)$, $(\cos \theta, 0)$, $(\cos \theta - \cos \alpha, \sin \alpha)$, and $(-\cos \theta + \cos \beta, \sin \beta)$. The condition $\|P_4, P_5\| = 1$ implies

$$4 \cos^2 \theta - 4 \cos \theta (\cos \alpha + \cos \beta) + 2 \cos(\alpha + \beta) + 1 = 0. \quad (9)$$

Fig. 5. A 22-point cluster centered at C_2 . This is the smallest known example of a packing that is better than any found by the greedy algorithm.

Fig. 6. (a) and (b) Optimal packing of five pennies. (c)–(e) Other arrangements of five pennies.

Using (9) we find that

$$U = \{\sin \theta \sin s(4(\cos^2 \theta + \cos^2 s) - 1) \\ + \cos \theta \cos s(12(\cos^2 \theta - \cos^2 s) + 25)\} / (10 \cos \theta \cos s),$$

where $s = (\alpha + \beta)/2$. We wish to prove that there is no local minimum of U in the interior of the permissible range of values of θ , α , and β . This will imply that the minimum of U is attained at the boundary, when the graph has an additional edge and has therefore already been discussed.

The conditions $\partial U / \partial \theta = \partial U / \partial s = 0$ imply

$$\sqrt{1-u^2}(8v^4-4v^2+4u^2-1) = \sqrt{1-v^2}(24uv^3), \quad (10)$$

$$\sqrt{1-v^2}(-8u^4-4v^2+4u^2+1) = \sqrt{1-u^2}(24u^3v), \quad (11)$$

where $u = \cos s$, $v = \cos \theta$. We square (10) and (11) and eliminate v , obtaining a condition $f(u) = 0$, where f is a polynomial of degree 42 with integer coefficients. For each root u with $-1 \leq u \leq 1$ we determine v from (10) and (11) and hence θ , s , α , and β . It turns out that there is no solution to (10) and (11) for which the angles lie in the permissible range. This completes the proof. $\square$

Oler's inequality [6], [13] leads to a lower bound on $U(n)$ for all n .

Theorem 2.

$$U(n) \geq \sum_{k=1}^n \left\{ \left(\frac{\sqrt{3}}{2\pi} (k-1) + \frac{3}{16} \right)^{1/2} - \frac{\sqrt{3}}{4} \right\}^2. \quad (12)$$

Proof. Let $\{P_1, \dots, P_n\}$ be an optimal packing of pennies of diameter 1, let $d_k = \|P_k - \bar{P}\|$, and assume $d_1 \leq d_2 \leq \dots$. Let C_r be a circle of radius r centered at $\bar{P}$. Oler's inequality states that if

$$k > \frac{2\pi}{\sqrt{3}} r^2 + \pi r + 1,$$

then $P_k \notin C_r$, and so $d_k > r$. Therefore

$$d_k \geq \left(\frac{\sqrt{3}}{2\pi} (k-1) + \frac{3}{16} \right)^{1/2} - \frac{\sqrt{3}}{4}$$

which implies (12).

Unfortunately (12) is not strong enough to imply Theorem 1, nor (for example) to show the optimality of Fig. 1(a).

Corollary. As $n \rightarrow \infty$,

$$U(n) \sim \frac{\sqrt{3}}{4\pi} n^2.$$

Proof. It is easy to show (see [2], Theorem 4) that for a circular cluster in the hexagonal lattice centered at a lattice point we have

$$U = \frac{\sqrt{3}}{4\pi} n^2 (1 + o(1)), \quad (13)$$

which is therefore an upper bound on $U(n)$. On the other hand (12) implies

$$U(n) \geq \frac{\sqrt{3}}{4\pi} n^2 (1 + o(1)),$$

which completes the proof. □

References

1. C. H. Bennett, Serially deposited amorphous aggregates of hard spheres, *J. Appl. Phys.* **43** (1972), 2727–2734.
2. A. R. Calderbank and N. J. A. Sloane, New trellis codes based on lattices and cosets, *IEEE Trans. Inform. Theory* **33** (1987), 177–195.
3. C. N. Campopiano and B. G. Glazer, A coherent digital amplitude and phase modulation scheme, *IEEE Trans. Comm.* **10** (1962), 90–95.
4. J. H. Conway and N. J. A. Sloane, A fast encoding method for lattice codes and quantizers, *IEEE Trans. Inform. Theory* **29** (1983), 820–824.
5. G. Fejes Tóth, P. Gritzmann, and J. M. Wills, Finite sphere packing and sphere covering, *Discrete Comput. Geom.* **4** (1989), 19–40.
6. J. H. Folkman and R. L. Graham, A packing inequality for compact convex subsets of the plane, *Canad. Math. Bull.* **12** (1969), 745–752.
7. G. J. Foschini, R. D. Gitlin, and S. B. Weinstein, Optimization of two-dimensional signal constellations in the presence of Gaussian noise, *IEEE Trans. Comm.* **22** (1974), 28–38.
8. H. Groemer, Über die Einlagerung von Kreisen in einen konvexen Bereich, *Math. Z.* **73** (1960), 285–294.
9. M. R. Hoare, Structure and dynamics of simple microclusters, *Adv. Chem. Phys.* **40** (1979), 49–135.
10. M. R. Hoare and J. A. McInnes, Morphology and statistical statics of simple microclusters, *Adv. in Phys.* **32** (1983), 791–821.
11. K. Kinoshita and M. Kobayashi, Two-dimensionally arrayed optical-fibre splicing with a CO₂ laser, *Appl. Optics* **21** (1982), 3419–3422.
12. D. McCullough, *The Great Bridge*, Simon and Schuster, New York, 1972.
13. N. Oler, An inequality in the geometry of numbers, *Acta Math.* **105** (1961), 19–48.
14. N. J. A. Sloane and B. K. Teo, Theta series and magic numbers for close-packed spherical clusters, *J. Chem. Phys.* **83** (1985), 6520–6534.
15. Wegner, Über endliche Kreispackungen in der Ebene, *Studia Sci. Math. Hungar.*, to appear.

Received December 1, 1986.