Fig. 8—Theoretical and experimental creep curves for thick-walled cylinders, $b/a = 2.0$, $\beta = 0.5$

Fig. 9—Theoretical and experimental creep curves for thick-walled cylinders, $b/a = 1.5$, $\beta = 0.5$

accurately approximated by eq (3). The material constants σ_0 and ϵ_0 [see eq (3)] at any specified time were used in predicting the axial strain and the circumferential strains at both the inner and outer radii of each thick-walled cylinder at the specified time. Good agreement was found between theory and experiment. The results of the investigation

indicated that the redistribution of stress with time in the cylinders did not influence the deformations and indicated that the material constants σ_0 and ϵ_0 , for any time after a change in load history, accurately predicted the effect of the same load history on the thick-walled cylinders.

Acknowledgments

This investigation was conducted as part of the work of the Engineering Experiment Station of the University of Illinois, of which Ross J. Martin is the director, in the Department of Theoretical and Applied Mechanics, of which T. J. Dolan is the head. The high-density polyethylene was donated by the polychemical department of E. I. DuPont Company.

Bibliography

1. Lubahn, J. D., and Felgar, R. P., "Plasticity and Creep of Metals," Wiley (1961).
2. Bauld, N. R., Jr., and Sidebottom, O. M., "Experimental and Theoretical Evaluation of Several Creep Theories for Creep Torsion of Circular Bars," 2nd Southeastern Conf. Theo. and Appl. Mech. (1964).
3. Bailey, R. W., "Utilization of Creep Test Data in Engineering Design," Proceedings of the Institute of Mechanical Engineers, **131**, 131 (1935).
4. Finnie, I., and Heller, W. R., "Creep of Engineering Materials," McGraw-Hill (1959).
5. Rimrott, F. P. J., Mills, E. J., and Martin, J., "Prediction of Creep Failure Time for Pressure Vessels," ASME paper No. 60-APM-7.
6. Rimrott, F. P. J., "Creep of Thick-Walled Tubes Under Internal Pressure Considering Large Strains," Jnl. Appl. Mech., **26**, 271-275 (1959).
7. Finnie, I., "Steady-State Creep of a Thick-Walled Cylinder Under Combined Axial Load and Internal Pressure," ASME Paper No. 59-A-47.
8. Weir, C. D., "The Creep of Thick Tubes Under Internal Pressure," ASME paper No. 57-APM-32.
9. Coffin, L. F., Jr., Shepler, P. D., and Cherniak, G. S., "Primary Creep in the Design of Internal Pressure Vessels," Jnl. Appl. Mech., **71**, 9-241 (1949).
10. Sidebottom, O. M., Costello, G. A., and Dharmarajan, S., "Theoretical and Experimental Analyses of Members Made of Materials that Creep," Engrg. Expt. Sta., Univ. of Illinois, Bln. 460 (1961).
11. Costello, G. A., Sidebottom, O. M., and Pocs, E., "Inelastic Design of Load Carrying Members—Part II The Effect of End Conditions on the Collapse Load of Columns," TAM Rept. No. 178, Univ. of Illinois of WADD Tech. Rept. 60-580 (1960).
12. Sidebottom, O. M., and Dewhurst, D. L., "Theoretical and Experimental Creep Analyses of Beam-Columns," ASME paper No. 62-WA-229 (1962).
13. Patnaik, N., and Sidebottom, O. M., "Creep of Circular-Section Torsion-Tension Members Subjected to Nonproportionate Load Changes," Univ. of Illinois Engrg. Expt. Sta. Tech. Rpt. No. 6 (1963).
14. Dharmarajan, S., and Sidebottom, O. M., "Arc Hyperbolic Sine Creep Theory Applied to Torsion-tension Member of Circular Cross-Section," EXPERIMENTAL MECHANICS, **3** (7), 153-160 (1963).
15. Gubser, J. L., Sidebottom, O. M., and Shammamy, M. R., "Creep Torsion of Prismatic Bars," Proc. Joint Intl. Conf. on Creep, 2-99-2-108 (1963).
16. Shanley, R. F., "Weight-Strength Analysis of Aircraft Structures," McGraw-Hill, Ch. 19 (1952).

ERRATA:

Photothermoelastic Investigation of Stresses Around a Hole in a Plate Subjected to Thermal Shock

by G. A. Gurtman and A. A. Colao

We regret that an error appeared in Fig. 8 on page 100 of the April issue of *E/M*. The sequential order of the photographs in parts (b), (c), (d) and (e) is incorrect. The photograph in part (b) should appear in position (d); the one in part

(d) should appear in position (e); the one in part (e) should appear in position (c); and the one in part (c) should appear in position (b).

The sequential order of all titles is correct as is.

The Editors