In these equations v_1 and v_2 are the average velocities of particles of components 1 and 2 in an arbitrary co-ordinate system, N_1 and N_2 are the mol fractions of 1 and 2, and V_m is the molar volume.

Values of diffusion coefficients calculated by two methods are compared in Table III. While the two methods yield almost the same value for D , Wagner's method is preferable since it allows for shifts due to changes in the specific volumes of the phases, as well as displacement of the specimen surfaces.

The author wish to acknowledge the support of the

N.A.S.A. Lewis Research Laboratory under Grant NGR 33-015-160.

1. J. W. Colby: *Magic-Microprobe Analysis General Intensity Correction Program*, Version 3, Bell Laboratories, Allentown, Pennsylvania, 1969.
2. Th. Heumann: *Z. Phys. Chem.*, 1952, vol. 201, pp 168-89.
3. V. T. Borisov, V. M. Goltkov, and G. N. Dubinin: *Diffusion Cladding of Metals*, G. V. Samsonov, ed., pp. 17-23, translated from Russian by Consultants Bureau, New York, 1967.
4. C. Wagner: *Acta Met.*, 1969, vol. 17, pp. 99-107.
5. R. W. Balluffi and L. L. Seigle: *J. Appl. Phys.*, 1954, vol. 25, pp. 607-14.
6. M. M. P. Janssen, Koninklijke/Shell - Lab., Amsterdam, (Shell Research N. V.), Netherlands, private communication.

Corrections to *Met. Trans.*, 1972, vol. 3

Stability and Mechanical Properties of Some Metastable Austenitic Steels, by D. Bhandarkar, V. F. Zackay, and E. R. Parker, p. 2619.

Page 2619

An error of omission occurred in the first paragraph. Beginning with line 6, the second and third sentences should read as follows:

"The nature of these transformations and their influences on mechanical properties have been the subjects of active research for many years. It has been clearly established that both diffusion controlled reactions and martensitic transformations can occur..."