Temperature Dependence of Ultrasonic Absorption in Mixtures of Glycerol and Water.

G. S. DARBARI, R. P. SINGH and G. S. VERMA

Physics Department, Allahabad University - Allahabad

(*Nuovo Cimento*, **41** B, 15 (1965))

$(\text{CH}_2\text{OH} \cdot \text{CHOH} \cdot \text{CH}_2\text{OH})_4 \cdot \text{H}_2\text{O}$ should be $(\text{CH}_2\text{OH} \cdot \text{CHOH} \cdot \text{CH}_2\text{OH}) \cdot \text{H}_2\text{O}$.

Radiation-Induced Noise in Semiconductor Counters.

A. BERTIN, P. GONDI and G. SCANDOLA

Istituto di Fisica dell'Università - Bologna

(*Nuovo Cimento*, **41** B, 198 (1965))

The following misprints of this paper should be corrected.

The caption of Fig. 1 was incorrect. Hereunder is published the figure with the correct caption.

Fig. 1. - Scheme of the circuits used for the noise measurements: a), b) and c) are respectively the detector circuit, the detector-equivalent RC circuit and the test circuit, to be opportunely connected to the terminals as indicated by the numbers.

$$\begin{aligned} R_i &= 2 \cdot 10^7 \, \Omega, & C_d &= 1.5 \cdot 10^{-10} \, \text{F}, \\ R_d &= 5 \cdot 10^8 \, \Omega, & C_i &= 1.4 \cdot 10^{-8} \, \text{F}. \end{aligned}$$

In Table II of p. 203 read: reproduction errors of 30% ..., instead of: reproducibility of errors of 30%

In the caption of Fig. 5 read $\overline{m_p^2}/\overline{m_r}$ values instead of $\overline{m_p^2}/\overline{m_r^2}$ values.