REFERENCES

- 1) Wait, J. R., J. Appl. Phys. **26** (1955) 458.
- 2) Wong, J. Y., Proc. Instn Radio Engrs **4b** (1953) 1172.
- 3) Morse, P. M. and H. Feshbach, Methods of Theoretical Physics, Part II, McGraw Hill Book Co., New York 1953, p. 1571.
- 4) Wait, J. R. and S. H. Kahana, Can. J. Tech. **33** (1955) 211.
- 5) Wait, J. R., Wireless Engr **32** (1955) 316; also Nat. Bur. Stand. J. Res. **59** (1957) 255.
- 6) Fock, V. A., J. Phys. USSR **10** (1946) 130 and 399.
- 7) Wait, J. R., Electromagnetic Radiation from Cylindrical Structures Pergamon Press, London, 1959.

Also see the articles by J. Y. Wong, Trans. Instn Radio Engrs AP-3 (1955) 200 (for patterns of single and multiple axial slots on elliptic cylinders of vanishing minor axis, i.e. strips) and George Sinclair, Proc. Instn Radio Engrs **39** (1951) 660 (shows an E -plane pattern for a small axial loop at the end of the major axis for the case $kb = 4$ and $b/a = 1.63$ which is very similar to our fig. 3c for $kb = 4$ and $b/a = 2$).

ERRATUM

Appl. sci. Res. B7 (1959) 361.

EQUIVALENT BASE RESISTANCE
OF POINT-CONTACT TRANSISTORS

by FREDERICK J. YOUNG

Eq. (3) should read

$$\frac{\partial v}{\partial x} (\pm x_0, y, -z_0 < z < z_0) = \frac{\partial v}{\partial y} (x, \pm y, -z_0 < z < 0) = 0.$$