Erratum to: Component and system reliability-based topology optimization using a single-loop method

Mariana Silva · Daniel A. Tortorelli · Julian A. Norato ·
 Christopher Ha · Ha-Rok Bae

Published online: 25 February 2010
 © Springer-Verlag 2010

Erratum to: Struct Multidisc Optim DOI 10.1007/s00158-009-0401-5

The original version of this article unfortunately contained mistake. The presentation of Figs. 4, 8, 12, 17, 18 and 19 were incorrect. The corrected figures are given below.

Fig. 4 Topology optimization of an automotive control arm

The online version of the original article can be found at
<http://dx.doi.org/10.1007/s00158-009-0401-5>.

M. Silva (✉) · D. A. Tortorelli
 Department of Mechanical Science and Engineering,
 University of Illinois at Urbana-Champaign,
 1206 West Green St., Urbana, IL 61801, USA
 e-mail: mfsilva@uiuc.edu

J. A. Norato · C. Ha · H.-R. Bae
 Champaign Simulation Center, Caterpillar Inc.,
 1901 S. First St., Champaign, IL 61820, USA

Fig. 8 The 2D topology optimization of a knee

Fig. 12 Topology optimization of a knee

(a) CRBTO

(b) SRBTO

Fig. 17 Constraint convergence for the knee problem (a, b)

(a) CRBTO

(b) SRBTO

Fig. 19 γ convergence for the knee problem (a, b)

(a) CRBTO

(b) SRBTO

Fig. 18 Load realization convergence for the knee problem (a, b)