Development and characterization of an integrated silicon micro flow cytometer

R. Bernini · E. De Nuccio · F. Brescia · A. Minardo ·
L. Zeni · P. M. Sarro · R. Palumbo · M. R. Scarfi

Published online: 4 November 2006
© Springer-Verlag 2006

Regrettably, the legends of Figs. 4 and 5 were mistakenly interchanged. The corrected figures with the corresponding legends are given below.

Fig. 4 Schematic representation of the experimental setup used for characterization of the integrated micro flow cytometer

The online version of the original article can be found at <http://dx.doi.org/10.1007/s00216-006-0623-y>.

R. Bernini (✉) · F. Brescia · M. R. Scarfi
IREA-CNR,
Via Diocleziano 328,
80124 Napoli, Italy
e-mail: bernini.r@irea.cnr.it

E. De Nuccio · A. Minardo · L. Zeni
DII, Seconda Università di Napoli,
Via Roma 29,
81031 Aversa, Italy

P. M. Sarro
ECTM-DIMES, TUDelft,
Feldmannweg 17,
2600 GB Delft, The Netherlands

R. Palumbo
IBB-CNR,
Via Mezzocannone 16,
80134 Napoli, Italy

Fig. 5 The hydrodynamic focusing effect in the micro flow cytometer. The width of the focused stream is approximately 24 μm