Performance of smooth and micro-fin tubes in high mass flux region of R-134a during evaporation

Jittraporn Wongsangam, Thipjak Nualboonrueng, Somchai Wongwises

437

1

Heat and Mass Transfer (2002)

DOI 10.1007/s00231-002-0397-5

Unfortunately there were two errors in Conclusion section.

In topic 3 the sentence should read:

3. The average heat transfer coefficient and average pressure drop for the 9.52 mm OD micro-fin tube are 50%

to 100% and 10% to 60% greater than for the smooth tube, respectively.

The subtopic 3 in topic 4, the sentence should read:

3) The two-phase friction multiplier ϕ_l^2 for the smooth tube;

Published online: 5 May 2004

© Springer-Verlag 2004

Without Abstract

The online version of the original article can be found at <http://dx.doi.org/10.1007/s00231-002-0397-5>

J. Wongsangam
Energy Division, The Joint Graduate School of Energy
and Environment, King Mongkut's University of Technology
Thonburi, Bangmod, Bangkok 10140, Thailand

T. Nualboonrueng, S. Wongwises (✉)
Fluid Mechanics, Thermal Engineering and Multiphase Flow Research
Laboratory (FUTURE), Department of Mechanical Engineering,
King Mongkut's University of Technology Thonburi, Bangmod,
Bangkok 10140, Thailand
E-mail: somchai.won@kmutt.ac.th
Tel.: +662-470-9115
Fax: +662-470-9111