Effects of carbon fiber surface treatment on the tribological properties of 2D woven carbon fabric/polyimide composites

Xinrui Zhang · Xianqiang Pei · Qian Jia · Qihua Wang

Published online: 5 May 2009
© Springer-Verlag 2009

Erratum to: Appl Phys A (2009) 95: 793–799
DOI 10.1007/s00339-009-5073-x

Equation (2) in our article is incorrect. It should read as follows:

$$\omega = \frac{B}{L \cdot P} \left[\frac{\pi r^2}{180} \arcsin\left(\frac{b}{2r}\right) - \frac{b}{2r} \sqrt{r^2 - \frac{b^2}{2}} \right] \left(\frac{\text{mm}^3}{\text{Nm}} \right).$$

The online version of the original article can be found under
doi:[10.1007/s00339-009-5073-x](https://doi.org/10.1007/s00339-009-5073-x).

X. Zhang · X. Pei · Q. Jia · Q. Wang (✉)
State Key Laboratory of Solid Lubrication, Lanzhou Institute
of Chemical Physics, Chinese Academy of Sciences,
Lanzhou 730000, China
e-mail: wangqh@lzb.ac.cn
Fax: +86-931-8277088

X. Zhang
Graduate School, Chinese Academy of Sciences, Beijing 100039,
China