Erratum to: Direct laser printing of thin-film polyaniline devices

M. Kandyla · C. Pandis · S. Chatzandroulis · P. Pissis ·
I. Zergioti

Published online: 6 October 2012
© Springer-Verlag Berlin Heidelberg 2012

Erratum to: Appl Phys A DOI 10.1007/s00339-012-7127-8

Due to a processing error, the presentation of Fig. 4 was incorrect.

The corrected Fig. 4 is given below.

The online version of the original article can be found under doi: [10.1007/s00339-012-7127-8](https://doi.org/10.1007/s00339-012-7127-8).

M. Kandyla · C. Pandis · P. Pissis · I. Zergioti (✉)
Physics Department, National Technical University of Athens,
9 Iroon Polytechniou Street, Zografou, Athens 15780, Greece
e-mail: zergioti@central.ntua.gr
Fax: +30-210-7723338

M. Kandyla
e-mail: kandyla@central.ntua.gr
Fax: +30-210-7723025

C. Pandis
e-mail: pandis@central.ntua.gr
Fax: +30-210-7722932

P. Pissis
e-mail: ppissis@central.ntua.gr
Fax: +30-210-7722932

S. Chatzandroulis
Institute of Microelectronics, NCSR Demokritos,
Agia Paraksevi, Athens 15310, Greece
e-mail: stavros@imel.demokritos.gr
Fax: +30-210-6511723

Fig. 4 Current–voltage (I – V) characteristics of polyaniline films laser-deposited between Au electrodes on a Si/SiO₂ substrate, on (a) a linear and (b) a logarithmic scale