Erratum to: High-volume-fraction Cu/Al₂O₃–SiC hybrid interpenetrating phase composite

Hesam Saidi¹ · Ghodratollah Roudini¹ · Mahdi Shafiee Afarani¹

Published online: 7 October 2015
© Springer-Verlag Berlin Heidelberg 2015

Erratum to: Appl. Phys. A (2015) 121:109–113
DOI 10.1007/s00339-015-9392-9

The original version of this article unfortunately contained mistakes.

The second paragraph in 3.2 Composites, beginning “The effect of...”, should not have been included in this article and should be disregarded. The presentation of Figs. 3, 4, 5, 6, 7 and 8 and legends were interchanged. The correct figures and legends are given below.

Fig. 3 The SEM micrographs of sintered preform without SiC

The online version of the original article can be found under doi:[10.1007/s00339-015-9392-9](https://doi.org/10.1007/s00339-015-9392-9).

✉ Ghodratollah Roudini
ghodratollah.roudini@eng.usb.ac.ir

¹ Department of Materials Engineering, Faculty of Engineering, University of Sistan and Baluchestan, Zahedan, Iran

Fig. 4 The SEM micrographs of sintered preform with 50 wt% SiC

Fig. 6 Effect of SiC concentration on density preforms

Fig. 5 Effect of SiC concentration on porosity values of the preforms

Fig. 7 Effect of SiC concentration on flexural strength of preforms

Fig. 8 XRD patterns of the sintered preform with different SiC concentrations