ERRATUM

Erratum to: Electromagnetic shielding effectiveness and mechanical properties of graphite-based polymeric films

G. Kenanakis¹ · K. C. Vasilopoulos¹ · Z. Viskadourakis² · N.-M. Barkoula³ · S. H. Anastasiadis^{1,4} · M. Kafesaki^{1,5} · E. N. Economou¹ · C. M. Soukoulis^{1,6}

Published online: 30 August 2016
© Springer-Verlag Berlin Heidelberg 2016

Erratum to: Appl Phys A (2016) 122:802 DOI 10.1007/s00339-016-0338-7

The original version of this article unfortunately contained a mistake. The presentation of Figs. 1 and 2 was incorrect. The correct Figs. 1 and 2 are given here.

The original article was corrected.

Fig. 1 Experimental setup used for the impedance measurements of the graphite/PS composites

Fig. 2 TGA curves of the graphite/PS composites from RT to 600 °C at a rate of 20 °C/min, under air flow. In the inset of Fig. 1, one can see the theoretical and experimental % w/w concentration of graphite in the polymeric films

The online version of the original article can be found under doi:10.1007/s00339-016-0338-7.

✉ G. Kenanakis
gkenanak@iesl.forth.gr

- ¹ Institute of Electronic Structure and Laser, Foundation for Research & Technology-Hellas, N. Plastira 100, 70013 Heraklion, Crete, Greece
- ² Crete Center for Quantum Complexity and Nanotechnology, University of Crete, 71003 Heraklion, Greece
- ³ Department of Materials Engineering, University of Ioannina, 45110 Ioannina, Greece
- ⁴ Department of Chemistry, University of Crete, 71003 Heraklion, Crete, Greece
- ⁵ Department of Materials Science and Technology, University of Crete, 71003 Heraklion, Crete, Greece
- ⁶ Ames Laboratory, U.S. Department of Energy and Department of Physics and Astronomy, Iowa State University, Ames, IA 50011, USA