ERRATUM

Fabrication and modulation characteristics of InGaAsP/InGaAsP MQW DCPBH lasers at $\lambda \sim 1.57 \mu\text{m}$

S.W. Park · S.S. Park · J.S. Yu

Published online: 23 July 2008
© Springer-Verlag 2008

Erratum to: Appl Phys B (2008) 90: 55–59
DOI 10.1007/s00340-007-2850-0

does not give a perfectly straight flat line over the whole range.

On p. 57, first column, 19th line and 39th line, the sentences contain typographical errors: “34 mW/mA” and “24 mW/mA” should be changed to “0.34 mW/mA,” and “0.24 mW/mA,” respectively. We also note that the slope efficiencies are obtained on average because the L–I curve

The online version of the original article can be found under doi: [10.1007/s00340-007-2850-0](https://doi.org/10.1007/s00340-007-2850-0).

S.W. Park
Network Examination Team, Korean Intellectual Property Office,
Daejeon 302-701, Korea

S.W. Park
Neoptek Ltd., Anyang 431-080, Korea

S.S. Park
National Research Laboratory of Nonlinear Optics, Yonsei
University, Seoul 120-749, Korea

J.S. Yu (✉)
Department of Electronic Engineering, Kyung Hee University,
Yongin 446-701, Korea
e-mail: jsyu@khu.ac.kr