M. Raffel · H. Richard · K. Ehrenfried
B. Van der Wall · C. Burley · P. Beaumier
K. McAlister · K. Pengel

Recording and evaluation methods of PIV investigations on a helicopter rotor model

Published online: 1 March 2006
© Springer-Verlag 2006

Experiments in Fluids (2004) 36(1):146–156

In the original publication of this article, there are typographical errors in the first equation on page 154. We apologize for this mistake. The correct equation is:

$$e_{u,rel} \leq W_{max}/U_{max} \times 3/(\Delta Z \times M) \times ex,$$

Accordingly the following sentences should read “Therefore, the measurement error can be reduced by minimizing any one of three terms: W_{max}/U_{max} , $3/(\Delta Z \times M)$, and ex .”

The online version of the original article can be found at <http://dx.doi.org/10.1007/s00348-003-0689-7>

M. Raffel (✉) · H. Richard · K. Ehrenfried
Institut für Aerodynamik und Strömungstechnik, DLR, Göttingen,
Germany
E-mail: markus.raffel@dlr.de

B. Van der Wall
Institut für Flugsystemtechnik, DLR, Braunschweig, Germany

C. Burley
NASA Langley Research Center, Langley, VA, USA

P. Beaumier
ONERA, Chatillon, France

K. McAlister
US Army AFDD, NASA Ames Research Center, Moffett Field,
CA, USA

K. Pengel
Large Low Speed Facility LLF, DNW, Nordostpolder,
The Netherlands