Editorial

D. Palmer-Brown

Published online: 2 August 2011
© Springer-Verlag London Limited 2011

EANN 2009 provided a rich set of papers to choose from for this special issue. A characteristic of the EANN conferences is the diversity of applications and methods and 2009 was no exception. Combining several well-known methods in one application is also common.

In “Credit Rating Modelling by Kernel-based Approaches with Supervised and Semi-supervised Learning”, Petr Hajek and Vladimir Olej deploy Support Vector Machines with supervised learning as well as kernel-based approaches with semi-supervised learning, in order to classify objects into rating classes. The results show that the rating classes assigned to bond issuers can be classified with high classification accuracy using a limited subset of input variables. This holds true for kernel-based approaches with both supervised and semi-supervised learning. Financial data also features in “Neural Network Methods for One-To-Many Multi-Valued Mapping Problems”, in which the authors investigate the neural network-based methods for predicting the values of multiple parameters, when given only the value of a single parameter within the problem domain. They show which methods appear to be most suited to one-to-many mapping problems (MLPs and RBF networks). In another financial application “Modeling and Forecasting Cumulative Average Temperature and Heating Degree Day Indices for Weather Derivative Pricing”, A. Zapanis and A. Alexandridis show that wavelet neural networks are effective for modeling a temperature process with seasonal variations. They forecast up to 2 months ahead, out of sample, daily temperatures. The proposed model is validated in 8 European and 5 USA cities, and the

results suggest that the proposed method outperforms alternative pricing methods.

Support Vector Machines remain popular, appearing in two more papers. One of the most unusual and intriguing applications is “Relating Halftone Dot Quality to Paper Surface Topography”, in which Pekka Kumpulainen et al. examine the statistical dependence between the defects in printed dots and the topography measurement of the unprinted paper by using a self-organizing map and clustering. Features from the unprinted paper surface topography are then used to classify the corresponding paper areas using Support Vector Machine classification. Perhaps, the most fascinating application of Support Vector Machines appears in the paper on recognizing and differentiating between facial expressions. An unusual aspect of the approach is the use of Curvilinear component analysis to reduce dimensionality. Perhaps surprisingly only 5 components are necessary in some cases to successfully classify expressions with a Support Vector Machine.

Clustering and self-organization are the key themes from the conference. Nadia Mammone et al. cluster entropy topography in epileptic Electroencephalography and attempt to predict these phenomena minutes before the seizure itself occurs, by introducing a technique, based on entropy topography, that studies the synchronization of the electric activity of neuronal sources in the brain. Entropy showed a steady spatial distribution linked to the brain zone where seizures originated. A self-organizing map-based spatial clustering of entropy topography showed that the critical electrodes shared the same cluster long time before the seizure onset, whereas the healthy subjects exhibited a more random pattern. Another novel clustering approach is covered “New Aspects of the Elastic Net Algorithm for Cluster Analysis” by Marcos Lévano and Hans Nowak. The elastic net algorithm can be used as a

D. Palmer-Brown (✉)
London, UK
e-mail: d.palmer-brown@londonmet.ac.uk

tool for data clustering in n -dimensional space. A stopping criterion is applied for the annealing process, and the method is found to be effective in a medical application to localize tumors and their size in images of X-ray tomography and positron emission tomography. In the most safety critical application “Tracking of the Plasma States in a Nuclear Fusion Device using SOMs”, M. Camplani et al. examine two clustering techniques, K-means and self-organizing maps, for the identification of characteristic regions for plasma scenarios in nuclear fusion experimental devices. The choice of the number of clusters that heavily affects the performance of the mapping is optimized. Then, the current process state and its history in time are visualized as a trajectory on the self-organizing map, in order to attempt a prediction of the safe or disruptive state of the plasma.

Few papers tackle hardware issues. An exception is “Soft-computing Methods for Robust Authentication Using Soft-biometric Data”, in which Mario Malcangi presents a multi-biometric platform that combines voice-print and fingerprint authentication as a reference model to demonstrate the potential of soft-computing methods on soft-biometric data. The embedded implementation is shown to be effective, based on a single-chip, floating-point, digital signal processor (DSP). Another hardware-oriented project is described in “Application of Neural Fuzzy Controller for Streaming Video over Bluetooth 1.2” by Guillaume F. Remy et al. Noise and interference create difficulties in achieving an accurate real-time transmission rate at the receiving end, so a new buffer is introduced at the input of the Bluetooth 1.2 device. The buffer is controlled by a Rule-Based Fuzzy (RBF) logic controller at the input and a Neural Fuzzy Controller (NFC) at the output. Two fuzzy rules manipulate and supervise the flow of

video over the Bluetooth 1.2 standard. The simulation results show improvement in image quality, reduced data loss, and reduced time delay.

In a novel and successful application, “A Neural Network Based Solution for Automatic Typing Errors Correction”, Jun Li et al. synthesize some distinct word correction algorithms to produce an optimal prediction based on database updates and neural networks. Experimental results show that the developed WLR model (i.e., word-list neural network ranking model) achieves the best results in comparison with Levenshtein distance, Metaphone, and Two-Gram prediction algorithms throughout all stages.

Two papers tackle time-series or sequence data for which recurrent networks are suitable. In “Nonmonotone Levenberg–Marquardt Training of Recurrent Neural Architectures for Processing Symbolic Sequences”, the novelty is the adoption of nonmonotone criteria, allowing temporal increase of training errors, and an adaptive scheme for tuning the size of the nonmonotone slide window. The proposed nonmonotone learning algorithms are shown to improve RNNs training. RNNs also appear in “Combining GRN Modeling and Demonstration-Based Programming for Robot Control”, where Wei-Po Lee and Tsung-Hsien Yang exploit RNN abilities to model dynamics and combined them the principles of gene regulation to develop a biologically and computationally plausible model for robot control. To simulate the regulatory effects and to make the model inferable from time-series data, they also implement an enhanced network learning algorithm. The conclusion of the experiments is that the regulatory model can be successfully inferred for robot control.