Erratum to: Fracture-Induced Anisotropic Attenuation

José M. Carcione · Juan E. Santos · Stefano Picotti

Published online: 13 December 2013
© Springer-Verlag Wien 2013

Erratum to: Rock Mech Rock Eng (2012) 45:929–942
DOI: 10.1007/s00603-012-0237-y

Equation (49): l_1 and l_3 have to be replaced by s_1 and s_3 , where s is the complex slowness or the reciprocal of the complex velocity.

Equation (49) should be

$$W = p_{55}(\xi s_1 + \gamma s_3),$$

$$X = \gamma p_{11}s_1 + \xi p_{13}s_3,$$

$$Z = \gamma p_{13}s_1 + \xi p_{33}s_3$$

The online version of the original article can be found under doi:[10.1007/s00603-012-0237-y](https://doi.org/10.1007/s00603-012-0237-y).

J. M. Carcione (✉) · S. Picotti
Istituto Nazionale di Oceanografia e di Geofisica Sperimentale (OGS), Borgo Grotta Gigante 42c, 34010 Sgonico, Trieste, Italy
e-mail: jcarcione@inogs.it

J. E. Santos
CONICET, Instituto del Gas y del Petróleo, Facultad de Ingeniería, Universidad de Buenos Aires, C1127AAR Buenos Aires, Argentina
e-mail: santos@math.purdue.edu

J. E. Santos
Universidad Nacional de La Plata, La Plata, Argentina

J. E. Santos
Department of Mathematics, Purdue University, W. Lafayette, IN 47907-2067, USA