Erratum to: Experimental Investigation of Seepage Properties of Fractured Rocks Under Different Confining Pressures

D. Ma · X. X. Miao · Z. Q. Chen · X. B. Mao

Published online: 1 January 2015
© Springer-Verlag Wien 2014

Erratum to: Rock Mech Rock Eng (2013) 46:1135–1144
DOI 10.1007/s00603-012-0329-8

The spelling of Eqs. (9) and (10) was incorrect and some financial supports were omitted in the original publication of the article.

The corrected spelling of the Eqs. (9) and (10) should be

$$k = \frac{\mu \left[\left(\sum_{i=1}^n v_i^3 \right)^2 - \sum_{i=1}^n v_i^2 \sum_{i=1}^n v_i^4 \right]}{\sum_{i=1}^n p_i v_i^2 \sum_{i=1}^n v_i^3 - \sum_{i=1}^n p_i v_i \sum_{i=1}^n v_i^4} \quad (9)$$

$$\beta = \frac{\sum_{i=1}^n p_i v_i \sum_{i=1}^n v_i^3 - \sum_{i=1}^n p_i v_i^2 \sum_{i=1}^n v_i^2}{\rho \left[\left(\sum_{i=1}^n v_i^3 \right)^2 - \sum_{i=1}^n v_i^2 \sum_{i=1}^n v_i^4 \right]} \quad (10)$$

In the Acknowledgments, the last financial supports were omitted:

The National Basic Research Program of China (2013CB227900) and the National Natural Science Foundation of China (U1261201 and 51421003).

The online version of the original article can be found under doi:[10.1007/s00603-012-0329-8](https://doi.org/10.1007/s00603-012-0329-8).

D. Ma · X. X. Miao · Z. Q. Chen (✉) · X. B. Mao
State Key Laboratory for Geomechanics and Deep Underground Engineering, School of Mechanics and Civil Engineering,
China University of Mining and Technology,
Xuzhou 221008, Jiangsu, China
e-mail: madancumt@gmail.com