Correction to: A new and simple method for measuring in situ field-saturated hydraulic conductivity using a falling-head single cylinder

Kosuke Noborio¹ · Yuki Ito² · Hailong He³ · Min Li⁴ · Yuki Kojima⁵ · Hirofumi Hara⁶ · Masaru Mizoguchi⁷

Published online: 13 February 2018

© The International Society of Paddy and Water Environment Engineering and Springer Japan KK, part of Springer Nature 2018

Correction to: Paddy Water Environ

<https://doi.org/10.1007/s10333-017-0617-8>

In the original publication of this article, the equation 12 had a typographical error and has been incorrectly published online. Now the correct equation has been provided in this erratum.

$$\frac{di}{dH} = \left| \frac{1}{t + \frac{\beta}{2\alpha}} \right|. \quad (12)$$

The original article can be found online at <https://doi.org/10.1007/s10333-017-0617-8>.

✉ Kosuke Noborio
noboriok@meiji.ac.jp

¹ School of Agriculture, Meiji University, 1-1-1 Higashimita, Tama-ku, Kawasaki, Kanagawa 214-8571, Japan

² Graduate School of Agriculture, Meiji University, 1-1-1 Higashimita, Tama-ku, Kawasaki, Kanagawa 214-8571, Japan

³ College of Natural Resources and Environment, Northwest A&F University, Taicheng Rd. 3, Yangling 712100, Shaanxi Province, China

⁴ Key Laboratory of Agricultural Soil and Water Engineering in Arid and Semiarid Areas, Ministry of Education, Northwest A&F University, Yangling 712100, Shaanxi Province, China

⁵ Faculty of Engineering, Gifu University, 1-1 Yanagodo, Gifu City, Gifu 501-1193, Japan

⁶ Department of Environmental Engineering and Green Technology, Malaysia-Japan International Institute of Technology (MJIIT), Universiti Teknologi Malaysia (UTM), Jalan Sultan Yahya Petra, 54100 Kuala Lumpur, Malaysia

⁷ Graduate School of Agriculture and Life Sciences, The University of Tokyo, 1-1-1 Yayoi, Bunkyo-ku, Tokyo 113-8657, Japan