Active Acquisition of Information for Diagnosis and Supervisory Control of Discrete Event Systems

David Thorsley · Demosthenis Teneketzis

Published online: 16 October 2007
© Springer Science + Business Media, LLC 2007

Erratum to: Discrete Event Dyn Syst DOI 10.1007/s10626-007-0027-y

In (Thorsley and Teneketzis 2007), Definition 1 is incomplete. The revised definition below states the additional necessary condition missing from Thorsley and Teneketzis (2007).

Definition 1 An observation policy $g := (g_0, \dots, g_{T-1})$ is a sequence of functions $g_t : L_T \rightarrow 2^{\Sigma_{co}}$ such that for all $t, t = 0, \dots, T-1$, g_t is measurable with respect to the σ -field $\mathcal{G}_t^g$, defined below (in Definition 3).

Note that for all $s' \in L_t$ and $s, \hat{s} \in \chi_t(s')$, $g_t(s) = g_t(\hat{s})$. The statement “The functions χ_t are used in the following definition,” found above Definition 1 in the text, should be ignored when reading the paper.

Definition 3 is unchanged, but we restate it here for convenience.

The online version of the original article can be found at
<http://dx.doi.org/10.1007/s10626-007-0027-y>

D. Thorsley (✉)
Department of Electrical Engineering, University of Washington, Seattle, WA 98195, USA
e-mail: thorsley@ee.washington.edu

D. Teneketzis
Department of EECS, University of Michigan, Ann Arbor, MI 48109, USA
e-mail: teneketzis@eecs.umich.edu

Definition 3 The filtration $\{\mathcal{G}_t^g, t = 0 \dots T\}$ corresponding to g is

$$\sigma(\pi_t : \pi_t \in R_t^g), t = 0 \dots T. \quad (11)$$

Note that $\mathcal{G}_t^g, t = 0 \dots T - 1$, depends on $g_0, g_1, \dots, g_{t-1}$.

References

- Thorsley D, Teneketzis D (2007) Active acquisition of information for diagnosis and supervisory control of discrete event systems. *Discrete Event Dyn Syst: Theory and Applications* 17(4): 531–583