## **ERRATUM**



## Erratum to: An extreme learning machine model for the simulation of monthly mean streamflow water level in eastern Queensland

Ravinesh C. Deo · Mehmet Şahin

Published online: 7 March 2016

© Springer International Publishing Switzerland 2016

Erratum to: Environ Monit Assess DOI 10.1007/s10661-016-5094-9

The accepted version of Table 6 for this published online article contained an error.

The corrected Table 6 is shown in the next page.

The online version of the original article can be found at http://dx.  $\frac{doi.org}{10.1007/s}10661-016-5094-9$ .

R. C. Deo (⊠)

School of Agricultural Computational and Environmental Sciences, International Centre of Applied Climate Science (ICACS), University of Southern Queensland, Springfield, QLD 4300, Australia

e-mail: ravinesh.deo@usq.edu.au

M. Şahin
 Department of Electrical and Electronics Engineering, Siirt
 University, 56100 Siirt, Turkey



**Table 6** The model performance based on coefficient of determination ( $R^2$ ), Willmott's index (d), Nash–Sutcliffe coefficient ( $E_{NS}$ ), peak percentage deviation ( $P_{dv}$ ) and mean absolute error (MAE) in the test period (2006–2012)

Station	ELM					ANN				
	$R^2$	d	$E_{ m NS}$	P <sub>dv</sub> (%)	MAE (m)	$R^2$	d	$E_{ m NS}$	P <sub>dv</sub> (%)	MAE (m)
Optimum Model										
Gowrie Creek	0.964	0.968	0.963	1.993	0.053	0.732	0.802	0.698	18.080	0.144
Albert River	0.957	0.962	0.955	-0.091	0.023	0.830	0.863	0.816	-5.527	0.049
Mary River	0.990	0.986	0.989	0.372	0.079	0.892	0.855	0.891	-0.254	0.249
Trial Model with o	nly rainfall	and mont	h as inputs							
Gowrie Creek	0.781	0.802	0.691	4.918	0.128	0.723	0.773	0.656	18.389	0.149
Albert River	0.685	0.537	0.617	-3.503	0.072	0.571	0.588	-0.312	7.500	0.145
Mary River	0.910	0.870	0.909	0.016	0.227	0.823	0.776	0.800	1.555	0.312
Trial Model all nine	e inputs (n	o prior sele	ection)							
Gowrie Creek	0.732	0.809	0.698	18.080	0.144					
Albert River	0.859	0.876	0.812	2.358	0.049					
Mary River	0.928	0.903	0.926	4.178	0.222					

The optimum model was selected based on input combinations (x) and compared with an equivalent ANN model

