Erratum to: Growing microalgae as aquaculture feeds on twin-layers: a novel solid-state photobioreactor

Thomas Naumann · Zehra Çebi · Björn Podola ·
Michael Melkonian

Published online: 16 March 2013
© Springer Science+Business Media Dordrecht 2013

Erratum to: J Appl Phycol
DOI 10.1007/s10811-012-9962-6

In the sentence “With a surface productivity of $2 \text{ g m}^{-2} \text{ day}^{-1}$ and a flow rate of 6 L^{-1} per meter TL module, approximately 1 kWh is required for pumping to produce 1 kg of algal dry mass” the flow rate should include the time (in hours). The corrected sentence is shown below.

“With a surface productivity of $2 \text{ g m}^{-2} \text{ day}^{-1}$ and a flow rate of $6 \text{ L}^{-1} \text{ h}^{-1}$ per meter TL module, approximately 1 kWh is required for pumping to produce 1 kg of algal dry mass”.

The online version of the original article can be found at <http://dx.doi.org/10.1007/s10811-012-9962-6>.

T. Naumann · Z. Çebi · B. Podola (✉) · M. Melkonian
Botanisches Institut, Lehrstuhl 1, Universität zu Köln, Biozentrum,
Köln, Zùlpicher Str. 47 b,
50674 Köln, Germany
e-mail: bpodola@uni-koeln.de