Erratum to: An enhanced beam-theory model of the mixed-mode bending (MMB) test—Part II: Applications and results

Stefano Bennati · Paolo Fisicaro · Paolo S. Valvo

Published online: 17 January 2013
 © Springer Science+Business Media Dordrecht 2013

Erratum to: Meccanica
DOI 10.1007/s11012-012-9682-7

Due to an unfortunate turn of events this article was published with typos in some formulas appearing in Eqs. (34), (35) and (47). Please find on this page the correct version of such formulas that should be regarded by the reader as the final version.

$$C_{DCB}^{EBT} \cong \frac{2a^3}{3BD_1} + \frac{2a}{BC_1} + \frac{2}{BD_1} \times \frac{1}{\lambda_1\lambda_2} \left[(\lambda_1 + \lambda_2)a^2 + 2a + \frac{1}{\lambda_1} + \frac{1}{\lambda_2} \right], \quad (34)$$

$$C_{ENF}^{EBT} \cong \frac{3a^3 + 8\ell^3}{8BE_x h^3} + \frac{3\ell}{10BG_{zx}h} + \frac{9}{8BE_x h^3} \times \frac{1}{\lambda_5^2} \left[\lambda_5 a^2 + a + 2\ell - \frac{1}{2\lambda_5} - \frac{a}{\exp \lambda_5(\ell - a)} \right]. \quad (35)$$

$$\mu_{II} = \left[\coth \lambda_5 b + \frac{1}{\lambda_5 a} \left(1 - 2 \frac{\sinh \lambda_5 \ell}{\sinh \lambda_5 b} \right) \right]^2. \quad (47)$$

The online version of the original article can be found under doi:10.1007/s11012-012-9682-7.

S. Bennati · P. Fisicaro · P.S. Valvo (✉)
 Dipartimento di Ingegneria Civile e Industriale, Università di Pisa, Largo Lucio Lazzarino, 56126 Pisa, Italy
 e-mail: p.valvo@ing.unipi.it