Erratum to: Asymmetric quantum codes: new codes from old

Giuliano G. La Guardia

Published online: 10 April 2013
© Springer Science+Business Media New York 2013

Erratum to: Quantum Inf Process DOI 10.1007/s11128-013-0562-4

We regret that unfortunately an error was introduced in the original version of this article. There is an error under the Section 4 Construction methods in Theorem 4.2. An inline equation was erroneously included. The correct text for Theorem 4.2 is as follows.

Theorem 4.2 *Let q be a prime power. Assume that there exists an AQECC with parameters $[[n, k, d_z/d_x]]_{q^m}$, derived from linear codes $C_1 = [n, k_1, d_1]_{q^m}$ and $C_2 = [n, k_2, d_2]_{q^m}$, respectively. Then, there exists an AQECC with parameters $[[mn, mk, d_z^*/d_x^*]]_q$, where $k = k_1 - k_2$, $d_z^* \geq d_1$ and $d_x^* \geq d_2^\perp$, where $d_2^\perp$ denotes the minimum distance of the dual code $C_2^\perp$.*

The online version of the original article can be found under doi:[10.1007/s11128-013-0562-4](https://doi.org/10.1007/s11128-013-0562-4).

G. G. La Guardia (✉)
Department of Mathematics and Statistics, State University of Ponta Grossa, Ponta Grossa,
PR 84030-900, Brazil
e-mail: gguardia@uepg.br