Erratum to: Study the Sensitivity of Solid Lubricating Additives to Attapulgite Clay Base Grease

Zeyun Wang · Yanqiu Xia · Zhilu Liu

Published online: 31 March 2011
© Springer Science+Business Media, LLC 2011

Erratum to: Tribol Lett DOI 10.1007/s11249-011-9754-1

The original version of this article unfortunately contained three mistakes. The captions of Figures 6, 7 and 8 were incorrect. The corrected captions are given below.

Fig. 6 Friction coefficient as a function of time with lubrication of the base grease containing MoS₂ or graphite/MoS₂ (800 N and 30 Hz)

Fig. 7 A comparison of the friction coefficient and wear rate as functions of sliding frequency for the attapulgite clay base grease containing 5 wt% MoS₂ and the bentone base grease containing 5 wt% MoS₂

Fig. 8 Friction coefficient as a function of time with lubrication of the base grease containing different additives, respectively (200 N and 40 Hz)

The online version of the original article can be found under doi:[10.1007/s11249-011-9754-1](https://doi.org/10.1007/s11249-011-9754-1).

Z. Wang · Y. Xia (✉) · Z. Liu
State Key Laboratory of Solid Lubrication, Lanzhou Institute of Chemical Physics, Chinese Academy of Sciences, 18 Tianshui Zhong Road, Lanzhou 730000, China
e-mail: xiayq@licp.cas.cn

Z. Wang
Graduate School of Chinese Academy of Sciences, Beijing 100039, People's Republic of China