Correction to: Strict anaerobic side-stream reactor: effect of the sludge interchange ratio on sludge reduction in a biological nutrient removal process

Roberta Ferrentino¹ · Michela Langone¹ · Roberta Villa¹ · Gianni Andreottola¹

Published online: 28 November 2017

© Springer-Verlag GmbH Germany, part of Springer Nature 2017

Correction to: Environ Sci Pollut Res

<https://doi.org/10.1007/s11356-017-0448-6>

The correct Fig. 1 is shown in this paper.

The original article was corrected.

The online version of the original article can be found at <https://doi.org/10.1007/s11356-017-0448-6>.

✉ Roberta Ferrentino
roberta.ferrentino@unitn.it; ferrentino.roberta@gmail.com

Michela Langone
michela.langone@unitn.it

Roberta Villa
roberta.villa@unitn.it

Gianni Andreottola
gianni.andreottola@unitn.it

¹ Department of Civil, Environmental and Mechanical Engineering,
University of Trento, Via Mesiano 77, 38123 Trento, Italy

Fig. 1 The experimental setup. Q_{IN} wastewater influent flow rate to the SBR, Q_{EFF} wastewater effluent flow rate to the SBR, Q_W excess sludge flow rate, $Q_{IN,DSSR}$ sludge influent flow rate to the DSSR, $Q_{IN,ASSR}$ sludge influent flow rate to the ASSR, $Q_{OUT,ASSR}$ sludge effluent flow rate from the ASSR, Q_{SUP} supernatant flow rate from the DSSR