Dependence of NO₂ sensitivity on thickness of oxide-sensing electrodes for mixed-potential-type sensor using stabilized zirconia

Perumal Elumalai · Vladimir V. Plashnitsa ·
Taro Ueda · Masaharu Hasei · Norio Miura

Published online: 13 February 2008
© Springer-Verlag 2008

Erratum to: Ionics (2007) 13:387–393
DOI: 10.1007/s11581-006-0059-6

This article was accidentally published twice. Please refer to the first publication: Ionics, Volume 12/issue 6, December 2006; p 331–337; DOI 10.1007/s11581-006-0063-x.

Springer apologizes for this mistake.

The online version of the original article can be found at <http://dx.doi.org/10.1007/s11581-006-0059-6>

P. Elumalai · V. V. Plashnitsa · N. Miura (✉)
Art, Science and Technology Center for Cooperative Research,
Kyushu University,
Kasuga-shi,
Fukuoka 816-8580, Japan
e-mail: miura@astec.kyushu-u.ac.jp

T. Ueda
Interdisciplinary Graduate School of Engineering Sciences,
Kyushu University,
Kasuga-shi,
Fukuoka 816-8580, Japan

M. Hasei
R&D Division, Riken Corporation,
Kumagaya-shi,
Saitama 360-8522, Japan