Erratum to: Electromagnetically Modified Filtration of Aluminum Melts—Part I: Electromagnetic Theory and 30 PPI Ceramic Foam Filter Experimental Results

MARK WILLIAM KENNEDY, SHAHID AKHTAR, JON ARNE BAKKEN,
and RAGNHILD E. AUNE

DOI: 10.1007/s11663-013-9968-8

© The Minerals, Metals & Materials Society and ASM International 2013

**Erratum to: METALLURGICAL AND MATERIALS
TRANSACTIONS B, Vol. 44B, 2013, pp. 691-705
DOI: 10.1007/s11663-013-9798-8**

IN Eq. [7], the value of the magnetic permeability of free space, μ_0 , has been incorrectly transcribed from the original manuscript. The value of μ_0 is in fact defined as precisely equal to: $4\pi \times 10^{-7}$ (H/m).

MARK WILLIAM KENNEDY, Chief Technology Officer, is with the Proval Partners S.A., 1004 Lausanne, Switzerland. Contact e-mail: m.kennedy@provalp.com SHAHID AKHTAR, Technical Manager, is with the Hydro Aluminium, Karmøy, 4265 Håvik, Norway. JON ARNE BAKKEN, Professor Emeritus, is with the Department of Material Science and Engineering, Norwegian University of Science and Technology (NTNU), 7491 Trondheim, Norway. RAGNHILD E. AUNE, Professor, is with the Department of Material Science and Engineering, Norwegian University of Science and Technology (NTNU) and also with the Department of Material Science and Engineering, Royal Institute of Technology (KTH), 100 44 Stockholm, Sweden.

The online version of the original article can be found under doi: [10.1007/s11663-013-9798-8](https://doi.org/10.1007/s11663-013-9798-8).

Article published online October 12, 2013.