Erratum to: Effect of CaO Addition on Iron Recovery from Copper Smelting Slags by Solid Carbon

JUNG HO HEO, BYUNG-SU KIM, and JOO HYUN PARK

DOI: 10.1007/s11663-013-9992-8

© The Minerals, Metals & Materials Society and ASM International 2013

Erratum to: METALLURGICAL AND MATERIALS TRANSACTIONS B

DOI: 10.1007/s11663-013-9908-7

THERE is an error in Figure 7(a). The scale of right y-axis for iron recovery (pct) should be corrected as follows.

Therefore, the following should be corrected.

- 1) Abstract; line 11; about 90 pct → about 60 pct
- 2) Table II; 2nd column; iron recovery (7.8, 24.4, 90.0, 24.8) → iron recovery (5.2, 16.2, 60.0, 16.5)
- 3) after Figure 9, line 2; iron recovery (~90 pct) → iron recovery (~60 pct)
- 4) Conclusions; #2, line 7; about 90 pct → about 60 pct

Fig. 7—Recovery of iron from slag as a function of CaO content at 1773 K (1500 °C) (a) and the morphology of iron ingot separated from slag (b).

JUNG HO HEO, Graduate Student, is with the Department of Materials Engineering, Hanyang University, Ansan 426-791, Korea, and also with the School of Materials Science and Engineering, University of Ulsan, Ulsan 680-749, Korea. BYUNG-SU KIM, Senior Researcher, is with the Korea Institute of Geoscience and Mineral Resources (KIGAM), Daejeon 305-350, Korea. JOO HYUN PARK, Professor, is with the Department of Materials Engineering, Hanyang University. Contact e-mail: basicity@hanyang.ac.kr

The online version of the original article can be found under doi: [10.1007/s11663-013-9908-7](https://doi.org/10.1007/s11663-013-9908-7).

Article published online November 19, 2013.