Particle Behavior During the Arc Spraying Process with Cored Wires

W. Tillmann, E. Vogli, M. Abdulgader, M. Gurriss, D. Kuzmin, and S. Turek

Erratum to: Journal of Thermal Spray Technology DOI 10.1007/s11666-008-9272-3

This article was mistakenly published without the following credit line:

This article is an invited paper selected from presentations at the 2008 International Thermal Spray Conference

and has been expanded from the original presentation. It is simultaneously published in *Thermal Spray Crossing Borders, Proceedings of the 2008 International Thermal Spray Conference*, Maastricht, The Netherlands, June 2-4, 2008, Basil R. Marple, Margaret M. Hyland, Yuk-Chiu Lau, Chang-Jiu Li, Rogerio S. Lima, and Ghislain Montavon, Ed., ASM International, Materials Park, OH, 2008.

The online version of the original article can be found under doi:[10.1007/s11666-008-9272-3](https://doi.org/10.1007/s11666-008-9272-3).

W. Tillmann, E. Vogli, and M. Abdulgader, Institute of Materials Engineering, Dortmund University of Technology, Leonhard-Euler-Str. 2, 44227 Dortmund, Germany; and **M. Gurriss, D. Kuzmin, and S. Turek**, Institute of Applied Mathematics, Dortmund University of Technology, Vogelpothsweg 87, 44227 Dortmund, Germany. Contact e-mail: wolfgang.tillmann@udo.edu.