Erratum to: Investigation on the Flexural Creep Stiffness Behavior of PC–ABS Material Processed by Fused Deposition Modeling Using Response Surface Definitive Screening Design

OMAR AHMED MOHAMED^{1,3}, SYED HASAN MASOOD,¹
 and JAHAR LAL BHOWMIK²

1.—Department of Mechanical and Product Design Engineering, Swinburne University of Technology, Hawthorn, VIC, Australia. 2.—Department of Statistics, Data Science and Epidemiology, Swinburne University of Technology, Hawthorn, VIC, Australia. 3.—e-mail: Omar.Ahmed.Mohamed@outlook.com

Erratum to: JOM DOI: 10.1007/s11837-016-2228-z

This article has been updated to correct errors introduced during the production process. The $\pm$ in Eq. 2 has been corrected.

$$\begin{aligned} \text{FCS(MPa)} = & 902.487 - 29.387 \times \left[\frac{(x_1 - 0.2540)}{0.0762} \right] - 250.631 \times \left[\frac{(x_2 - 0.25)}{0.25} \right] + 28.794 \times \left[\frac{(x_3 - 45)}{45} \right] \\ & - 13.417 \times \left[\frac{(x_4 - 45)}{45} \right] - 8.331 \times \left[\frac{(x_5 - 0.5177)}{0.0605} \right] + 218.064 \times \left[\frac{(x_6 - 5)}{5} \right] \\ & + \left[\frac{(x_1 - 0.2540)}{0.0762} \right] \times \left\{ \left[\frac{(x_3 - 45)}{45} \right] \times 59.672 \right\} + \left[\frac{(x_4 - 45)}{45} \right] \times \left\{ \left[\frac{(x_4 - 45)}{45} \right] \times 30.083 \right\} \\ & + \left[\frac{(x_2 - 0.25)}{0.25} \right] \times \left\{ \left[\frac{(x_6 - 5)}{5} \right] \times 232.638 \right\} + \left[\frac{(x_5 - 0.5177)}{0.0605} \right] \times \left\{ \left[\frac{(x_6 - 5)}{5} \right] \times 67.608 \right\} \end{aligned} \quad (2)$$