

ERRATA for "Stability of Cracks in Elastic and in Elastic Plastic Materials,"
 by W.S. Blackburn, International Journal of Fracture Mechanic, Vol. 3,
 No. 3, September 1967, pp.155-164.

- P158 eqn (2) $\mu\bar{D} = (z-\bar{z})\Omega'(z) + K\bar{\Omega}(\bar{z}) - \bar{\Omega}(z) + \frac{1}{4}We^{2it}z$
- P160, eqns (13)-(15) replace $(1+K)\sqrt{C}$ by $M(1+K)\sqrt{C}$
- P161, line 3, replace $\pi\omega\delta$ by $\omega\delta$
 line 7, replace $\pi\omega\delta^2$ by $\mu\delta^2/\pi$
- P162, eqn (17) replace $48\left|\frac{1}{2}W-4iy\Omega''(z)\right|^2$ by $3\left|\frac{1}{2}W-4iy\Omega''(z)\right|^2$
- P165, line 38, replace $w/W > 1/3$ or $-2/3 > w/W$ by $w/W > 1$ or $-2 > w/W$
 line 39, replace $-2/3 < w/W < 1/3$ by $-2 < w/W < 1$
- P167, eqn (37) replace $-Q$ by $-\frac{\pi Q}{Y_\gamma}$
- P168, eqn (41) replace $\log \frac{b-z}{2l} +$ by $\log \frac{b-z}{2l} + \log$