

H.J. BUSSCHER and A.W.J. VAN PELT The possibility of deriving solid-surface free energies from contact-angle measurements with one liquid	815	M.T. LAUGIER Hertzian indentation of ultra-fine grain size WC-Co composites	841
G. MAURIN and D. POTTIER Electrodeposited tellurium with the A7 lattice type	817	T. SATO Effect of composition on glass-forming regions of iron-base alloy powders prepared by water atomization	844
DEREK O. NORTHWOOD and I.O. SMITH Effect of metallurgical condition on the creep behaviour of Ti-13V-11Cr-3Al	820	B. KANTHA REDDY, K. SOMAIAH and V. HARI BABU Growth and glow curves of flux grown NaMgCl <sub>3</sub> crystals	847
E. MÁRQUEZ, R. JIMÉNEZ-GARAY, A. ALEGRÍA and A. ARRUABARRENA Switching electrical power of bulk chalcogenide glassy semiconductors	823	J.E.O. OVRI and T.J. DAVIES Effect of surface condition on the flexural strength of sintered silicon nitride	849
T. TAKI, S. MAEDA, K. OKAMURA, M. SATO and T. MATSUZAWA Oxidation curing mechanism of polycarbosilane fibres by solid-state <sup>29</sup> Si high-resolution NMR	826	J. KREY, K. FRIEDRICH and K.-H. SCHWALBE Fracture toughness and fatigue crack propagation of single fibre-bundle reinforced model composites	851
K. ROHATGI, S.V. PRASAD and P.K. ROHATGI Release of silica-rich particles from rice husk by microbial fermentation	829	M.H.B. STIDDARD Chemiplating of copper sulphide on cadmium and copper: stoichiometry and potential application in solar cells	857
A. WEINBERG and P. SCHWARTZ Twist effects on the mechanical behaviour of Kevlar 29/epoxy strands	832	N. MORITA, T. ENDO, T. SATO and M. SHIMADA TiF <sub>2</sub> with fluorite structure – a new compound	859
S.V. MOHARIL, B.T. DESHMUKH and P.L. MUTHAL Thermoluminescence in polyethylene fibres	835	K.C. GORETTA, J.L. ROUTBORT Effect of aspect ratio on compression of MgO single crystals	862
Z.W. KOWALSKI and D. JERZMAŃSKI New "3S" method to examine surface roughness of broad ion-beam sputtered materials	837	T. SAKAI, H. WATANABE and T. AIKAWA Effects of carbon on phase transformation of β-SiC with Al <sub>2</sub> O <sub>3</sub>	865
I.K. GOPALAKRISHNAN, J.V. YAKHMI and R.M. IYER Electrical conductivity behaviour of Ni <sub>2-x</sub> Cu <sub>x</sub> Mo <sub>2</sub> S <sub>3</sub>	839	M. TOMOZAWA and K. HIRAO Diffusion of water into oxides during microhardness indentation	867

---

#### Corrigendum

C. MURALIDHAR and P.K.C. PILLAI, *J. Mater. Sci. Lett.* **6** (1987) 346.  
On page 347: on line 6, the second frequency value, 1 MHz, should read 1 kHz.

---

#### Errata

B.L. DAVIDSON, I.J. POLMEAR and I.R. DOVER, *J. Mater. Sci. Lett.* **6** (1987) 381.  
On page 382: on line 7, the lead content should read 0.02%.

E.R. MADDRELL, *J. Mater. Sci. Lett.* **6** (1987) 486.  
On page 486: on line 4, the word carbide should be replaced by carbon.

A.K. PRADHAN and R.N.P. CHOUDHARY, *J. Mater. Sci. Lett.* **6** (1987) 1.  
On page 2: the illustrations of figs 1 and 2 should be transposed.

---