Correction to: Acoustic emission signal of fiber-reinforced composite grinding: frequency components and damage pattern recognition

Jinhua Wei¹ · Haoji Wang¹ · Bin Lin^{1,2} · Tianyi Sui¹ · Feifei Zhao¹ · Sheng Fang²

Published online: 14 May 2019

© Springer-Verlag London Ltd., part of Springer Nature 2019

Correction to: The International Journal of Advanced Manufacturing Technology
<https://doi.org/10.1007/s00170-019-03645-x>

The original version of this article contained a mistake.

The arrows and lines in Figs. 1(a) and Fig. 5 are missing.
The correct images are shown below.

The original article has been corrected.

The online version of the original article can be found at <https://doi.org/10.1007/s00170-019-03645-x>

✉ Bin Lin
tdlinbin@126.com

Jinhua Wei
15222527210@163.com

Haoji Wang
18822408206@163.com

Tianyi Sui
tdsuity@163.com

Feifei Zhao
zhaofeifei760521@163.com

Sheng Fang
fangsheng0666@163.com

¹ Key Laboratory of Advanced Ceramics and Machining Technology, Ministry of Education, Tianjin University, Tianjin, China

² Key Laboratory of Advanced Functional Composites, CASC, Beijing, China

Fig. 1 Single-grain grinding experiment. **a** Experiment device setup. **b** Relation between fiber orientation and grinding direction

Fig. 5 SEM images of processed surfaces. **a** Processed surface on grinding direction 1. **b** Zoomed zone of grain vertex of (a). **c, d** Processed surface on direction 2 with tool's heading direction parallel to

fiber bundle side surface. **e, f** Processed surface on direction 2 with tool's heading direction perpendicular to fiber bundle side surface