A rapid fractionation method for heavy metals in soil by continuous-flow sequential extraction assisted by focused microwaves

Tetsuya Nakazato · Mikio Akasaka · Hiroaki Tao

Published online: 17 January 2007

© Springer-Verlag 2007

Unfortunately, there were some typographical errors in this article. The corrections are given below.

In Fig. 3, the label on the y -axis should read “Relative extraction efficiency for heavy metals to BCR batchwise method (%)”.

In Table 2, the concentration units in “Amounts of heavy metals extracted from soil (mg g^{-1})” should be corrected from “ mg g^{-1} ” to “ $\mu\text{g g}^{-1}$ ”.

Fig. 3 Dependence of microwave power and the extractant flow rate on the extraction efficiency for heavy metals in step 1. Microwave power: 0 W (white bars), 10 W (shaded bars), 30 W (dashed bars), and 40 W (filled bars). Flow rates of the extractant in step 1: 0.1 mL min⁻¹ (a and b) and 1.0 mL min⁻¹ (c). Length of soil column: 10 mm (a and c) and 5 mm (b)

The online version of the original article can be found at <http://dx.doi.org/10.1007/s00216-006-0700-2>.

T. Nakazato (✉) · M. Akasaka · H. Tao
Research Institute for Environmental Management Technology,
National Institute of Advanced Industrial Science and Technology
(AIST),
Onogawa 16-1,
Tsukuba 305-8569, Japan
e-mail: tet.nakazato@aist.go.jp

M. Akasaka
Japan Industrial Technology Association,
Higashi 1-1-1,
Tsukuba 305-0046, Japan