

Erratum to: Effect of hydraulic retention time on the performance of down-flow hanging sponge system treating grey wastewater

Ahmed Tawfik · Rifaat Abdel Wahab ·
Azza Al-Asmer · Fatma Matary

Published online: 26 June 2011
© Springer-Verlag 2011

Erratum to: Bioprocess Biosyst Eng
DOI 10.1007/s00449-011-0528-9

Erratum to the conclusion section

Accordingly, it is recommended to operate such a system at an HRT not exceeding 5.8 h and OLR of 3.6 kg COD/m³ day for producing an effluent quality complying for reuse in unrestricted irrigation purposes [39].

39. Tawfik A, Abdel Wahaab R, Al-Asmer A, Matary F (2011) Optimization of down-flow hanging sponge (DHS) system treating grey wastewater for reuse in irrigation purposes. *Int J Sustain Water Environ Syst* 3(1):13–18

The online version of the original article can be found under doi:[10.1007/s00449-011-0528-9](https://doi.org/10.1007/s00449-011-0528-9).

A. Tawfik (✉)
School of Energy Resources and Environmental Engineering,
Egypt-Japan University of Science and Technology (E-Just),
P.O. Box 179, New Borg El Arab City, Alexandria 21934, Egypt
e-mail: Tawfik8@hotmail.com; ahmed.tawfik@ejust.edu.eg

A. Tawfik · R. A. Wahab
Water Pollution Research Department, National Research
Center, El-Behouth St., Dokki, P.O. Box 12622, Cairo, Egypt

A. Al-Asmer · F. Matary
Demitta Branch, Faculty of Science,
Department of Environmental Science,
Mansoura University, Mansoura, Egypt