Berg Huettenmaenn Monatsh (2019) Vol. 164 (12): 557–558
<https://doi.org/10.1007/s00501-019-00919-5>
© Austrian Society for Metallurgy of Metals (ASMET) and
Bergmännischer Verband Österreich (BVÖ) 2019

BHM Berg- und
Hüttenmännische
Monatshefte

Erratum to: Internal Fractures After Blasting Confined Rock and Mortar Cylinders

I. Kukolj¹, B. Oberdorfer², and F. Ouchterlony¹

¹Chair of Mining Engineering and Mineral Economics, Montanuniversitaet Leoben, Leoben, Austria

²Österreichisches Gießerei Institut (ÖGI), Montanuniversitaet Leoben, Leoben, Austria

Published online November 18, 2019

Erratum to:

Berg Huettenmaenn Monatsh 2019

<https://doi.org/10.1007/s00501-019-00899-6>

Unfortunately there was a mistake concerning Figs. 6 and 7 as published in Issue 10.

Please find here the corrected version.

We apologize for any inconvenience that might have occurred in this connection.

The online version of the original article can be found under
<https://doi.org/10.1007/s00501-019-00899-6>.

I. Kukolj (✉)

Chair of Mining Engineering and Mineral Economics,
Montanuniversitaet Leoben,
Erzherzog-Johann-Straße 3,
8700 Leoben, Austria
ivan.kukolj@unileoben.ac.at

Fig. 6: Deformation zones and crack patterns near the blast hole in the thin sections (SEM images). (a, b Granite, 12 g/m (bl240). c, d Mortar, 12 g/m PETN (bl20))

Fig. 7: Selected results of the fracture surface analysis in CloudCompare (mortar, 12 g/m PETN (bl20))