CORRECTION



Correction to: A wake field design system utilizing a database analysis to enhance the performance of energy saving devices and propeller

Yasuo Ichinose¹ · Yusuke Tahara¹

Published online: 11 September 2019 © The Japan Society of Naval Architects and Ocean Engineers (JASNAOE) 2019

Correction to: Journal of Marine Science and Technology https://doi.org/10.1007/s00773-018-0611-x **Publisher's Note** Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

In the original publication, Table 2 has been published incorrectly. The correct version of Table 2 is provided in this correction.

Table 2 Correspondence of parameters of DB1

	$[L_{\rm PP}, B, d]$	$[\xi,\eta,\zeta]$
1	[81.0, 14.2, 3.8]	[0, 0, 0]
2	[83.0, 13.8, 3.8]	[1, 0, 0]
3	[83.0, 14.5, 3.8]	[1, 1, 0]
4	[79.0, 14.5, 3.8]	[0, 1, 0]
(5)	[73.0, 12.8, 4.8]	[0, 0, 1]
6	[83.0, 12.8, 4.8]	[1, 0, 1]
7	[77.0, 13.8, 4.8]	[1, 1, 1]
8	[73.0, 14.5, 4.8]	[0, 1, 1]
⑤⑥⑦	[79.0, 14.5, 3.8] [73.0, 12.8, 4.8] [83.0, 12.8, 4.8] [77.0, 13.8, 4.8]	[0, 1, 0] [0, 0, 1] [1, 0, 1] [1, 1, 1]

The original article can be found online at https://doi.org/10.1007/s00773-018-0611-x.

National Maritime Research Institute, Mitaka, Japan

