## CORRECTION



## Correction: Characterization of microfluidic trap and mixer module for rapid fluorescent tagging of microplastics

Seongcheol Shin $^1\cdot$  Boeun Jeon $^1\cdot$  Wonkyu Kang $^1\cdot$  Cholong Kim $^1\cdot$  Jonghoon Choi $^2\cdot$  Sung Chul Hong $^3\cdot$  Hyun Ho Lee $^1$ 

© The Author(s), under exclusive licence to Springer-Verlag GmbH Germany, part of Springer Nature 2024

Correction: Microfluidics and Nanofluidics (2024) 28:18 https://doi.org/10.1007/s10404-024-02716-0

In this article the wrong figure appeared as Fig. 1; the Fig. 1 should have appeared as shown below. The original article has been corrected.

**Publisher's Note** Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

The original article can be found online at https://doi.org/10.1007/s10404-024-02716-0.

Published online: 06 May 2024



Department of Chemical Engineering, Myongji University, Yongin 17058, Republic of Korea

School of Integrative Engineering, Chung-Ang University, Seoul 06974, Republic of Korea

Nanotechnology and Advanced Materials Engineering, Sejong University, Seoul 05006, Republic of Korea

Fig. 1 a Optical microscopy image of cryo-grinded and mesh sieved randomly shaped PE MPs and PP MPs, and b specifications of PDMS microfuidic trap module fabrication by photolithography using SU-8 master fabrication



