Correction to: Seismic soil-structure interaction analysis of structure with shallow foundation using response spectrum method

Zhidong Gao¹ · Mi Zhao¹ · Xiuli Du¹ · Xu Zhao¹

Published online: 5 June 2020
© Springer Nature B.V. 2020

Correction to: Bulletin of Earthquake Engineering
<https://doi.org/10.1007/s10518-020-00827-x>

This erratum is being published to correct two reference mistake and equation symbol in the paper.

Before correction:

GB (50011-2010) Code for Seismic Design of Buildings China. Architecture and Building Press, Beijing (**in Chinese**).

Wolf JP, Paronesso A (1991) Errata: Consistent lumped-parameter models for unbounded soil. Earthq Eng Struct Dyn 20(6):597–599.

$$\text{Equation (29): } \eta = 1.0 + \frac{0.05 - \zeta}{0.08 - 1.6\zeta}.$$

After correction:

GB (2014) Code for Seismic Design of Urban Rail Transit Structures (GB 50909-2014). China Planning Press, Beijing (**in Chinese**).

Wolf JP (1991) Consistent lumped-parameter models for unbounded soil: physical representation. Earthq Eng Struct Dyn 20(1):11–32.

$$\text{Equation (29): } \eta = 1.0 + \frac{0.05 - \zeta}{0.08 + 1.6\zeta}.$$

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

The original article can be found online at <https://doi.org/10.1007/s10518-020-00827-x>.

✉ Mi Zhao
zhaomi@bjut.edu.cn

¹ Key Laboratory of Urban Security and Disaster Engineering of Ministry of Education, Beijing University of Technology, Beijing 100124, China